



nix.dev

nix.dev contributors

Jan 01, 2026

CONTENTS

1	Install Nix	1
1.1	Verify installation	2
2	Tutorials	3
2.1	First steps	3
2.1.1	Ad hoc shell environments	3
2.1.2	Reproducible interpreted scripts	7
2.1.3	Declarative shell environments with <code>shell.nix</code>	8
2.1.4	Towards reproducibility: pinning Nixpkgs	11
2.2	Nix language basics	12
2.2.1	Overview	13
2.2.2	Names and values	16
2.2.3	Functions	26
2.2.4	Function libraries	31
2.2.5	Impurities	34
2.2.6	Derivations	36
2.2.7	Worked examples	37
2.2.8	References	39
2.2.9	Next steps	39
2.3	Packaging existing software with Nix	40
2.3.1	Introduction	40
2.3.2	Your first package	41
2.3.3	A package with dependencies	44
2.3.4	Finding packages	48
2.3.5	Fixing build failures	50
2.3.6	A successful build	52
2.3.7	References	52
2.3.8	Next steps	52
2.4	Package parameters and overrides with <code>callPackage</code>	52
2.4.1	Overview	52
2.4.2	Automatic function calls	53
2.4.3	Parameterised builds	53
2.5	Overrides	55
2.5.1	Interdependent package sets	55
2.5.2	Summary	57
2.5.3	References	57
2.5.4	Next steps	57
2.6	Working with local files	57
2.6.1	File sets	57
2.6.2	Example project	58
2.6.3	Adding files to the Nix store	59
2.6.4	Difference	60
2.6.5	Missing files	62
2.6.6	Union (explicitly exclude files)	63

2.6.7	Filter	64
2.6.8	Union (explicitly include files)	64
2.6.9	Matching files tracked by Git	65
2.6.10	Intersection	66
2.6.11	Conclusion	67
2.7	Cross compilation	67
2.7.1	What do you need?	67
2.7.2	Platforms	67
2.7.3	What's a target platform?	67
2.7.4	Determining the host platform config	68
2.7.5	Choosing the host platform with Nix	68
2.7.6	Specifying the host platform	69
2.7.7	Cross compiling for the first time	70
2.7.8	Real-world cross compiling of a Hello World example	70
2.7.9	Developer environment with a cross compiler	71
2.7.10	Next steps	72
2.8	Module system	72
2.8.1	What do you need?	73
2.8.2	How long will it take?	73
2.9	NixOS	96
2.9.1	Creating NixOS images	96
2.9.2	Testing and deploying NixOS configurations	97
2.9.3	Scaling up	97
3	Guides	133
3.1	Recipes	133
3.1.1	Configure Nix to use a custom binary cache	133
3.1.2	Automatic environment activation with <code>direnv</code>	134
3.1.3	Dependencies in the development shell	135
3.1.4	Automatically managing remote sources with <code>npins</code>	136
3.1.5	Setting up a Python development environment	139
3.1.6	Setting up post-build hooks	141
3.1.7	Continuous integration with GitHub Actions	143
3.2	Best practices	144
3.2.1	URLs	144
3.2.2	Recursive attribute set <code>rec { ... }</code>	145
3.2.3	<code>with scopes</code>	145
3.2.4	<code><...></code> lookup paths	146
3.2.5	Reproducible Nixpkgs configuration	147
3.2.6	Updating nested attribute sets	147
3.2.7	Reproducible source paths	148
3.3	Troubleshooting	148
3.3.1	What to do if a binary cache is down or unreachable?	149
3.3.2	How to force Nix to re-check if something exists in the binary cache?	149
3.3.3	How to fix: <code>error: querying path in database: database disk image is malformed</code>	149
3.3.4	How to fix: <code>error: current Nix store schema is version 10, but I only support 7</code>	149
3.3.5	How to fix: <code>writing to file: Connection reset by peer</code>	149
3.3.6	macOS update breaks Nix installation	149
3.4	Frequently Asked Questions	150
3.4.1	Nix	150
3.4.2	NixOS	150
4	Reference	153
4.1	Glossary	153
4.2	Nix reference manual	154
4.3	Further reading	154

4.3.1	Nix language tutorials	154
4.3.2	Other articles	155
4.3.3	Other videos	155
4.4	Pinning Nixpkgs	156
4.4.1	Possible URL values	156
4.4.2	Examples	156
4.4.3	Finding specific commits and releases	157
5	Concepts	159
5.1	Flakes	159
5.1.1	What are flakes?	159
5.1.2	Should I use flakes in my project?	160
5.1.3	Further reading	164
5.2	Frequently Asked Questions	164
5.2.1	What is the origin of the name Nix?	164
5.2.2	What are flakes?	164
5.2.3	Which channel branch should I use?	164
5.2.4	Are there any impurities left in sandboxed builds?	165
6	Contributing	167
6.1	How to contribute	167
6.1.1	Getting started	167
6.1.2	Report an issue	168
6.1.3	Contribute to Nix	168
6.1.4	Contribute to Nixpkgs	169
6.1.5	Contribute to NixOS	169
6.2	How to get help	169
6.3	How to get help	169
6.3.1	How to find maintainers	169
6.3.2	Which communication channels to use	170
6.3.3	Other venues	170
6.4	Contributing documentation	171
6.4.1	Getting started	171
6.4.2	Feedback	171
6.4.3	Licensing and attribution	172
7	Acknowledgements	181
7.1	Sponsoring	181
7.2	History	181
	Index	183

INSTALL NIX

Requirements:

- Prior to installation, you might first need to install `xz-utils` or similar for decompressing the Nix binary tarball (`.tar.xz`) that will be downloaded via the scripts below.

Linux

Install Nix via the recommended [multi-user installation](#)³:

```
$ curl -L https://nixos.org/nix/install | sh -s -- --daemon
```

On Arch Linux, you can alternatively [install Nix through pacman](#)⁴.

On Fedora, you can [install Nix via dnf](#)⁵.

macOS

Install Nix via the recommended [multi-user installation](#)⁶:

```
$ curl -L https://nixos.org/nix/install | sh
```

Important

Updating to macOS 15 Sequoia

If you recently updated to macOS 15 Sequoia and are getting the error

```
error: the user '_nixbld1' in the group 'nixbld' does not exist
```

when running Nix commands, refer to GitHub issue [NixOS/nix#10892](#)⁷ for instructions to fix your installation without reinstalling.

Windows (WSL2)

Install Nix via the recommended [single-user installation](#)⁸:

```
$ curl -L https://nixos.org/nix/install | sh -s -- --no-daemon
```

However, if you have [systemd support](#)⁹ enabled, install Nix via the recommended [multi-user installation](#)¹⁰:

³ <https://nix.dev/manual/nix/stable/installation/multi-user.html>

⁴ <https://wiki.archlinux.org/title/Nix#Installation>

⁵ <https://src.fedoraproject.org/rpms/nix>

⁶ <https://nix.dev/manual/nix/stable/installation/multi-user.html>

⁷ <https://github.com/NixOS/nix/issues/10892>

⁸ <https://nix.dev/manual/nix/stable/installation/single-user.html>

⁹ <https://learn.microsoft.com/en-us/windows/wsl/wsl-config#systemd-support>

¹⁰ <https://nix.dev/manual/nix/stable/installation/multi-user.html>

```
$ curl -L https://nixos.org/nix/install | sh -s -- --daemon
```

Docker

Start a Docker shell with Nix:

```
$ docker run -it nixos/nix
```

Or start a Docker shell with Nix exposing a `workdir` directory:

```
$ mkdir workdir  
$ docker run -it -v $(pwd)/workdir:/workdir nixos/nix
```

The `workdir` example from above can also be used to start hacking on Nixpkgs:

```
$ git clone git@github.com:NixOS/nixpkgs  
$ docker run -it -v $(pwd)/nixpkgs:/nixpkgs nixos/nix  
bash-5.1# nix-build -I nixpkgs=/nixpkgs -A hello  
bash-5.1# find ./result # this symlink points to the build package
```

1.1 Verify installation

Check the installation by opening a **new terminal** and typing:

```
$ nix --version  
nix (Nix) 2.11.0
```

TUTORIALS

These sections contain a series of lessons to get started.

2.1 First steps

This tutorial series is where you should start learning Nix.

In these lessons, you will use basic Nix commands to obtain almost any piece of software, create development environments on the fly, and learn how to make reproducible scripts. You will also learn to read the Nix language, and later use it to build portable, reproducible development environments.

2.1.1 Ad hoc shell environments

In a Nix shell environment, you can immediately use any program packaged with Nix, without installing it permanently.

You can also share the command invoking such a shell with others, and it will work on all Linux distributions, WSL, and macOS¹.

Create a shell environment

Once you *install Nix* (page 1), you can use it to create new *shell environments* with programs that you want to use.

In this section you will run two exotic programs called `cowsay` and `lolcat` that you will probably not have installed on your machine:

```
$ cowsay no can do
The program 'cowsay' is currently not installed.

$ echo no chance | lolcat
The program 'lolcat' is currently not installed.
```

Use `nix-shell` with the `-p` (`--packages`) option to specify that we need the `cowsay` and `lolcat` packages:

Note

The first invocation of `nix-shell` for these packages may take a while to download all dependencies.

```
$ nix-shell -p cowsay lolcat
these 3 derivations will be built:
/nix/store/zx1j8gchgwzfn7sr4r8yxb7a0afkjdgd-builder.pl.drv
/nix/store/h9sbaa2k8ivnihw2czhl5b58k0f7fsfh-lolcat-100.0.1.drv
...
```

(continues on next page)

¹ Not all packages are supported for both Linux and macOS. Especially support for graphical programs may vary.

(continued from previous page)

```
[nix-shell:~]$
```

Within the Nix shell, you can use the programs provided by these packages:

```
[nix-shell:~]$ cowsay Hello, Nix! | lolcat
```

Type `exit` or press `CTRL-D` to exit the shell, and the programs won't be available anymore.

```
[nix-shell:~]$ exit
exit

$ cowsay no more
The program 'cowsay' is currently not installed.

$ echo all gone | lolcat
The program 'lolcat' is currently not installed.
```

Running programs once

You can go even faster, by running any program directly:

```
$ nix-shell -p cowsay --run "cowsay Nix"
```

If the command consists only of the program name, no quotes are needed:

```
$ nix-shell -p hello --run hello
```

Search for packages

What can you put in a shell environment? If you can think of it, there's probably a Nix package of it.

Tip

Enter the program name you want to run in search.nixos.org¹¹ to find packages that provide it.

For the following example, find the package names for these programs:

- `git`
- `nvim`
- `npm`

In the search results, each item shows the package name, and the details list the available programs.²

Run any combination of programs

Once you have the package name, you can start a shell with that package. The `-p` (`--packages`) argument can take multiple package names.

Start a Nix shell with the packages providing `git`, `nvim`, and `npm`. Again, the first invocation may take a while to download all dependencies.

¹¹ <https://search.nixos.org/packages>

² A package name is not the same as a program name. Many packages provide multiple programs, or no programs at all if they are libraries. Even for packages that provide exactly one program, the package and program name are not necessarily the same.

```
$ nix-shell -p git neovim nodejs
these 9 derivations will be built:
/nix/store/7gz8jyn99kw4k74bgm4qp6z487l5ap06-packdir-start.drv
/nix/store/d6fkgxc3b04m85wrhg6j0l5y0ray82l7-packdir-opt.drv
/nix/store/da6njv7r0zzc2n54n2j54g2a5sbi4a5i-manifest.vim.drv
/nix/store/zs4jb2ybr4rcyzwq0dag9rlhlc368h6-builder.pl.drv
/nix/store/g8sl2xnsshfrz9f39ki94k8p15vp3xd7-vim-pack-dir.drv
/nix/store/jmxkg8b1psk52awsvfziy9nq6dwmxmjp-luajit-2.1.0-2022-10-04-env.drv
/nix/store/kn83q8yk6ds74zgyklrjhvv5wkv5wmch-python3-3.10.9-env.drv
/nix/store/m445wn3vizcgg7syna2cdkks3kk1gq8-neovim-ruby-env.drv
/nix/store/r2wa882mw99c311a4my7hcis9lq3kp3v-neovim-0.8.1.drv
these 151 paths will be fetched (186.43 MiB download, 1018.20 MiB unpacked):
/nix/store/046zx1xhq4srm3ggafkymx794bn1jksc-bzip2-1.0.8
/nix/store/0p1jxcb7b4p8jhhlf8qnjc4cqwy89460-unibilium-2.1.1
/nix/store/0q4fpmqmg8liqraj7zidylcyd062f6z0-perl5.36.0-URI-5.05
...

[nix-shell:~]$
```

Check package versions

Check that you have the specific version of these programs provided by Nix, even if you had any of them already installed on your machine.

```
[nix-shell:~]$ which git
/nix/store/3cdi52xh6lk3h1fb51jkxs3p561p37wg-git-2.38.3/bin/git

[nix-shell:~]$ git --version
git version 2.38.3

[nix-shell:~]$ which nvim
/nix/store/ynskzkgkf07lmrrs3cl2kzr9ah487lwab-neovim-0.8.1/bin/nvim

[nix-shell:~]$ nvim --version | head -1
NVIM v0.8.1

[nix-shell:~]$ which npm
/nix/store/q12w83z0i5pi1y0m6am7qmw1r73228sh-nodejs-18.12.1/bin/npm

[nix-shell:~]$ npm --version
8.19.2
```

Nested shell sessions

If you need an additional program temporarily, you can run a nested Nix shell. The programs provided by the specified packages will be added to the current environment.

```
[nix-shell:~]$ nix-shell -p python3
this path will be fetched (11.42 MiB download, 62.64 MiB unpacked):
/nix/store/pwy30a7siqrkki9r7xd1lksyv9fg4l1r-python3-3.10.11
copying path '/nix/store/pwy30a7siqrkki9r7xd1lksyv9fg4l1r-python3-3.10.11' from
↳ 'https://cache.nixos.org'...

[nix-shell:~]$ python --version
Python 3.10.11
```

Exit the shell as usual to return to the previous environment.

Towards reproducibility

These shell environments are very convenient, but the examples so far are not reproducible yet. Running these commands on another machine may fetch different versions of packages, depending on when Nix was installed there.

What do we mean by reproducible? A fully reproducible example would give exactly the same results no matter when or where you run the command. The environment provided would be identical each time.

The following example creates a fully reproducible environment. You can run it anywhere, anytime to obtain the exact same version of the `git`.

```
$ nix-shell -p git --run "git --version" --pure -I
↳nixpkgs=https://github.com/NixOS/nixpkgs/tarball/2a601aafdc5605a5133a2ca506a34a3a73377247
...
git version 2.33.1
```

There are three things going on here:

1. `--run` executes the given [Bash command](#)¹² within the environment created by Nix, and exits when it's done.

You can use this with `nix-shell` whenever you want to quickly run a program you don't have installed on your machine.

2. `--pure` discards most environment variables set on your system when running the shell.

It means that only the `git` provided by Nix is available inside that shell. This is useful for simple one-liners such as in the example. While developing, however, you will usually want to have your editor and other tools around. Therefore we recommend to omit `--pure` for development environments, and to add it only when the extra isolation is needed.

3. `-I` determines what to use as a source of package declarations.

Here we provided a [specific Git revision of nixpkgs](#)¹³, leaving no doubt about which version of the packages in that collection will be used.

References

- [Nix manual: `nix-shell`](#)¹⁴ (or run `man nix-shell`)
- [Nix manual: `-I` option](#)¹⁵

Next steps

- [Reproducible interpreted scripts](#) (page 7) – use Nix for reproducible scripts
- [Nix language basics](#) (page 12) – learn reading the Nix language, which is used to declare packages and configurations
- [Declarative shell environments with `shell.nix`](#) (page 8) – create reproducible shell environments with a declarative configuration file
- [Towards reproducibility: pinning `Nixpkgs`](#) (page 11) – learn different ways of specifying exact versions of package sources

If you're done trying out Nix for now, you may want to free up some disk space occupied by the different versions of programs you downloaded by running the examples:

```
$ nix-collect-garbage
```

¹² <https://www.gnu.org/software/bash/manual/bash.html#Shell-Commands>

¹³ <https://github.com/NixOS/nixpkgs/tree/2a601aafdc5605a5133a2ca506a34a3a73377247>

¹⁴ <https://nix.dev/manual/nix/stable/command-ref/nix-shell>

¹⁵ <https://nix.dev/manual/nix/stable/command-ref/opt-common.html#opt-I>

2.1.2 Reproducible interpreted scripts

In this tutorial, you will learn how to use Nix to create and run reproducible interpreted scripts, also known as shebang¹⁶ scripts.

Requirements

- A working *Nix installation* (page 1)
- Familiarity with *Bash*¹⁷

A trivial script with non-trivial dependencies

Take the following script, which fetches the content XML of a URL, converts it to JSON, and formats it for better readability:

```
#!/bin/bash

curl https://github.com/NixOS/nixpkgs/releases.atom | xml2json | jq .
```

It requires the programs `curl`, `xml2json`, and `jq`. It also requires the `bash` interpreter. If any of these dependencies are not present on the system running the script, it will fail partially or altogether.

With Nix, we can declare all dependencies explicitly, and produce a script that will always run on any machine that supports Nix and the required packages taken from Nixpkgs.

The script

A *shebang*¹⁸ determines which program to use for running an interpreted script.

We will use the shebang line `#!/usr/bin/env nix-shell`.

`env`¹⁹ is a program available on most modern Unix-like operating systems at the file system path `/usr/bin/env`. It takes a command name as argument and will run the first executable by that name it finds in the directories listed in the environment variable `$PATH`.

We use `nix-shell` as a *shebang interpreter*²⁰. It takes the following parameters relevant for our use case:

- `-i` tells which program to use for interpreting the rest of the file
- `--pure` excludes most environment variables when the script is run
- `-p` lists packages that should be present in the interpreter's environment
- `-I` explicitly sets the *search path*²¹ for packages

More details on the options can be found in the *nix-shell reference documentation*²².

Create a file named `nixpkgs-releases.sh` with the following content:

```
#!/usr/bin/env nix-shell
#! nix-shell -i bash --pure
#! nix-shell -p bash cacert curl jq python3Packages.xmljson
#! nix-shell -I
↪nixpkgs=https://github.com/NixOS/nixpkgs/archive/2a601aafdc5605a5133a2ca506a34a3a73377247.tar.g

curl https://github.com/NixOS/nixpkgs/releases.atom | xml2json | jq .
```

The first line is a standard shebang. The additional shebang lines are a Nix-specific construct:

¹⁶ [https://en.wikipedia.org/wiki/Shebang_\(Unix\)](https://en.wikipedia.org/wiki/Shebang_(Unix))

¹⁷ <https://www.gnu.org/software/bash/>

¹⁸ [https://en.wikipedia.org/wiki/Shebang_\(Unix\)](https://en.wikipedia.org/wiki/Shebang_(Unix))

¹⁹ <https://pubs.opengroup.org/onlinepubs/9699919799/utilities/env.html>

²⁰ <https://nix.dev/manual/nix/stable/command-ref/nix-shell.html#use-as-a-interpretor>

²¹ <https://nix.dev/manual/nix/stable/command-ref/opt-common.html#opt-I>

²² <https://nix.dev/manual/nix/stable/command-ref/nix-shell.html#options>

- With the `-i` option, `bash` is specified as the interpreter for the rest of the file.
- In this case, the `--pure` option is enabled to prevent the script from implicitly using programs that may already exist on the system on which the script is run.
- The `-p` option lists the packages required for the script to run.

The command `xml2json` is provided by the package `python3Packages.xmljson`, while `bash`, `jq`, and `curl` are provided by packages of the same name. `cacert` must be present for SSL authentication to work.

Tip

Use search.nixos.org²³ to find packages providing the program you need.

- The parameter of `-I` refers to a specific Git commit of the Nixpkgs repository.

This ensures that the script will always run with the exact same package versions, everywhere.

Make the script executable:

```
chmod +x nixpkgs-releases.sh
```

Run the script:

```
./nixpkgs-releases.sh
```

Next steps

- *Nix language basics* (page 12) to learn about the Nix language, which is used to declare packages and configurations.
- *Declarative shell environments with `shell.nix`* (page 8) to create reproducible shell environments with a declarative configuration file.
- *Garbage Collection*²⁴ – free up storage used by the programs made available through Nix

2.1.3 Declarative shell environments with `shell.nix`

Overview

Declarative shell environments allow you to:

- Automatically run bash commands during environment activation
- Automatically set environment variables
- Put the environment definition under version control and reproduce it on other machines

What will you learn?

In the *Ad hoc shell environments* (page 3) tutorial, you learned how to imperatively create shell environments using `nix-shell -p`. This is great when you want to quickly access tools without installing them permanently. You also learned how to execute that command with a specific Nixpkgs revision using a Git commit as an argument, to recreate the same environment used previously.

In this tutorial we'll take a look at how to create reproducible shell environments with a declarative configuration in a *Nix file*. This file can be shared with anyone to recreate the same environment on a different machine.

²³ <https://search.nixos.org/packages>

²⁴ <https://nix.dev/manual/nix/stable/package-management/garbage-collection.html>

How long will it take?

30 minutes

What do you need?

- Familiarity with the Unix shell
- A rudimentary understanding of the *Nix language* (page 12)

Entering a temporary shell

Suppose we want an environment where `cowsay` and `lolcat` are available. The simplest possible way to accomplish this is via the `nix-shell -p` command:

```
$ nix-shell -p cowsay lolcat
```

This command works, but there's a number of drawbacks:

- You have to type out `-p cowsay lolcat` every time you enter the shell.
- It doesn't (ergonomically) allow you any further customization of your shell environment.

A better solution is to create our shell environment from a `shell.nix` file.

A basic `shell.nix` file

Create a file called `shell.nix` with these contents:

```
1 let
2   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-24.05";
3   pkgs = import nixpkgs { config = {}; overlays = []; };
4 in
5
6 pkgs.mkShellNoCC {
7   packages = with pkgs; [
8     cowsay
9     lolcat
10  ];
11 }
```

Detailed explanation

We use a version of *Nixpkgs pinned to a release branch* (page 156). If you followed the *Ad hoc shell environments* (page 3) tutorial and don't want to download all dependencies again, specify the exact same revision as in the section *Towards reproducibility* (page 6):

```
1 let
2   nixpkgs = fetchTarball
3     ↪ "https://github.com/NixOS/nixpkgs/tarball/2a601aafdc5605a5133a2ca506a34a3a73377247";
4     ↪ ";
5   pkgs = import nixpkgs { config = {}; overlays = []; };
6 in
```

We explicitly set `config` and `overlays` to avoid them being inadvertently overridden by *global configuration*²⁵.

`mkShellNoCC` is a function that takes as an argument an attribute set. Here we give it an attribute `packages` with a list containing two items from the `pkgs` attribute set.

²⁵ <https://nixos.org/manual/nixpkgs/stable/#chap-packageconfig>

Side note on mkShell

`nix-shell` and `mkShell` were originally conceived as a way to construct a shell environment containing the tools needed to debug package builds²⁶, such as Make or GCC. Only later did it become widely used as a general way to make temporary environments for other purposes. `mkShellNoCC` is a function that produces such an environment, but without a compiler toolchain.

You may encounter examples of `mkShell` or `mkShellNoCC` that add packages to the `buildInputs` or `nativeBuildInputs` attributes instead. `mkShellNoCC` is a wrapper around `mkDerivation`²⁷, so it takes the same arguments as `mkDerivation`, such as `buildInputs` or `nativeBuildInputs`. The `packages` attribute argument to `mkShellNoCC` is simply an alias for `nativeBuildInputs`.

Enter the environment by running `nix-shell` in the same directory as `shell.nix`:

Note

The first invocation of `nix-shell` on this file may take a while to download all dependencies.

```
$ nix-shell
[nix-shell]$ cowsay hello | lolcat
```

`nix-shell` by default looks for a file called `shell.nix` in the current directory and builds a shell environment from the Nix expression in this file. Packages defined in the `packages` attribute will be available in `$PATH`.

Environment variables

You may want to automatically export certain environment variables when you enter a shell environment.

Set `GREETING` so it can be used in the shell environment:

```
let
  nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-24.05";
  pkgs = import nixpkgs { config = {}; overlays = []; };
in

pkgs.mkShellNoCC {
  packages = with pkgs; [
    cowsay
    lolcat
  ];

+  GREETING = "Hello, Nix!";
}
```

Any attribute name passed to `mkShellNoCC` that is not reserved otherwise and has a value which can be coerced to a string will end up as an environment variable.

Try it out. Exit the shell by typing `exit` or pressing `Ctrl+D`, then start it again with `nix-shell`.

```
[nix-shell]$ echo $GREETING
```

Warning

Some variables are protected from being set as described above.

For example, the shell prompt format for most shells is set by the `PS1` environment variable, but `nix-shell` already sets this by default, and will ignore a `PS1` attribute set in the argument.

²⁶ <https://nixos.org/manual/nixpkgs/stable/#sec-tools-of-stdenv>

²⁷ <https://nixos.org/manual/nixpkgs/stable/#sec-pkgs-mkShell>

If you need to override these protected environment variables, use the `shellHook` attribute as described in the next section.

Startup commands

You may want to run some shell commands before entering the interactive shell environment. These commands can be placed in the `shellHook` attribute provided to `mkShellNoCC`.

Set `shellHook` to output a colorful greeting:

```
let
  nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-24.05";
  pkgs = import nixpkgs { config = {}; overlays = []; };
in

pkgs.mkShellNoCC {
  packages = with pkgs; [
    cowsay
    lolcat
  ];

  GREETING = "Hello, Nix!";
+
+ shellHook = ''
+   echo $GREETING | cowsay | lolcat
+ '';
}
```

Try it again. Exit the shell by typing `exit` or pressing `Ctrl+D`, then start it again with `nix-shell` to observe the effect.

References

- [mkShell documentation](#)²⁸
- [Nixpkgs shell functions and utilities](#)²⁹ documentation
- [nix-shell documentation](#)³⁰

Next steps

- *Nix language basics* (page 12)
- *Automatic environment activation with direnv* (page 134)
- *Dependencies in the development shell* (page 135)
- *Automatically managing remote sources with npins* (page 136)

2.1.4 Towards reproducibility: pinning Nixpkgs

In various Nix examples, you'll often see the following:

```
1 { pkgs ? import <nixpkgs> {} } :
2
3 ...
```

²⁸ <https://nixos.org/manual/nixpkgs/stable/#sec-pkgs-mkShell>

²⁹ <https://nixos.org/manual/nixpkgs/stable/#ssec-stdenv-functions>

³⁰ <https://nix.dev/manual/nix/stable/command-ref/nix-shell>

Note

`<nixpkgs>` points to the file system path of some revision of *Nixpkgs*. Find more information on *lookup paths* (page 25) in *Nix language basics* (page 12).

This is a **convenient** way to quickly demonstrate a Nix expression and get it working by importing Nix packages.

However, **the resulting Nix expression is not fully reproducible**.

Pinning packages with URLs inside a Nix expression

To create **fully reproducible** Nix expressions, we can pin an exact version of Nixpkgs.

The simplest way to do this is to fetch the required Nixpkgs version as a tarball specified via the relevant Git commit hash:

```
1 { pkgs ? import (fetchTarball
  ↪ "https://github.com/NixOS/nixpkgs/archive/06278c77b5d162e62df170fec307e83f1812d94b.tar.gz"
  ↪ ) } { }
2 } :
3
4 . . .
```

Picking the commit can be done via status.nixos.org³¹, which lists all the releases and the latest commit that has passed all tests.

When choosing a commit, it is recommended to follow either

- the **latest stable NixOS** release by using a specific version, such as `nixos-21.05`, or
- the latest **unstable release** via `nixos-unstable`.

Next steps

- For more examples and details of the different ways to pin `nixpkgs`, see *Pinning Nixpkgs* (page 156).
- *Automatically managing remote sources with npins* (page 136)

2.2 Nix language basics

The Nix language is designed for conveniently creating and composing *derivations* – precise descriptions of how contents of existing files are used to derive new files. It is a domain-specific, purely functional, lazily evaluated, dynamically typed programming language.

Notable uses of the Nix language

- *Nixpkgs*
The largest, most up-to-date software distribution in the world, and written in the Nix language.
- *NixOS*
A Linux distribution that can be configured fully declaratively and is based on Nix and Nixpkgs.
Its underlying modular configuration system is written in the Nix language, and uses packages from Nixpkgs. The operating system environment and services it provides are configured with the Nix language.

You may quickly encounter Nix language expressions that look very complicated. As with any programming language, the required amount of Nix language code closely matches the complexity of the problem it is supposed to solve, and

³¹ <https://status.nixos.org/>

reflects how well the problem – and its solution – is understood. Building software is a complex undertaking, and Nix both *exposes* and *allows managing* this complexity with the Nix language.

Yet, the Nix language itself has only a few basic concepts that will be introduced in this tutorial, and which can be combined arbitrarily. What may look complicated comes not from the language, but from how it is used.

2.2.1 Overview

This is an introduction to **reading the Nix language**, for the purpose of following other tutorials and examples.

Using the Nix language in practice entails multiple things:

- Language: syntax and semantics
- Libraries: `builtins` and `pkgs.lib`
- Developer tools: testing, debugging, linting, formatting, ...
- Generic build mechanisms: `stdenv.mkDerivation`, **build helpers**, ...
- Composition and configuration mechanisms: `override`, `overrideAttrs`, **overlays**, `callPackage`, ...
- Ecosystem-specific packaging mechanisms: `buildGoModule`, `buildPythonApplication`, ...
- NixOS module system: `config`, `option`, ...

This tutorial only covers the most important language features, briefly discusses libraries, and at the end will direct you to reference material and resources on the other components.

What will you learn?

This tutorial should enable you to read typical Nix language code and understand its structure. Its goal is to highlight where the Nix language may differ from languages you are used to.

It therefore shows the most common and distinguishing patterns in the Nix language:

- *Assigning names and accessing values* (page 16)
- Declaring and calling *functions* (page 26)
- *Built-in and library functions* (page 31)
- *Impurities* (page 34) to obtain build inputs
- *Derivations* (page 36) that describe build tasks

Important

This tutorial *does not* explain all Nix language features in detail and *does not* go into specifics of syntactical rules. For instance, this tutorial skips over commonplace constructs such as `if ... then ... else ...`.

See the [Nix manual](https://nix.dev/manual/nix/stable/language/index.html)³² for a full language reference.

What do you need?

- Familiarity with software development
- Familiarity with Unix shell, to read command line examples
- A *Nix installation* (page 1) to run the examples

³² <https://nix.dev/manual/nix/stable/language/index.html>

How long does it take?

- No experience with functional programming: 2 hours
- Familiar with functional programming: 1 hour
- Proficient with functional programming: 30 minutes

Run all examples. Play with them to validate your assumptions and test what you have learned. Read detailed explanations if you want to make sure you fully understand the examples.

How to run the examples?

- A piece of Nix language code is a *Nix expression*.
- Evaluating a Nix expression produces a *Nix value*.
- The content of a *Nix file* (file extension `.nix`) is a Nix expression.

Note

To *evaluate* means to transform an expression into a value according to the language rules.

This tutorial contains many examples of Nix expressions. Each one is followed by the expected evaluation result.

The following example is a Nix expression adding two numbers:

```
1 + 2
```

```
3
```

Interactive evaluation

Use `nix repl`³³ to evaluate Nix expressions interactively (by typing them on the command line):

```
$ nix repl
Welcome to Nix 2.13.3. Type :? for help.

nix-repl> 1 + 2
3
```

Note

The Nix language uses lazy evaluation, and `nix repl` by default only computes values when needed.

Some examples show a fully evaluated data structure for clarity. If your output does not match the example, try prepending `:p` to the input expression.

Example:

```
nix-repl> { a.b.c = 1; }
{ a = { ... }; }

nix-repl> :p { a.b.c = 1; }
{ a = { b = { c = 1; }; }; }
```

Type `:q` to exit `nix repl`³⁴.

³³ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-repl.html>

³⁴ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-repl.html>

Evaluating Nix files

Use `nix-instantiate --eval`³⁵ to evaluate the expression in a Nix file.

```
$ echo 1 + 2 > file.nix
$ nix-instantiate --eval file.nix
3
```

Detailed explanation

The first command writes `1 + 2` to a file `file.nix` in the current directory. The contents of `file.nix` are now `1 + 2`, which you can check with

```
$ cat file.nix
1 + 2
```

The second command runs `nix-instantiate` with the `--eval` option on `file.nix`, which reads the file and evaluates the contained Nix expression. The resulting value is printed as output.

`--eval` is required to evaluate the file and do nothing else. If `--eval` is omitted, `nix-instantiate` expects the expression in the given file to evaluate to a special value called a *derivation*, covered at the end of this tutorial in *Derivations* (page 36).

Note

`nix-instantiate --eval` will try to read from `default.nix` if no file name is specified.

```
$ echo 1 + 2 > default.nix
$ nix-instantiate --eval
3
```

Note

The Nix language uses lazy evaluation, and `nix-instantiate` by default only computes values when needed.

Some examples show a fully evaluated data structure for clarity. If your output does not match the example, try adding the `--strict` option to `nix-instantiate`.

Example:

```
$ echo "{ a.b.c = 1; }" > file.nix
$ nix-instantiate --eval file.nix
{ a = <CODE>; }
```

```
$ echo "{ a.b.c = 1; }" > file.nix
$ nix-instantiate --eval --strict file.nix
{ a = { b = { c = 1; }; }; }
```

Notes on whitespace

White space is used to delimit *lexical tokens*³⁶, where required. It is otherwise insignificant.

Line breaks, indentation, and additional spaces are for the reader's convenience.

The following are equivalent:

³⁵ <https://nix.dev/manual/nix/stable/command-ref/nix-instantiate.html>

³⁶ https://en.wikipedia.org/wiki/Lexical_analysis#Lexical_token_and_lexical_tokenization

```
let
  x = 1;
  y = 2;
in x + y
```

```
3
```

```
let x=1;y=2;in x+y
```

```
3
```

2.2.2 Names and values

Values in the Nix language can be primitive data types, lists, attribute sets, and functions.

Examples of primitive data types and lists appear in the context of *attribute sets* (page 16). Later in this section, you will encounter special features of character strings: *string interpolation* (page 22), *file system paths* (page 24), and *indented strings* (page 24). *Functions* (page 26) are covered separately.

Attribute sets (page 16) and *let expressions* (page 18) are used to assign names to values. Assignments are denoted by a single equal sign (=).

Whenever you encounter an equal sign (=) in Nix language code:

- On its left is the assigned name.
- On its right is the value, delimited by a semicolon (;).

Attribute set { ... }

An attribute set is a collection of name-value-pairs, where names must be unique.

The following example shows all primitive data types, lists, and attribute sets.

Note

If you are familiar with JSON, imagine the Nix language as *JSON with functions*.

Nix language data types *without functions* work just like their counterparts in JSON and look very similar.

Nix

```
1 {
2   string = "hello";
3   integer = 1;
4   float = 3.141;
5   bool = true;
6   null = null;
7   list = [ 1 "two" false ];
8   attribute-set = {
9     a = "hello";
10    b = 2;
11    c = 2.718;
12    d = false;
13  }; # comments are supported
14 }
```

JSON

```
{
  "string": "hello",
  "integer": 1,
  "float": 3.141,
  "bool": true,
  "null": null,
  "list": [1, "two", false],
  "object": {
    "a": "hello",
    "b": 1,
    "c": 2.718,
    "d": false
  }
}
```

Note

- Attribute set syntax³⁷: attribute names usually do not need quotes
- List syntax³⁸: list elements are separated by white space

Recursive attribute set `rec { ... }`

You will sometimes see attribute sets declared with `rec` prepended. This allows access to attributes from within the set.

Example:

```
rec {
  one = 1;
  two = one + 1;
  three = two + 1;
}
```

```
{ one = 1; three = 3; two = 2; }
```

Note

Elements in an attribute set can be declared in any order, and are ordered on evaluation.

Counter-example:

```
{
  one = 1;
  two = one + 1;
  three = two + 1;
}
```

```
error: undefined variable 'one'
```

```
at «string»:3:9:
```

(continues on next page)

³⁷ <https://nix.dev/manual/nix/stable/language/syntax#attrs-literal>

³⁸ <https://nix.dev/manual/nix/stable/language/syntax#list-literal>

(continued from previous page)

```
2|  one = 1;
3|  two = one + 1;
   |      ^
4|  three = two + 1;
```

let ... in ...

Also known as “let expression” or “let binding”

let expressions allow assigning names to values for repeated use.

Example:

```
let
  a = 1;
in
a + a
```

```
2
```

Detailed explanation

Assignments are placed between the keywords `let` and `in`. In this example we assign `a = 1`.

After `in` comes the expression in which the assignments are valid, i.e., where assigned names can be used. In this example the expression is `a + a`, where `a` refers to `a = 1`.

By replacing the names with their assigned values, `a + a` evaluates to 2.

Names can be assigned in any order, and expressions on the right of the assignment (`=`) can refer to other assigned names.

Example:

```
let
  b = a + 1;
  a = 1;
in
a + b
```

```
3
```

Detailed explanation

Assignments are placed between the keywords `let` and `in`. In this example we assign `a = 1` and `b = a + 1`.

The order of assignments does not matter. Therefore the following example, where the assignments are in reverse order, is equivalent:

```
let
  a = 1;
  b = a + 1;
in
a + b
```

```
3
```

Note that the `a` in `b = a + 1` refers to `a = 1`.

After `in` comes the expression in which the assignments are valid. In this example the expression is `a + b`, where `a` refers to `a = 1`, and `b` refers to `b = a + 1`.

By replacing the names with their assigned values, `a + b` evaluates to 3.

This is similar to *recursive attribute sets* (page 17): in both, the order of assignments does not matter, and names on the left can be used in expressions on the right of the assignment (`=`).

Example:

```
let ... in ...
```

```
let
  b = a + 1;
  c = a + b;
  a = 1;
in { c = c; a = a; b = b; }
```

```
{ a = 1; b = 2; c = 3; }
```

```
rec { ... }
```

```
rec {
  b = a + 1;
  c = a + b;
  a = 1;
}
```

```
{ a = 1; b = 2; c = 3; }
```

The difference is that while a recursive attribute set evaluates to an *attribute set* (page 16), any expression can follow after the `in` keyword.

In the following example we use the `let` expression to form a list:

```
let
  b = a + 1;
  c = a + b;
  a = 1;
in [ a b c ]
```

```
[ 1 2 3 ]
```

Only expressions within the `let` expression itself can access the newly declared names. The bindings have local scope.

Counter-example:

```
{
  a = let x = 1; in x;
  b = x;
}
```

```
error: undefined variable 'x'
```

```
at «string»:3:7:
```

```
2|   a = let x = 1; in x;
3|   b = x;
  |       ^
4| }
```

Attribute access

Attributes in a set are accessed with a dot (.) and the attribute name.

Example:

```
let
  attrset = { x = 1; };
in
attrset.x
```

```
1
```

Accessing nested attributes works the same way.

Example:

```
let
  attrset = { a = { b = { c = 1; }; }; };
in
attrset.a.b.c
```

```
1
```

The dot (.) notation can also be used for assigning attributes.

Example:

```
{ a.b.c = 1; }
```

```
{ a = { b = { c = 1; }; }; }
```

with ...; ...

The `with` expression allows access to attributes without repeatedly referencing their attribute set.

Example:

```
let
  a = {
    x = 1;
    y = 2;
    z = 3;
  };
in
with a; [ x y z ]
```

```
[ 1 2 3 ]
```

The expression

```
with a; [ x y z ]
```

is equivalent to

```
[ a.x a.y a.z ]
```

Attributes made available through `with` are only in scope of the expression following the semicolon (;).

Counter-example:

```
let
  a = {
    x = 1;
    y = 2;
    z = 3;
  };
in
{
  b = with a; [ x y z ];
  c = x;
}
```

error: undefined variable 'x'

at «string»:10:7:

```

9|   b = with a; [ x y z ];
10|  c = x;
   |      ^
11| }
```

inherit ...

`inherit` is shorthand for assigning the value of a name from an existing scope to the same name in a nested scope. It is for convenience to avoid repeating the same name multiple times.

Example:

```
let
  x = 1;
  y = 2;
in
{
  inherit x y;
}
```

```
{ x = 1; y = 2; }
```

The fragment

```
inherit x y;
```

is equivalent to

```
x = x; y = y;
```

inherit (...) ...

It is also possible to `inherit` names from a specific attribute set by enclosing its name parentheses.

Example:

```
let
  a = { x = 1; y = 2; };
in
{
  inherit (a) x y;
}
```

```
{ x = 1; y = 2; }
```

The fragment

```
inherit (a) x y;
```

is equivalent to

```
x = a.x; y = a.y;
```

inherit also works inside let expressions.

Example:

```
let
  a = { x = 1; y = 2; };
  inherit (a) x y;
in [ x y ]
```

```
[ 1 2 ]
```

Detailed explanation

While this example is contrived, in more complex code you will regularly see nested *let expressions* (page 18) that re-use names from their outer scope.

Here we use the attribute set `a = { x = 1; y = 2; }` to have something non-trivial to inherit from. The `let` expression inherits `x` and `y` from `a` using `( )`, which is equivalent to writing:

```
let
  x = a.x;
  y = a.y;
in
```

The new inner scope now contains `x` and `y`, which are used in the list `[ x y ]`.

String interpolation `${ ... }`

Previously known as “antiquotation”.

The value of a Nix expression can be inserted into a character string with the dollar-sign and braces (`${ ... }`).

Example:

```
let
  name = "Nix";
in
"hello ${name}"
```

```
"hello Nix"
```

Only character strings or values that can be represented as a character string are allowed.

Counter-example:

```
let
  x = 1;
in
"${x} + ${x} = ${x + x}"
```

```
error: cannot coerce an integer to a string

    at «string»:4:2:

      3| in
      4| "${x} + ${x} = ${x + x}"
        | ^
      5|
```

Interpolated expressions can be arbitrarily nested.

(This can become hard to read. Avoid it in practice.)

Example:

```
let
  a = "no";
in
"${a + " ${a + " ${a}"}}"
```

```
"no no no"
```

Detailed explanation

Any Nix expression where the value can be represented as a string can be used within `${ }`.

The `+` sign in the above expression is the [string concatenation operator](#)³⁹, which takes two strings and produces a new string.

The expression in the example is deliberately confusing to demonstrate that arbitrarily nested string interpolations are possible, but tend to be hard to read.

It denotes a string that contains the interpolation of concatenating the value of `a` with a string that starts with a space and is followed by another interpolated string. That second interpolated string is again the result of concatenating the value of `a` and yet another string that starts with a space and is followed by an interpolation of `a`.

Example:

```
let
  a = "one";
  b = "two";
in
"${a + b}"
```

```
"onetwo"
```

Built-in functions are discussed in a [later section](#) (page 31).

Warning

You may encounter strings that use the dollar sign (`$`) before an assigned name, but no braces (`{ }`):

These are *not* interpolated strings, but usually denote variables in a shell script.

In such cases, the use of names from the surrounding Nix expression is a coincidence.

Example:

³⁹ <https://nix.dev/manual/nix/latest/language/operators#string-concatenation>

```
let
  out = "Nix";
in
"echo ${out} > $out"

"echo Nix > $out"
```

Indented strings

Also known as “multi-line strings”.

The Nix language offers convenience syntax for character strings which span multiple lines that have common indentation.

Indented strings are denoted by *double single quotes* (‘ ‘ ‘ ‘).

Example:

```
‘ ‘
multi
line
string
‘ ‘
```

```
"multi\nline\nstring\n"
```

Equal amounts of prepended white space are trimmed from the result.

Example:

```
‘ ‘
  one
  two
  three
‘ ‘
```

```
"one\n two\n  three\n"
```

Note

Indented strings also support *string interpolation* (page 22). For details check the [documentation on string literals in the Nix language](#)⁴⁰.

File system paths

The Nix language offers convenience syntax for file system paths.

Absolute paths always start with a slash (/).

Example:

```
/absolute/path
```

```
/absolute/path
```

⁴⁰ <https://nix.dev/manual/nix/2.24/language/syntax#string-literal>

Paths are relative when they contain at least one slash (/) but do not start with one. They evaluate to the path relative to the file containing the expression.

The following examples assume the containing Nix file is in `/current/directory` (or `nix repl` is run in `/current/directory`).

Example:

```
./relative
```

```
/current/directory/relative
```

Example:

```
relative/path
```

```
/current/directory/relative/path
```

One dot (.) denotes the current directory within the given path.

You will often see the following expression, which specifies a Nix file's directory.

Example:

```
./.
```

```
/current/directory
```

Detailed explanation

Since relative paths must contain a slash (/) but must not start with one, and the dot (.) denotes no change of directory, the combination `./.` specifies the current directory as a relative path.

Two dots (..) denote the parent directory.

Example:

```
../.
```

```
/current
```

Note

Paths can be used in interpolated expressions – an *impure operation* (page 34) covered in detail in a *later section* (page 35).

Lookup paths

Also known as “angle bracket syntax”.

Example:

```
<nixpkgs>
```

```
/nix/var/nix/profiles/per-user/root/channels/nixpkgs
```

The value of a *lookup path*⁴¹ is a file system path that depends on the value of `builtins.nixPath`⁴².

⁴¹ <https://nix.dev/manual/nix/2.22/language/constructs/lookup-path>

⁴² <https://nix.dev/manual/nix/2.22/language/builtin-constants#builtins-nixPath>

In practice, `<nixpkgs>` points to the file system path of some revision of *Nixpkgs*.

For example, `<nixpkgs/lib>` points to the subdirectory `lib` of that file system path:

```
<nixpkgs/lib>
```

```
/nix/var/nix/profiles/per-user/root/channels/nixpkgs/lib
```

While you will encounter many such examples, *avoid lookup paths* (page 146) in production code, as they are *impurities* (page 34) which are not reproducible.

2.2.3 Functions

Functions are everywhere in the Nix language and deserve particular attention.

A function always takes exactly one argument. Argument and function body are separated by a colon (`:`).

Wherever you find a colon (`:`) in Nix language code:

- On its left is the function argument
- On its right is the function body.

Function arguments are the third way, apart from *attribute sets* (page 16) and *let expressions* (page 18), to assign names to values. Notably, values are not known in advance: the names are placeholders that are filled when *calling a function* (page 27).

Function declarations in the Nix language can appear in different forms. Each of them is explained in the following, and here is an overview:

- Single argument

```
x: x + 1
```

- Multiple arguments via nesting

```
x: y: x + y
```

- Attribute set argument

```
{ a, b }: a + b
```

- With default attributes

```
{ a, b ? 0 }: a + b
```

- With additional attributes allowed

```
{ a, b, ... }: a + b
```

- Named attribute set argument

```
args@{ a, b, ... }: a + b + args.c
```

or

```
{ a, b, ... }@args: a + b + args.c
```

Functions in the Nix language have no names. They are anonymous, and such a function is called a *lambda*.⁶⁸

Example:

⁶⁸ The term *lambda* is a shorthand for *lambda abstraction*⁶⁹ in the *lambda calculus*⁷⁰.

⁶⁹ https://en.wikipedia.org/wiki/Lambda_calculus#lambdaAbstr

⁷⁰ https://en.wikipedia.org/wiki/Lambda_calculus

```
x: x + 1
```

```
<LAMBDA>
```

The `<LAMBDA>` indicates the resulting value is an anonymous function.

As with any other value, functions can be assigned to a name.

Example:

```
let
  f = x: x + 1;
in f
```

```
<LAMBDA>
```

Calling functions

Also known as “function application”.

Calling a function with an argument means writing the argument after the function.

Example:

```
let
  f = x: x + 1;
in f 1
```

```
2
```

Example:

```
let
  f = x: x.a;
in
f { a = 1; }
```

```
1
```

The above example calls `f` on a literal attribute set. One can also pass arguments by name.

Example:

```
let
  f = x: x.a;
  v = { a = 1; };
in
f v
```

```
1
```

Since function and argument are separated by white space, sometimes parentheses `(( ))` are required to achieve the desired result.

Example:

```
(x: x + 1) 1
```

```
2
```

Detailed explanation

This expression applies an anonymous function $x: x + 1$ to the argument 1. The function has to be written in parentheses to distinguish it from the argument.

Example:

List elements are also separated by white space, therefore the following are different:

```
let
  f = x: x + 1;
  a = 1;
in [ (f a) ]
```

```
[ 2 ]
```

```
let
  f = x: x + 1;
  a = 1;
in [ f a ]
```

```
[ <LAMBDA> 1 ]
```

The first example reads: apply f to a , and put the result in a list. The resulting list has one element.

The second example reads: put f and a in a list. The resulting list has two elements.

Multiple arguments

Also known as “curried⁴³ functions”.

Nix functions take exactly one argument. Multiple arguments can be handled by nesting functions.

Such a nested function can be used like a function that takes multiple arguments, but offers additional flexibility.

Example:

```
x: y: x + y
```

```
<LAMBDA>
```

The above function is equivalent to

```
x: (y: x + y)
```

```
<LAMBDA>
```

This function takes one argument and returns another function $y: x + y$ with x set to the value of that argument.

Example:

```
let
  f = x: y: x + y;
in
f 1
```

⁴³ <https://en.wikipedia.org/wiki/Currying>

```
<LAMBDA>
```

Applying the function which results from `f 1` to another argument yields the inner body `x + y` (with `x` set to 1 and `y` set to the other argument), which can now be fully evaluated.

```
let
  f = x: y: x + y;
in
f 1 2
```

```
3
```

Attribute set argument

Also known as “keyword arguments” or “destructuring”.

Nix functions can be declared to require an attribute set with specific structure as argument.

This is denoted by listing the expected attribute names separated by commas (,) and enclosed in braces ({ }).

Example:

```
{a, b}: a + b
```

```
<LAMBDA>
```

The argument defines the exact attributes that have to be in that set. Leaving out or passing additional attributes is an error.

Example:

```
let
  f = {a, b}: a + b;
in
f { a = 1; b = 2; }
```

```
3
```

Counter-example:

```
let
  f = {a, b}: a + b;
in
f { a = 1; b = 2; c = 3; }
```

```
error: 'f' at (string):2:7 called with unexpected argument 'c'
```

```
at «string»:4:1:
```

```

3| in
4| f { a = 1; b = 2; c = 3; }
  | ^
5|
```

Default values

Also known as “default arguments”.

Destructured arguments can have default values for attributes.

This is denoted by separating the attribute name and its default value with a question mark (?).

Attributes in the argument are not required if they have a default value.

Example:

```
let
  f = {a, b ? 0}: a + b;
in
f { a = 1; }
```

```
1
```

Example:

```
let
  f = {a ? 0, b ? 0}: a + b;
in
f { } # empty attribute set
```

```
0
```

Additional attributes

Additional attributes are allowed with an ellipsis (...):

```
{a, b, ...}: a + b
```

Unlike in the previous counter-example, passing an argument that contains additional attributes is not an error.

Example:

```
let
  f = {a, b, ...}: a + b;
in
f { a = 1; b = 2; c = 3; }
```

```
3
```

Named attribute set argument

Also known as “@ pattern”, “@ syntax”, or “‘at’ syntax”.

An attribute set argument can be given a name to be accessible as a whole.

This is denoted by prepending or appending the name to the attribute set argument, separated by the at sign (@).

Example:

```
{a, b, ...}@args: a + b + args.c
```

```
<LAMBDA>
```

or

```
args@{a, b, ...}: a + b + args.c
```

```
<LAMBDA>
```

Example:

```
let
  f = {a, b, ...}@args: a + b + args.c;
in
f { a = 1; b = 2; c = 3; }
```

```
6
```

2.2.4 Function libraries

In addition to the [built-in operators](#)⁴⁴ (+, ==, &&, etc.), there are two widely used libraries that *together* can be considered standard for the Nix language. You need to know about both to understand and navigate Nix language code.

Skim them to familiarise yourself with what is available.

builtins

Also known as “primitive operations” or “primops”.

Nix comes with many functions that are built into the language. They are implemented in C++ as part of the Nix language interpreter.

Note

The Nix manual lists all [Built-in Functions](#)⁴⁵, and shows how to use them.

These functions are available under the `builtins` constant.

Example:

```
builtins.toString
```

```
<PRIMOP>
```

import

Most built-in functions are only accessible through `builtins`. A notable exception is `import`, which is also available at the top level.

`import` takes a path to a Nix file, reads it to evaluate the contained Nix expression, and returns the resulting value. If the path points to a directory, the file `default.nix` in that directory is used instead.

Example:

```
$ echo 1 + 2 > file.nix
```

```
import ./file.nix
```

⁴⁴ <https://nix.dev/manual/nix/stable/language/operators.html>

⁴⁵ <https://nix.dev/manual/nix/stable/language/builtins.html>

```
3
```

Detailed explanation

The preceding shell command writes the contents `1 + 2` to the file `file.nix` in the current directory.

The above Nix expression refers to this file as `./file.nix`. `import` reads the file and evaluates to the contained Nix expression.

It is an error if the file system path does not exist.

After reading `file.nix` the Nix expression is equivalent to the file contents:

```
1 + 2
```

```
3
```

Since a Nix file can contain any Nix expression, `imported` functions can be applied to arguments immediately.

Whenever you find additional tokens after a call to `import`, the returned value is a function. Anything that follows are arguments to that function.

Example:

```
$ echo "x: x + 1" > file.nix
```

```
import ./file.nix 1
```

```
2
```

Detailed explanation

The preceding shell command writes the contents `x: x + 1` to the file `file.nix` in the current directory.

The above Nix expression refers to this file as `./file.nix`. `import ./file.nix` reads the file and evaluates to the contained Nix expression.

It is an error if the file system path does not exist.

After reading the file, the Nix expression `import ./file.nix` is equivalent to the file contents:

```
(x: x + 1) 1
```

```
2
```

This applies the function `x: x + 1` to the argument `1`, and therefore evaluates to `2`.

Note

Parentheses are required to separate function declaration from function application.

pkgs.lib

The `nixpkgs`⁴⁶ repository contains an attribute set called `lib`⁴⁷, which provides a large number of useful functions. They are implemented in the Nix language, as opposed to *builtins* (page 31), which are part of the language itself.

⁴⁶ <https://github.com/NixOS/nixpkgs>

⁴⁷ <https://github.com/NixOS/nixpkgs/blob/master/lib/default.nix>

Note

The Nixpkgs manual lists all [Nixpkgs library functions](#)⁴⁸.

These functions are usually accessed through `pkgs.lib`, as the Nixpkgs attribute set is given the name `pkgs` by convention.

Example:

```
let
  pkgs = import <nixpkgs> {};
in
pkgs.lib.strings.toUpper "lookup paths considered harmful"
```

```
LOOKUP PATHS CONSIDERED HARMFUL
```

Detailed explanation

This is a more complex example, but by now you should be familiar with all its components.

The name `pkgs` is declared to be the expression imported from some file. That file's path is determined by the value of the lookup path `<nixpkgs>`, which in turn is determined by the `$NIX_PATH` environment variable at the time this expression is evaluated. As this expression happens to be a function, it requires an argument to evaluate, and in this case passing an empty attribute set `{}` is sufficient.

Now that `pkgs` is in scope of `let ... in ...`, its attributes can be accessed. From the Nixpkgs manual one can determine that there exists a function under `lib.strings.toUpper`⁴⁹.

For brevity, this example uses a lookup path to obtain *some version* of Nixpkgs. The function `toUpper` is trivial enough that we can expect it not to produce different results for different versions of Nixpkgs. Yet, more sophisticated software is likely to suffer from such problems. A fully reproducible example would therefore look like this:

```
let
  nixpkgs = fetchTarball
    ↪ "https://github.com/NixOS/nixpkgs/archive/06278c77b5d162e62df170fec307e83f1812d94b.tar.gz"
    ↪ ";
  pkgs = import nixpkgs {};
in
pkgs.lib.strings.toUpper "always pin your sources"
```

```
ALWAYS PIN YOUR SOURCES
```

See *Towards reproducibility: pinning Nixpkgs* (page 11) for details.

What you will also often see is that `pkgs` is passed as an argument to a function. By convention one can assume that it refers to the Nixpkgs attribute set, which has a `lib` attribute:

```
{ pkgs, ... } :
pkgs.lib.strings.removePrefix "no " "no true scotsman"
```

```
<LAMBDA>
```

To make this function produce a result, you can write it to a file (e.g. `file.nix`) and pass it an argument through `nix-instantiate`:

```
$ nix-instantiate --eval file.nix --arg pkgs 'import <nixpkgs> {}'
"true scotsman"
```

⁴⁸ <https://nixos.org/manual/nixpkgs/stable/#sec-functions-library>

⁴⁹ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.strings.toUpper>

Oftentimes you will see in NixOS configurations, and also within Nixpkgs, that `lib` is passed directly. In that case one can assume that this `lib` is equivalent to `pkgs.lib` where only `pkgs` is available.

Example:

```
{ lib, ... }:
let
  to-be = true;
in
lib.trivial.or to-be (! to-be)
```

```
<LAMBDA>
```

To make this function produce a result, you can write it to a file (e.g. `file.nix`) and pass it an argument through `nix-instantiate`:

```
$ nix-instantiate --eval file.nix --arg lib '(import <nixpkgs> {}).lib'
true
```

Sometimes both `pkgs` and `lib` are passed as arguments. In that case, one can assume `pkgs.lib` and `lib` to be equivalent. This is done to improve readability by avoiding repeated use of `pkgs.lib`.

Example:

```
{ pkgs, lib, ... }:
# ... multiple uses of `pkgs`
# ... multiple uses of `lib`
```

For historical reasons, some of the functions in `pkgs.lib` are equivalent to *builtins* (page 31) of the same name.

2.2.5 Impurities

So far this tutorial has only covered *pure expressions*: declaring data and transforming it with functions.

In practice, describing derivations – the Nix language’s defining feature, which enables functional programming with the file system – requires observing the outside world. *Derivations* (page 36) are discussed later in the tutorial.

There is only one impurity in the Nix language that is relevant here: reading files from the file system as *build inputs*.

Derivations refer to build inputs to describe how to derive new files. When run, a derivation will only have access to explicitly declared build inputs.

The only way to specify build inputs in the Nix language is explicitly with:

- File system paths
- Dedicated functions

Nix and the Nix language refer to files by their content hash. If file contents are not known in advance, it’s unavoidable to read files during expression evaluation.

Note

Nix supports other types of impure expressions, such as *lookup paths* (page 146) or the constant `builtins.currentSystem`⁵⁰. These are not covered here in more detail, as they do not matter for how the Nix language works in principle, and because they are discouraged for the very reason of breaking reproducibility.

⁵⁰ <https://nix.dev/manual/nix/stable/language/builtin-constants.html#builtins-currentSystem>

Paths

Whenever a file system path is used in *string interpolation* (page 22), the contents of that file are copied to a special location in the file system, the *Nix store*, as a side effect.

The evaluated string then contains the Nix store path assigned to that file.

Example:

```
$ echo 123 > data
```

```
"${./data}"
```

```
"/nix/store/h1qj5h5n05b5dl5q4nldrqq8mdg7dhqk-data"
```

Detailed explanation

The preceding shell command writes the characters 123 to the file `data` in the current directory.

The above Nix expression refers to this file as `./data` and converts the file system path to an *interpolated string* (page 22) `${ ... }`.

Such interpolated expressions must evaluate to something that can be represented as a character string. A file system path is such a value, and its character string representation is the corresponding Nix store path:

```
/nix/store/<hash>-<name>
```

The Nix store path is obtained by taking the hash of the file's contents (`<hash>`) and combining it with the file name (`<name>`). The file is copied into the Nix store directory `/nix/store` as a side effect of evaluation. It is an error if the file system path does not exist.

For directories the same thing happens: The entire directory (including nested files and directories) is copied to the Nix store, and the evaluated string becomes the Nix store path of the directory.

Fetchers

Files to be used as build inputs do not have to come from the file system.

The Nix language provides built-in impure functions to fetch files over the network during evaluation:

- `builtins.fetchurl`⁵¹
- `builtins.fetchTarball`⁵²
- `builtins.fetchGit`⁵³
- `builtins.fetchClosure`⁵⁴

These functions evaluate to a file system path in the Nix store.

Example:

```
builtins.fetchurl
↪ "https://github.com/NixOS/nix/archive/7c3ab5751568a0bc63430b33a5169c5e4784a0ff.tar.gz"
↪ "
```

```
"/
↪ nix/store/7dhgs330clj36384akg86140fqkqh8zf-7c3ab5751568a0bc63430b33a5169c5e4784a0ff.tar.gz
↪ "
```

⁵¹ <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-fetchurl>

⁵² <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-fetchTarball>

⁵³ <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-fetchGit>

⁵⁴ <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-fetchClosure>

Some of them add extra convenience, such as automatically unpacking archives.

Example:

```
builtins.fetchTarball
  ↪ "https://github.com/NixOS/nix/archive/7c3ab5751568a0bc63430b33a5169c5e4784a0ff.tar.gz"
  ↪ "
```

```
"/nix/store/d59llm96vgis5fy231x6m7nrijs0ww36-source"
```

Note

The Nixpkgs manual on [Fetchers](#)⁵⁵ lists numerous additional library functions to fetch files over the network.

It is an error if the network request fails.

2.2.6 Derivations

Derivations are at the core of both Nix and the Nix language:

- The Nix language is used to describe derivations.
- Nix runs derivations to produce *build results*.
- Build results can in turn be used as inputs for other derivations.

The Nix language primitive to declare a derivation is the built-in impure function `derivation`.

It is usually wrapped by the Nixpkgs build mechanism `stdenv.mkDerivation`, which hides much of the complexity involved in non-trivial build procedures.

Note

You will probably never encounter `derivation` in practice.

Whenever you encounter `mkDerivation`, it denotes something that Nix will eventually *build*.

Example: *a package using `mkDerivation`* (page 38)

The evaluation result of `derivation` (and `mkDerivation`) is an *attribute set* (page 16) with a certain structure and a special property: It can be used in *string interpolation* (page 22), and in that case evaluates to the Nix store path of its build result.

Example:

```
let
  pkgs = import <nixpkgs> {};
in "${pkgs.nix}"
```

```
"/nix/store/sv2srrjddrp2isghmrla8s6lazbzmikd-nix-2.11.0"
```

Note

Your output may differ. It may produce a different hash or even a different package version.

A derivation's output path is fully determined by its inputs, which in this case come from *some* version of Nixpkgs.

⁵⁵ <https://nixos.org/manual/nixpkgs/stable/#chap-pkgs-fetchers>

This is why *avoid lookup paths* (page 146) to ensure predictable outcomes, except in examples intended for illustration only.

Detailed explanation

The example imports the Nix expression from the lookup path `<nixpkgs>`, and applies the resulting function to an empty attribute set `{}`. Its output is assigned the name `pkgs`.

Converting the attribute `pkgs.nix` to a string with *string interpolation* (page 22) is allowed, as `pkgs.nix` is a derivation. That is, ultimately `pkgs.nix` boils down to a call to `derivation`.

The resulting string is the file system path where the build result of that derivation will end up.

There is more depth to the inner workings of derivations, but at this point it should be enough to know that such expressions evaluate to Nix store paths.

String interpolation on derivations is used to refer to their build results as file system paths when declaring new derivations.

This allows constructing arbitrarily complex compositions of derivations with the Nix language.

2.2.7 Worked examples

So far the examples have been artificial illustrations of the Nix language constructs.

You should now be able to read Nix language code for simple packages and configurations, and come up with similar explanations of the following practical examples.

Note

The goal of the following exercises is not to understand what the code means or how it works, but how it is structured in terms of functions, attribute sets, and other Nix language data types.

Shell environment

```
{ pkgs ? import <nixpkgs> {} }:  
let  
  message = "hello world";  
in  
pkgs.mkShellNoCC {  
  packages = with pkgs; [ cowsay ];  
  shellHook = ''  
    cowsay ${message}  
  '';  
}
```

This example declares a shell environment (which runs the `shellHook` on initialization).

Explanation:

- This expression is a function that takes an attribute set as its argument.
- If the argument has the attribute `pkgs`, it will be used in the function body. Otherwise, by default, import the Nix expression in the file found on the lookup path `<nixpkgs>` (which is a function in this case), call the function with an empty attribute set, and use the resulting value.
- The name `message` is bound to the string value `"hello world"`.
- The attribute `mkShellNoCC` of the `pkgs` set is a function that is passed an attribute set as argument. Its return value is also the result of the outer function.

- The attribute set passed to `mkShellNoCC` has the attributes `packages` (set to a list with one element: the `cowsay` attribute from `pkgs`) and `shellHook` (set to an indented string).
- The indented string contains an interpolated expression, which will expand the value of `message` to yield `"hello world"`.

NixOS configuration

```
{ config, pkgs, ... }: {  
  
  imports = [ ./hardware-configuration.nix ];  
  
  environment.systemPackages = with pkgs; [ git ];  
  
  # ...  
  
}
```

This example is (part of) a NixOS configuration.

Explanation:

- This expression is a function that takes an attribute set as an argument. It returns an attribute set.
- The argument must at least have the attributes `config` and `pkgs`, and may have more attributes.
- The returned attribute set contains the attributes `imports` and `environment`.
- `imports` is a list with one element: a path to a file next to this Nix file, called `hardware-configuration.nix`.

Note

`imports` is not the impure built-in `import`, but a regular attribute name!

- `environment` is itself an attribute set with one attribute `systemPackages`, which will evaluate to a list with one element: the `git` attribute from the `pkgs` set.
- The `config` argument is not (shown to be) used.

Package

```
{ lib, stdenv, fetchurl }:  
  
stdenv.mkDerivation rec {  
  
  pname = "hello";  
  
  version = "2.12";  
  
  src = fetchurl {  
    url = "mirror://gnu/${pname}/${pname}-${version}.tar.gz";  
    sha256 = "1ayhp9v4m4rdhjmn12bq3cibrbqqkgjbl3s7yk2nhlh8vj3ay16g";  
  };  
  
  meta = with lib; {  
    license = licenses.gpl3Plus;  
  };  
  
}
```

This example is a (simplified) package declaration from Nixpkgs.

Explanation:

- This expression is a function that takes an attribute set which must have exactly the attributes `lib`, `stdenv`, and `fetchurl`.
- It returns the result of evaluating the function `mkDerivation`, which is an attribute of `stdenv`, applied to a recursive set.
- The recursive set passed to `mkDerivation` uses its own `pname` and `version` attributes in the argument to the function `fetchurl`. `fetchurl` itself comes from the outer function's arguments.
- The `meta` attribute is itself an attribute set, where the `license` attribute has the value that was assigned to the nested attribute `lib.licenses.gpl3Plus`.

2.2.8 References

- Nix manual: Nix language⁵⁶
- Nix manual: String interpolation⁵⁷
- Nix manual: Built-in Functions⁵⁸
- Nix manual: `nix repl`⁵⁹
- Nixpkgs manual: Functions reference⁶⁰
- Nixpkgs manual: Fetchers⁶¹

2.2.9 Next steps

Get things done

- *Declarative shell environments with `shell.nix`* (page 8) – create reproducible shell environments from a Nix file
- *Packaging existing software with Nix* (page 40) – make more software available through Nix

If you want to take a longer break from learning Nix, you can remove unused build results from the Nix store with:

```
$ nix-collect-garbage
```

Learn more

If you worked through the examples, you will have noticed that reading the Nix language reveals the structure of the code, but does not necessarily tell what the code actually means.

Often it is not possible to determine from the code at hand

- the data type of a named value or function argument.
- the data type a called function accepts for its argument.
- which attributes are present in a given attribute set.

Example:

```
{ x, y, z }: (x y) z.a
```

How do you know...

- that `x` will be a function that, given an argument, returns a function?

⁵⁶ <https://nix.dev/manual/nix/stable/language/index.html>

⁵⁷ <https://nix.dev/manual/nix/stable/language/string-interpolation.html>

⁵⁸ <https://nix.dev/manual/nix/stable/language/builtins.html>

⁵⁹ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-repl.html>

⁶⁰ <https://nixos.org/manual/nixpkgs/stable/#sec-functions-library>

⁶¹ <https://nixos.org/manual/nixpkgs/stable/#chap-pkgs-fetchers>

- that, given x is a function, y will be an appropriate argument to x ?
- that, given $(x \ y)$ is a function, $z.a$ will be an appropriate argument to $(x \ y)$?
- that z will be an attribute set at all?
- that, given z is an attribute set, it will have an attribute a ?
- which data type y and $z.a$ will be?
- the data type of the end result?

And how does the caller of this function know that it requires an attribute set with attributes x , y , z ?

Answering such questions requires knowing the context in which a given expression is supposed to be used.

The Nix ecosystem and code style is driven by conventions. Most names you will encounter in Nix language code come from Nixpkgs:

- [Nix Pills](#)⁶² - a detailed explanation of derivations and how Nixpkgs is constructed from first principles

Nixpkgs provides generic build mechanisms that are widely used:

- `stdenv`⁶³ - most importantly `mkDerivation`
- [Build helpers](#)⁶⁴ - for creating derivations, including shell scripts and single files

Packages from Nixpkgs can be modified through multiple mechanisms:

- [overrides](#)⁶⁵ – specifically `override` and `overrideAttrs` to modify single packages
- [overlays](#)⁶⁶ – to produce a custom variant of Nixpkgs with individually modified packages

Different language ecosystems and frameworks have different requirements to accommodating them into Nixpkgs:

- [Languages and frameworks](#)⁶⁷ lists tools provided by Nixpkgs to build language- or framework-specific packages with Nix.

The NixOS Linux distribution uses a *modular configuration system* (page 72) that imposes its own conventions.

2.3 Packaging existing software with Nix

One of Nix's primary use-cases is in addressing common difficulties encountered with packaging software, such as specifying and obtaining dependencies.

In the long term, Nix alleviates such problems. But when *first* packaging existing software with Nix, it's common to encounter errors that seem inscrutable.

2.3.1 Introduction

In this tutorial, you'll create your first [Nix derivations](#)⁷¹ to package C/C++ software. You'll take advantage of the [Nixpkgs Standard Environment](#)⁷² (`stdenv`), which automates much of the work involved.

⁶² <https://nixos.org/guides/nix-pills/>

⁶³ <https://nixos.org/manual/nixpkgs/stable/#chap-stdenv>

⁶⁴ <https://nixos.org/manual/nixpkgs/stable/#part-builders>

⁶⁵ <https://nixos.org/manual/nixpkgs/stable/#chap-overrides>

⁶⁶ <https://nixos.org/manual/nixpkgs/stable/#chap-overlays>

⁶⁷ <https://nixos.org/manual/nixpkgs/stable/#chap-language-support>

⁷¹ <https://nix.dev/manual/nix/stable/language/derivations>

⁷² <https://nixos.org/manual/nixpkgs/stable/#part-stdenv>

What will you learn?

The tutorial begins with `hello`, an implementation of “hello world” which only requires dependencies already provided by `stdenv`. Next, you build more complex packages with their own dependencies, which leads to using additional derivation features.

You’ll encounter and address Nix error messages, build failures, and a host of other issues, developing your iterative debugging techniques along the way.

What do you need?

- Familiarity with the Unix shell and plain text editors
- You should be confident with *reading the Nix language* (page 12). Feel free to go back and work through the tutorial first.

How long does it take?

Going through all the steps carefully will take around 60 minutes.

2.3.2 Your first package

Note

A *package* is a loosely defined concept that refers to either a collection of files and other data, or a *Nix expression* representing such a collection before it comes into being. Packages in Nixpkgs have a conventional structure, allowing them to be discovered in searches and composed in environments alongside other packages.

For the purposes of this tutorial, a “package” is a Nix language function that will evaluate to a derivation. It will enable you or others to produce an artifact for practical use, as a consequence of having “packaged existing software with Nix”.

To start, consider this skeleton derivation:

```
1 { stdenv }:
2
3 stdenv.mkDerivation { }
```

This is a function which takes an attribute set containing `stdenv`, and produces a derivation (which currently does nothing).

A package function

GNU Hello is an implementation of the “hello world” program, with source code accessible from the GNU Project’s FTP server⁷³.

To begin, add a `pname` attribute to the set passed to `mkDerivation`. Every package needs a name and a version, and Nix will throw `error: derivation name missing without one`.

```
stdenv.mkDerivation {
+ pname = "hello";
+ version = "2.12.1";
```

Next, declare a dependency on the latest version of `hello`, and instruct Nix to use `fetchzip` to download the source code archive⁷⁴.

⁷³ <https://ftp.gnu.org/gnu/hello/>

⁷⁴ <https://ftp.gnu.org/gnu/hello/hello-2.12.1.tar.gz>

Note

fetchzip can fetch [more archives](#)⁷⁵ than just zip files!

The hash cannot be known until after the archive has been downloaded and unpacked. Nix will complain if the hash supplied to `fetchzip` is incorrect. Set the `hash` attribute to an empty string and then use the resulting error message to determine the correct hash:

```

1 # hello.nix
2 {
3     stdenv,
4     fetchzip,
5 }:
6
7 stdenv.mkDerivation {
8     pname = "hello";
9     version = "2.12.1";
10
11     src = fetchzip {
12         url = "https://ftp.gnu.org/gnu/hello/hello-2.12.1.tar.gz";
13         sha256 = "";
14     };
15 }
```

Save this file to `hello.nix` and run `nix-build` to observe your first build failure:

```

$ nix-build hello.nix
error: cannot evaluate a function that has an argument without a value ('stdenv')
Nix attempted to evaluate a function as a top level expression; in
this case it must have its arguments supplied either by default
values, or passed explicitly with '--arg' or '--argstr'. See
https://nix.dev/manual/nix/stable/language/constructs.html#functions.

at /home/nix-user/hello.nix:3:3:

      2| {
      3|     stdenv,
        |     ^
      4|     fetchzip,
```

Problem: the expression in `hello.nix` is a *function*, which only produces its intended output if it is passed the correct *arguments*.

Building with `nix-build`

`stdenv` is available from `nixpkgs`⁷⁶, which must be imported with another Nix expression to pass it as an argument to this derivation.

The recommended way to do this is to create a `default.nix` file in the same directory as `hello.nix`, with the following contents:

```

1 # default.nix
2 let
3     nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-24.05";
4     pkgs = import nixpkgs { config = {}; overlays = []; };

```

(continues on next page)

⁷⁵ <https://nixos.org/manual/nixpkgs/stable/#fetchurl>

⁷⁶ <https://github.com/NixOS/nixpkgs/>

(continued from previous page)

```

5 in
6 {
7   hello = pkgs.callPackage ./hello.nix { };
8 }

```

This allows you to run `nix-build -A hello` to realize the derivation in `hello.nix`, similar to the current convention used in Nixpkgs.

Note

`callPackage` automatically passes attributes from `pkgs` to the given function, if they match attributes required by that function's argument attribute set. In this case, `callPackage` will supply `stdenv` and `fetchzip` to the function defined in `hello.nix`.

The tutorial [Package parameters and overrides with callPackage](#) (page 52) goes into detail on how this works.

Now run the `nix-build` command with the new argument:

```

$ nix-build -A hello
error: hash mismatch in fixed-output derivation '/
↳nix/store/pd2kiyfa0c06giparlhd1k31bvllypbb-source.drv':
    specified: sha256-AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA=
    got:      sha256-1kJhtlsAkpNB7f6tZEs+dbKd8z7KoNHxDHEJ0tmhnc=
error: 1 dependencies of derivation '/
↳nix/store/b4mjwlv73nmiqgkdabsdjc4zq9gnma1l-hello-2.12.1.drv' failed to build

```

Finding the file hash

As expected, the incorrect file hash caused an error, and Nix helpfully provided the correct one. In `hello.nix`, replace the empty string with the correct hash:

```

1 # hello.nix
2 {
3   stdenv,
4   fetchzip,
5 }:
6
7 stdenv.mkDerivation {
8   pname = "hello";
9   version = "2.12.1";
10
11   src = fetchzip {
12     url = "https://ftp.gnu.org/gnu/hello/hello-2.12.1.tar.gz";
13     sha256 = "sha256-1kJhtlsAkpNB7f6tZEs+dbKd8z7KoNHxDHEJ0tmhnc=";
14   };
15 }

```

Now run the previous command again:

```

$ nix-build -A hello
this derivation will be built:
  /nix/store/rbq37s3r76rr77c7d8x8px7z04kw2mk7-hello.drv
building '/nix/store/rbq37s3r76rr77c7d8x8px7z04kw2mk7-hello.drv'...
...
configuring
...

```

(continues on next page)

(continued from previous page)

```
configure: creating ./config.status
config.status: creating Makefile
...
building
... <many more lines omitted>
```

The derivation built successfully.

The console output shows that `configure` was called, which produced a `Makefile` that was then used to build the project. It wasn't necessary to write any build instructions in this case because the `stdenv` build system is based on [GNU Autoconf](https://www.gnu.org/software/autoconf/)⁷⁷, which automatically detected the structure of the project directory.

Build result

Check your working directory for the result:

```
$ ls
default.nix hello.nix result
```

This result is a [symbolic link](#)⁷⁸ to a Nix store location containing the built binary; you can call `./result/bin/hello` to execute this program:

```
$ ./result/bin/hello
Hello, world!
```

Congratulations, you have successfully packaged your first program with Nix!

Next, you'll package another piece of software with external-to-`stdenv` dependencies that present new challenges, requiring you to make use of more `mkDerivation` features.

2.3.3 A package with dependencies

Now add a second, somewhat more complicated, program: `icat`⁷⁹ (which renders images in your terminal).

Change the `default.nix` from the previous section by adding a new attribute for `icat`:

```
1 # default.nix
2 let
3   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-24.05";
4   pkgs = import nixpkgs { config = {}; overlays = []; };
5 in
6 {
7   hello = pkgs.callPackage ./hello.nix { };
8   icat = pkgs.callPackage ./icat.nix { };
9 }
```

Copy `hello.nix` to a new file `icat.nix`, and update the `pname` and `version` attributes in that file:

```
1 # icat.nix
2 {
3   stdenv,
4   fetchzip,
5 }:
6
7 stdenv.mkDerivation {
```

(continues on next page)

⁷⁷ <https://www.gnu.org/software/autoconf/>

⁷⁸ https://en.wikipedia.org/wiki/Symbolic_link

⁷⁹ <https://github.com/atextor/icat>

(continued from previous page)

```

8  pname = "icat";
9  version = "v0.5";
10
11  src = fetchzip {
12      # ...
13  };
14 }

```

Now to download the source code. `icat`'s upstream repository is hosted on [GitHub](https://github.com/atextor/icat)⁸⁰, so you should replace the previous `source fetcher`⁸¹. This time, use `fetchFromGitHub`⁸² instead of `fetchzip`, by updating the argument attribute set to the function accordingly:

```

1  # icat.nix
2  {
3      stdenv,
4      fetchFromGitHub,
5  }:
6
7  stdenv.mkDerivation {
8      pname = "icat";
9      version = "v0.5";
10
11      src = fetchFromGitHub {
12          # ...
13      };
14  }

```

Fetching source from GitHub

While `fetchzip` required `url` and `sha256` arguments, more are needed for `fetchFromGitHub`⁸³.

The source URL is `https://github.com/atextor/icat`, which already gives the first two arguments:

- `owner`: the name of the account controlling the repository

```
owner = "atextor";
```

- `repo`: the name of the repository to fetch

```
repo = "icat";
```

Navigate to the project's [Tags page](https://github.com/atextor/icat/tags)⁸⁴ to find a suitable [Git revision](https://git-scm.com/docs/revisions)⁸⁵ (`rev`), such as the Git commit hash or tag (e.g. `v1.0`) corresponding to the release you want to fetch.

In this case, the latest release tag is `v0.5`.

As in the `hello` example, a hash must also be supplied. This time, instead of using the empty string and letting `nix-build` report the correct one in an error, you can fetch the correct hash in the first place with the `nix-prefetch-url` command.

You need the SHA256 hash of the *contents* of the tarball (as opposed to the hash of the tarball file itself). Therefore pass the `--unpack` and `--type sha256` arguments:

⁸⁰ <https://github.com/atextor/icat>

⁸¹ <https://nixos.org/manual/nixpkgs/stable/#chap-pkgs-fetchers>

⁸² <https://nixos.org/manual/nixpkgs/stable/#fetchfromgithub>

⁸³ <https://nixos.org/manual/nixpkgs/stable/#fetchfromgithub>

⁸⁴ <https://github.com/atextor/icat/tags>

⁸⁵ <https://git-scm.com/docs/revisions>

```
$ nix-prefetch-url --unpack
↳https://github.com/atextor/icat/archive/refs/tags/v0.5.tar.gz --type sha256
path is '/nix/store/p8jl1jlqxcsc7ryiazbpm7c1mqb6848b-v0.5.tar.gz'
0wyy2ksxp95vnh71ybj1bbmqd5ggp13x3mk37pzzr99ljs9awy8ka
```

Set the correct hash for `fetchFromGitHub`:

```
1 # icat.nix
2 {
3     stdenv,
4     fetchFromGitHub,
5 }:
6
7 stdenv.mkDerivation {
8     pname = "icat";
9     version = "v0.5";
10
11     src = fetchFromGitHub {
12         owner = "atextor";
13         repo = "icat";
14         rev = "v0.5";
15         sha256 = "0wyy2ksxp95vnh71ybj1bbmqd5ggp13x3mk37pzzr99ljs9awy8ka";
16     };
17 }
```

Missing dependencies

Running `nix-build` on only the new `icat` attribute, an entirely new issue is reported:

```
$ nix-build -A icat
these 2 derivations will be built:
  /nix/store/86q9x927hsyyzfr4lcqirmsbimysi6mb-source.drv
  /nix/store/l5wz9inkvkf0qhl8kpl39vpg2xfm2qpy-icat.drv
...
error: builder for '/nix/store/l5wz9inkvkf0qhl8kpl39vpg2xfm2qpy-icat.drv' failed
↳with exit code 2;
    last 10 log lines:
      > from /
↳nix/store/hkj250rjsvxabr31fr1v81cv88cdfp4l-glibc-2.37-8-dev/include/stdio.h:27,
      > from icat.c:31:
      > /
↳nix/store/hkj250rjsvxabr31fr1v81cv88cdfp4l-glibc-2.37-8-dev/include/features.h:195:3:
↳warning: #warning "_BSD_SOURCE and _SVID_SOURCE are deprecated, use _
↳DEFAULT_SOURCE"
↳[8;https://gcc.gnu.org/onlinedocs/gcc/Warning-Options.html#index-Wcpp-Wcpp8;;]
      > 195 | # warning "_BSD_SOURCE and _SVID_SOURCE are deprecated, use _
↳DEFAULT_SOURCE"
      > | ^~~~~~
      > icat.c:39:10: fatal error: Imlib2.h: No such file or directory
      > 39 | #include <Imlib2.h>
      > | ^~~~~~
      > compilation terminated.
      > make: *** [Makefile:16: icat.o] Error 1
      For full logs, run 'nix log /
↳nix/store/l5wz9inkvkf0qhl8kpl39vpg2xfm2qpy-icat.drv'.
```

A compiler error. The `icat` source was pulled from GitHub, and Nix tried to build what it found, but compilation failed due to a missing dependency: the `imlib2` header.

If you search for `imlib2` on search.nixos.org⁸⁶, you'll find that `imlib2` is already in Nixpkgs.

Add this package to your build environment by adding `imlib2` to the arguments of the function in `icat.nix`. Then add the argument's value `imlib2` to the list of `buildInputs` in `stdenv.mkDerivation`:

```

1 # icat.nix
2 {
3     stdenv,
4     fetchFromGitHub,
5     imlib2,
6 }:
7
8 stdenv.mkDerivation {
9     pname = "icat";
10    version = "v0.5";
11
12    src = fetchFromGitHub {
13        owner = "atextor";
14        repo = "icat";
15        rev = "v0.5";
16        sha256 = "0wyy2ksxp95vnh71ybj1bbmqd5ggp13x3mk37pzt991js9awy8ka";
17    };
18
19    buildInputs = [ imlib2 ];
20 }

```

Run `nix-build -A icat` again and you'll encounter another error, but compilation proceeds further this time:

```

$ nix-build -A icat
this derivation will be built:
  /nix/store/bw2d4rp2k1l5rg49hds199ma2mz36x47-icat.drv
...
error: builder for '/nix/store/bw2d4rp2k1l5rg49hds199ma2mz36x47-icat.drv' failed
↳ with exit code 2;
   last 10 log lines:
   >                                     from icat.c:31:
   > /
↳ nix/store/hkj250rjsvxcb31fr1v81cv88cdfp41-glibc-2.37-8-dev/include/features.h:195:3:
↳ warning: #warning "_BSD_SOURCE and _SVID_SOURCE are deprecated, use _
↳ DEFAULT_SOURCE"
↳ [8;;https://gcc.gnu.org/onlinedocs/gcc/Warning-Options.html#index-Wcpp-Wcpp8;;]
   > 195 | # warning "_BSD_SOURCE and _SVID_SOURCE are deprecated, use _
↳ DEFAULT_SOURCE"
   >     | ^~~~~~
   > In file included from icat.c:39:
   > /
↳ nix/store/4fvrh0sjc8sbkbqda7dfsh7q0gxmnh9p-imlib2-1.11.1-dev/include/Imlib2.h:45:10:
↳ fatal error: X11/Xlib.h: No such file or directory
   > 45 | #include <X11/Xlib.h>
   >     | ^~~~~~
   > compilation terminated.
   > make: *** [Makefile:16: icat.o] Error 1
   For full logs, run 'nix log /
↳ nix/store/bw2d4rp2k1l5rg49hds199ma2mz36x47-icat.drv'.

```

You can see a few warnings which should be corrected in the upstream code. But the important bit for this tutorial is fatal error: `X11/Xlib.h: No such file or directory`: another dependency is missing.

⁸⁶ <https://search.nixos.org/packages?query=imlib2>

2.3.4 Finding packages

Determining from where to source a dependency is currently somewhat involved, because package names don't always correspond to library or program names.

You need the `Xlib.h` headers from the `X11` C package. The Nixpkgs derivation for this is `libX11`, available in the `xorg` package set. There are multiple ways to figure this out:

search.nixos.org

Tip

The easiest way to find what you need is on search.nixos.org/packages⁸⁷.

Unfortunately in this case, [searching for `x11`](#)⁸⁸ produces too many irrelevant results because `X11` is ubiquitous. On the left side bar there is a list package sets, and [selecting `xorg`](#)⁸⁹ shows something promising.

In case all else fails, it helps to become familiar with searching the [Nixpkgs source code](#)⁹⁰ for keywords.

Local code search

To find name assignments in the source, search for "`<keyword> =`". For example, these are the search results for "`x11 =`"⁹¹ or "`libx11 =`"⁹² on Github.

Or fetch a clone of the [Nixpkgs repository](#)⁹³ and search the code locally.

Start a shell that makes the required tools available – `git` for version control, and `rg` for code search (provided by the [ripgrep package](#)⁹⁴):

```
$ nix-shell -p git ripgrep
[nix-shell:~]$
```

The Nixpkgs repository is huge. Only clone the latest revision to avoid waiting a long time for a full clone:

```
[nix-shell:~]$ git clone https://github.com/NixOS/nixpkgs --depth 1
...
[nix-shell:~]$ cd nixpkgs/
```

To narrow down results, only search the `pkgs` subdirectory, which holds all the package recipes:

```
[nix-shell:~]$ rg "x11 =" pkgs
pkgs/tools/X11/primus/default.nix
21: primus = if useNvidia then primusLib_ else primusLib_.override { nvidia_x11 =
↪null; };
22: primus_i686 = if useNvidia then primusLib_i686_ else primusLib_i686_.override
↪{ nvidia_x11 = null; };

pkgs/applications/graphics/imv/default.nix
38: x11 = [ libGLU xorg.libxcb xorg.libX11 ];
```

(continues on next page)

⁸⁷ <http://search.nixos.org/packages>

⁸⁸ <https://search.nixos.org/packages?query=x11>

⁸⁹ https://search.nixos.org/packages?buckets=%7B%22package_attr_set%22%3A%5B%22xorg%22%5D%2C%22package_license_set%22%3A%5B%5D%2C%22package_maintainers_set%22%3A%5B%5D%2C%22package_platforms%22%3A%5B%5D%7D&query=x11

⁹⁰ <https://github.com/nixos/nixpkgs>

⁹¹ <https://github.com/search?q=repo%3ANixOS%2Fnixpkgs+%22x11+%3D%22&type=code>

⁹² <https://github.com/search?q=repo%3ANixOS%2Fnixpkgs+%22libx11+%3D%22&type=code>

⁹³ <https://github.com/nixos/nixpkgs>

⁹⁴ <https://search.nixos.org/packages?show=ripgrep>

(continued from previous page)

```
pkgs/tools/X11/primus/lib.nix
14:   if nvidia_x11 == null then libGL

pkgs/top-level/linux-kernels.nix
573:   ati_drivers_x11 = throw "ati drivers are no longer supported by any kernel.
↳>=4.1"; # added 2021-05-18;
... <a lot more results>
```

Since `rg` is case sensitive by default, Add `-i` to make sure you don't miss anything:

```
[nix-shell:~]$ rg -i "libx11 =" pkgs
pkgs/applications/version-management/monotone-viz/graphviz-2.0.nix
55:   ++ lib.optional (libX11 == null) "--without-x";

pkgs/top-level/all-packages.nix
14191:   libX11 = xorg.libX11;

pkgs/servers/x11/xorg/default.nix
1119: libX11 = callPackage ({ stdenv, pkg-config, fetchurl, xorgproto,
↳libpthreadstubs, libxcb, xtrans, testers }: stdenv.mkDerivation (finalAttrs: {

pkgs/servers/x11/xorg/overrides.nix
147: libX11 = super.libX11.overrideAttrs (attrs: {
```

Local derivation search

To search derivations on the command line, use `nix-locate` from the [nix-index](https://github.com/nix-community/nix-index)⁹⁵.

Adding package sets as dependencies

Add `xorg` to your derivation's input attribute set and use `xorg.libX11` in `buildInputs`:

```
1 # icat.nix
2 {
3   stdenv,
4   fetchFromGitHub,
5   imlib2,
6   xorg,
7 }:
8
9 stdenv.mkDerivation {
10   pname = "icat";
11   version = "v0.5";
12
13   src = fetchFromGitHub {
14     owner = "atextor";
15     repo = "icat";
16     rev = "v0.5";
17     sha256 = "0wyy2ksxp95vnh71ybj1bbmqd5ggp13x3mk37pzt99ljs9awy8ka";
18   };
19
20   buildInputs = [ imlib2 xorg.libX11 ];
21 }
```

⁹⁵ <https://github.com/nix-community/nix-index>

Note

Because the Nix language is lazily evaluated, accessing only `xorg.libX11` means that the remaining contents of the `xorg` attribute set are never processed.

2.3.5 Fixing build failures

Run the last command again:

```
$ nix-build -A icat
this derivation will be built:
  /nix/store/x1d79ld8jxqdlA5zw2b47d2sl87mf56k-icat.drv
...
error: builder for '/nix/store/x1d79ld8jxqdlA5zw2b47d2sl87mf56k-icat.drv' failed
↳ with exit code 2;
   last 10 log lines:
   > 195 | # warning "_BSD_SOURCE and _SVID_SOURCE are deprecated, use _
↳ DEFAULT_SOURCE"
   >      | ^~~~~~
   > icat.c: In function 'main':
   > icat.c:319:33: warning: ignoring return value of 'write' declared with
↳ attribute 'warn_unused_result'
↳ [8;;https://gcc.gnu.org/onlinedocs/gcc/Warning-Options.html#index-Wunused-result-Wunused-result
   > 319 |                                     write(tempfile, &buf, 1);
   >      |                                     ^~~~~~
   > gcc -o icat icat.o -lImlib2
   > installing
   > install flags:
↳ SHELL=/nix/store/8fv91097mbh5049i9rglc73dx6kkg3qk-bash-5.2-p15/bin/bash install
   > make: *** No rule to make target 'install'. Stop.
   For full logs, run 'nix log /
↳ nix/store/x1d79ld8jxqdlA5zw2b47d2sl87mf56k-icat.drv'.
```

The missing dependency error is solved, but there is now another problem: `make: *** No rule to make target 'install'. Stop.`

installPhase

`stdenv` is automatically working with the `Makefile` that comes with `icat`. The console output shows that `configure` and `make` are executed without issue, so the `icat` binary is compiling successfully.

The failure occurs when the `stdenv` attempts to run `make install`. The `Makefile` included in the project happens to lack an `install` target. The `README` in the `icat` repository only mentions using `make` to build the tool, leaving the installation step up to users.

To add this step to your derivation, use the `installPhase` attribute⁹⁶. It contains a list of command strings that are executed to perform the installation.

Because `make` finishes successfully, the `icat` executable is available in the build directory. You only need to copy it from there to the output directory.

In Nix, the output directory is stored in the `$out` variable. That variable is accessible in the derivation's `builder` execution environment⁹⁷. Create a `bin` directory within the `$out` directory and copy the `icat` binary there:

```
1 # icat.nix
2 {
3   stdenv,
```

(continues on next page)

⁹⁶ <https://nixos.org/manual/nixpkgs/stable/#ssec-install-phase>

⁹⁷ <https://nix.dev/manual/nix/2.19/language/derivations#builder-execution>

(continued from previous page)

```

4   fetchFromGitHub,
5   imlib2,
6   xorg,
7 }:
8
9 stdenv.mkDerivation {
10   pname = "icat";
11   version = "v0.5";
12
13   src = fetchFromGitHub {
14     owner = "atextor";
15     repo = "icat";
16     rev = "v0.5";
17     sha256 = "0wyy2ksxp95vnh71ybj1bbmqd5ggp13x3mk37pzt991js9awy8ka";
18   };
19
20   buildInputs = [ imlib2 xorg.libX11 ];
21
22   installPhase = ''
23     mkdir -p $out/bin
24     cp icat $out/bin
25   '';
26 }

```

Phases and hooks

Nixpkgs `stdenv.mkDerivation` derivations are separated into [phases](#)⁹⁸. Each is intended to control some aspect of the build process.

Earlier you observed how `stdenv.mkDerivation` expected the project's Makefile to have an `install` target, and failed when it didn't. To fix this, you defined a custom `installPhase` containing instructions for copying the `icat` binary to the correct output location, in effect installing it. Up to that point, the `stdenv.mkDerivation` automatically determined the `buildPhase` information for the `icat` package.

During derivation realisation, there are a number of shell functions (“hooks”, in Nixpkgs) which may execute in each derivation phase. Hooks do things like set variables, source files, create directories, and so on.

These are specific to each phase, and run both before and after that phase's execution. They modify the build environment for common operations during the build.

Include calls to these hooks in the derivation phases you define, even when you don't make direct use of them. This facilitates easy [overriding](#)⁹⁹ of specific parts of the derivation later. And it keeps the code tidy and makes it easier to read.

Adjust your `installPhase` to call the appropriate hooks:

```

1  # icat.nix
2
3  # ...
4
5  installPhase = ''
6    runHook preInstall
7    mkdir -p $out/bin
8    cp icat $out/bin
9    runHook postInstall
10  '';

```

(continues on next page)

⁹⁸ <https://nixos.org/manual/nixpkgs/stable/#sec-stdenv-phases>

⁹⁹ <https://nixos.org/manual/nixpkgs/stable/#chap-overrides>

(continued from previous page)

```
11 # ...
12
```

2.3.6 A successful build

Running the `nix-build -A icat` command once more will finally do what you want, repeatably. Call `ls` in the local directory to find a `result` symlink to a location in the Nix store:

```
$ ls
default.nix hello.nix icat.nix result
```

`result/bin/icat` is the executable built previously. Success!

Running `nix-build` (without specifying an attribute) builds all attributes at once. The first (`hello`) appears under `result/bin/`, while the second (`icat`) appears under `result-2/bin/`. Adding more attributes produces additional `result-n` symlinks.

2.3.7 References

- [Nixpkgs Manual - Standard Environment](#)¹⁰⁰

2.3.8 Next steps

- *Package parameters and overrides with `callPackage`* (page 52)
- *Dependencies in the development shell* (page 135)
- *Automatic environment activation with `direnv`* (page 134)
- *Setting up a Python development environment* (page 139)
- Add your own new packages to Nixpkgs¹⁰¹
 - *How to contribute* (page 167)
 - *How to get help* (page 169)

2.4 Package parameters and overrides with `callPackage`

Nix ships with a special-purpose programming language for creating packages and configurations: the Nix language. It is used to build the Nix package collection, known as *Nixpkgs*.

Being purely functional, the Nix language allows declaring custom functions to abstract over common patterns. One of the most prominent patterns in Nixpkgs is parametrisation of package recipes.

2.4.1 Overview

Nixpkgs is a sizeable software project on its own, with coding conventions and idioms that have emerged over the years. It has established a convention¹⁰² of composing parameterised packages with automatic settings through a function named `callPackage`¹⁰³. This tutorial shows how to use it and why it's beneficial.

What will you learn?

- Using `callPackage` to invoke package recipes that follow Nixpkgs conventions
- Overriding package parameters
- Creating interdependent package sets

¹⁰⁰ <https://nixos.org/manual/nixpkgs/unstable/#part-stdenv>

¹⁰¹ <https://github.com/NixOS/nixpkgs/blob/master/CONTRIBUTING.md>

¹⁰² <https://github.com/nixos/nixpkgs/commit/d17f0f9cbca38fabb71624f069cd4c0d6feace92>

¹⁰³ <https://github.com/NixOS/nixpkgs/commit/fd268b4852d39c18e604c584dd49a611dc795a9b>

What do you need?

- Familiarity with the *Nix language* (page 12)
- First experience with *packaging existing software* (page 40)

How long does it take?

- 45 minutes

2.4.2 Automatic function calls

Create a new file `hello.nix`, which could be a typical package recipe as found in Nixpkgs: A function that takes an attribute set, with attributes corresponding to derivations in the top-level package set, and returns a derivation.

Listing 1: `hello.nix`

```
{ writeShellScriptBin }:  
writeShellScriptBin "hello" ''  
  echo "Hello, world!"  
''
```

Detailed explanation

`hello.nix` declares a function which takes as argument an attribute set with one element `writeShellScriptBin`. `writeShellScriptBin`¹⁰⁴ is a function that happens to exist in Nixpkgs, a *build helper*¹⁰⁵ that returns a derivation. The derivation output in this case contains an executable shell script in `$out/bin/hello` that prints “Hello world” when run.

Now create a file `default.nix` with the following contents:

Listing 2: `default.nix`

```
let  
  pkgs = import <nixpkgs> { };  
in  
pkgs.callPackage ./hello.nix { }
```

Realise the derivation in `default.nix` and run the executable that is produced:

```
$ nix-build  
$ ./result/bin/hello  
Hello, world!
```

The argument `writeShellScriptBin` gets filled in automatically when the function in `hello.nix` is evaluated. For every attribute in the function’s argument, `callPackage` passes an attribute from the `pkgs` attribute set if it exists.

It may appear cumbersome to create the extra file `hello.nix` for the package in such a simple setup. We have done so because this is exactly how Nixpkgs is organised: Every package recipe is a file that declares a function. This function takes as arguments the package’s dependencies.

2.4.3 Parameterised builds

Change the `default.nix` to produce an attribute set of derivations, with the attribute `hello` containing the original derivation:

¹⁰⁴ <https://nixos.org/manual/nixpkgs/unstable/#trivial-builder-writeShellScriptBin>

¹⁰⁵ <https://nixos.org/manual/nixpkgs/unstable/#part-builders>

Listing 3: default.nix

```
let
  pkgs = import <nixpkgs> { };
in
{
  hello = pkgs.callPackage ./hello.nix { };
}
```

When building the attribute `hello`, by accessing it with the `-A / --attr option`¹⁰⁶, the result will be the same as before:

```
$ nix-build -A hello
$ ./result/bin/hello
Hello, world!
```

Also change `hello.nix` to add an additional parameter `audience` with default value `"world"`:

Listing 4: hello.nix

```
{
  writeShellScriptBin,
  audience ? "world",
}:
writeShellScriptBin "hello" ''
  echo "Hello, ${audience}!"
''
```

This also does not change the result.

Things get more interesting when changing `default.nix` to make use of this new argument. Pass the parameter `audience` in the second argument to `callPackage`:

Listing 5: default.nix

```
let
  pkgs = import <nixpkgs> { };
in
{
  - hello = pkgs.callPackage ./hello.nix { };
  + hello = pkgs.callPackage ./hello.nix { audience = "people"; };
}
```

This attribute is passed on to the argument of the function defined in `hello.nix`: The same syntax can also be used to explicitly set the automatically discovered arguments, such as `writeShellScriptBin`, but that doesn't make sense here.

Try it out:

```
$ nix-build -A hello
$ ./result/bin/hello
Hello, people!
```

This pattern is used widely in Nixpkgs: For example, functions which represent Go programs often have a parameter `buildGoModule`. It is common to find expressions like `callPackage ./go-program.nix { buildGoModule = buildGo116Module; }` to change the default Go compiler version. Nixpkgs is therefore not simply a huge library of pre-configured packages, but a collection of functions – package *recipes* – for customising packages and even entire ecosystems (for example “All Python packages using my custom interpreter”) on the fly without duplicating code.

¹⁰⁶ <https://nix.dev/manual/nix/2.19/command-ref/nix-build#opt-attr>

2.5 Overrides

`callPackage` adds more convenience by allowing parameters to be customised *after the fact* using the returned derivation's `override` function.

Add a third attribute `hello-folks` to `default.nix` and set it to `hello.override` called with a new value for `audience`:

Listing 6: `default.nix`

```
let
  pkgs = import <nixpkgs> { };
in
- {
+ rec {
  hello = pkgs.callPackage ./hello.nix { audience = "people"; };
+ hello-folks = hello.override { audience = "folks"; };
}
```

Note

The resulting attribute set is now recursive (by the keyword `rec`). That is, attribute values can refer to names from within the same attribute set.

`override` passes `audience` to the original function in `hello.nix` - it *overrides* whatever arguments have been passed in the original `callPackage` that produced the derivation `hello`. All the other parameters will remain the same. This is especially useful and can be often found on packages that provide many options to customise a package.

Building `hello-folks` attribute and running the resulting executable will again produce a new version of the script:

```
$ nix-build -A hello-folks
$ ./result/bin/hello
Hello, folks!
```

A real-world example is the `neovim`¹⁰⁷ package recipe, which has overridable arguments such as `extraLuaPackages`, `extraPythonPackages`, or `withRuby`. Currently these parameters are only discoverable by reading the source code, which can be found by following the link to [Source](#) on search.nixos.org/packages¹⁰⁸.

2.5.1 Interdependent package sets

You can actually create your own version of `callPackage`! This comes in handy for package sets where the recipes depend on each other.

Note

The following examples do not show the “called” files, as they are not necessary for understanding the principle.

Consider the following recursive attribute set of derivations:

Listing 7: `default.nix`

```
let
  pkgs = import <nixpkgs> { };
in
rec {
```

(continues on next page)

¹⁰⁷ <https://search.nixos.org/packages?show=neovim>

¹⁰⁸ <https://search.nixos.org/packages>

(continued from previous page)

```

a = pkgs.callPackage ./a.nix { };
b = pkgs.callPackage ./b.nix { inherit a; };
c = pkgs.callPackage ./c.nix { inherit b; };
d = pkgs.callPackage ./d.nix { };
e = pkgs.callPackage ./e.nix { inherit c d; };
}

```

Note

Here, `inherit a;` is equivalent to `a = a;`.

Previously declared derivations are passed as arguments to other derivations through `callPackage`.

In this case you have to remember to manually specify all arguments required by each package in the respective *Nix file* that are not in `Nixpkgs`. If `./b.nix` requires an argument `a` but there is no `pkgs.a`, the function call will produce an error. This can become quite tedious quickly, especially for larger package sets.

Use `lib.callPackageWith` to create your own `callPackage` based on an attribute set.

Listing 8: default.nix

```

let
  pkgs = import <nixpkgs> { };
  callPackage = pkgs.lib.callPackageWith (pkgs // packages);
  packages = {
    a = callPackage ./a.nix { };
    b = callPackage ./b.nix { };
    c = callPackage ./c.nix { };
    d = callPackage ./d.nix { };
    e = callPackage ./e.nix { };
  };
in
packages

```

This requires some explanation.

First of all note that instead of a recursive attribute set, the names we operate on are now assigned in a `let` binding. It has the same property as recursive sets: Names on the left can be used in expressions on the right of the equal sign (`=`). This is how we can refer to `packages` when we merge its contents with the pre-existing attribute set `pkgs` using the `//` operator.

Your custom `callPackage` now makes available all the attributes in `pkgs` *and* `packages` to the called package function (the same names from `packages` taking precedence), and `packages` is being built up recursively with each call.

The last bit may make your head spin. This construction is only possible because the Nix language is lazily evaluated. That is, values are only computed when they are actually needed. It allows passing `packages` around without having fully defined it.

Each package's dependencies are now implicit at this level (they are still explicit in each of the package files), and `callPackage` resolves them *automagically*. This relieves you from dealing with them manually, and precludes configuration errors that may only surface late into a lengthy build process.

Of course this small example is still manageable in the original form. And the implicitly recursive variant can obscure the structure for software developers not familiar with lazy evaluation, making it harder to read for them than it was before. But this benefit really pays off for large constructions, where it is the amount of code that would obscure the structure, and where manual modifications would become cumbersome and error-prone.

2.5.2 Summary

Using `callPackage` not only follows Nixpkgs conventions, which makes your code easier to follow for experienced Nix users, but it also gives you some benefits for free:

1. Parametrized builds
2. Overridable builds
3. Concise implementation of interdependent package sets

2.5.3 References

- Nixpkgs manual: `callPackageWith`¹⁰⁹

2.5.4 Next steps

- *Working with local files* (page 57) - learn to package your own projects with Nix
- *Module system deep dive* (page 75) - learn to wield the functional programming magic behind NixOS

2.6 Working with local files

To build a local project in a Nix derivation, source files must be accessible to its `builder executable`¹¹⁰. By default, the `builder` runs in an `isolated environment`¹¹¹ that only allows reading from the Nix store. The Nix language has built-in features to copy local files to the store and expose the resulting store paths.

Using these features directly can be tricky however:

- Coercion of paths to strings, such as the wide-spread pattern of `src = ./.`, makes the derivation dependent on the name of the current directory. Furthermore, it always adds the entire directory to the store, including unneeded files, which causes unnecessary new builds when they change.
- The `builtins.path`¹¹² function (and equivalently `lib.sources.cleanSourceWith`¹¹³) can address these problems. However, it's often hard to express the desired path selection using the `filter` function interface.

In this tutorial you'll learn how to use the Nixpkgs `lib.fileset library`¹¹⁴ to work with local files in derivations. It abstracts over built-in functionality and offers a safer and more convenient interface.

2.6.1 File sets

A *file set* is a data type representing a collection of local files. File sets can be created, composed, and manipulated with the various functions of the library.

You can explore and learn about the library with `nix repl`¹¹⁵:

```
$ nix repl -f channel:nixos-23.11
...
nix-repl> fs = lib.fileset
```

The `trace`¹¹⁶ function pretty-prints the files included in a given file set:

¹⁰⁹ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.customisation.callPackageWith>

¹¹⁰ <https://nix.dev/manual/nix/stable/language/derivations#attr-builder>

¹¹¹ <https://nix.dev/manual/nix/stable/command-ref/conf-file.html#conf-sandbox>

¹¹² <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-path>

¹¹³ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.sources.cleanSourceWith>

¹¹⁴ <https://nixos.org/manual/nixpkgs/stable/#sec-functions-library-fileset>

¹¹⁵ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-repl>

¹¹⁶ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.fileset.trace>

```
nix-repl> fs.trace ./ . null
trace: /home/user (all files in directory)
null
```

All functions that expect a file set for an argument can also accept a [path](#)¹¹⁷. Such path arguments are then [implicitly turned into sets](#)¹¹⁸ that contain *all* files under the given path. In the previous trace this is indicated by (all files in directory).

Tip

The `trace` function pretty-prints its first argument and returns its second argument. But since you often just need the pretty-printing in `nix repl`, you can omit the second argument:

```
nix-repl> fs.trace ./
trace: /home/user (all files in directory)
«lambda @ /
↳nix/store/1czt278x24s3bl6qdnifpvm5z03wfi2p-nixpkgs-src/lib/fileset/default.nix:555:8»
```

Even though file sets conceptually contain local files, these files are *never* added to the Nix store unless explicitly requested. Therefore you don't have to worry as much about accidentally copying secrets into the world-readable store.

In this example, although you pretty-printed the home directory, no files were copied. This is in contrast to coercion of paths to strings such as in "`${./}`", which copies the whole directory to the Nix store on evaluation.

Warning

When using the `flakes` and `nix-command` [experimental features](#)¹¹⁹, a local directory within a Flake is always copied into the Nix store *completely* unless it is a Git repository.

This implicit coercion also works for files:

```
$ touch some-file
```

```
nix-repl> fs.trace ./some-file
trace: /home/user
trace: - some-file (regular)
```

In addition to the included file, this also prints its [file type](#)¹²⁰.

2.6.2 Example project

To further experiment with the library, make a sample project. Create a new directory, enter it, and set up `npins` to pin the Nixpkgs dependency:

```
$ mkdir fileset
$ cd fileset
$ nix-shell -p npins --run "npins init --bare; npins add github nixos nixpkgs --
↳branch nixos-23.11"
```

Then create a `default.nix` file with the following contents:

¹¹⁷ <https://nix.dev/manual/nix/stable/language/values#type-path>

¹¹⁸ <https://nixos.org/manual/nixpkgs/stable/#sec-fileset-path-coercion>

¹¹⁹ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-flake>

¹²⁰ <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-readFileType>

Listing 9: default.nix

```
{
  system ? builtins.currentSystem,
  sources ? import ./npins,
}:
let
  pkgs = import sources.nixpkgs {
    config = { };
    overlays = [ ];
    inherit system;
  };
in
pkgs.callPackage ./package.nix { }
```

Add two source files to work with:

```
$ echo hello > hello.txt
$ echo world > world.txt
```

2.6.3 Adding files to the Nix store

Files in a given file set can be added to the Nix store with `toSource`¹²¹. The argument to this function requires a `root` attribute to determine which source directory to copy to the store. Only the files in the `fileset` attribute are included in the result.

Define `package.nix` as follows:

Listing 10: package.nix

```
{ stdenv, lib }:
let
  fs = lib.fileset;
  sourceFiles = ./hello.txt;
in

fs.trace sourceFiles

stdenv.mkDerivation {
  name = "fileset";
  src = fs.toSource {
    root = ./.;
    fileset = sourceFiles;
  };
  postInstall = ''
    mkdir $out
    cp -v hello.txt $out
  '';
}
```

The call to `fs.trace` prints the file set that will be used as a derivation input.

Try building it:

¹²¹ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.fileset.toSource>

Note

It will take a while to fetch Nixpkgs the first time around.

```
$ nix-build
trace: /home/user/fileset
trace: - hello.txt (regular)
this derivation will be built:
  /nix/store/3ci6avmjaijx5g8jhb218i183xi7bi2n-fileset.drv
...
'hello.txt' -> '/nix/store/sa4g6h13v0zbpfw6pzva860kp5aks44n-fileset/hello.txt'
...
/nix/store/sa4g6h13v0zbpfw6pzva860kp5aks44n-fileset
```

But the real benefit of the file set library comes from its facilities for composing file sets in different ways.

2.6.4 Difference

To be able to copy both files `hello.txt` and `world.txt` to the output, add the whole project directory as a source again:

Listing 11: package.nix

```
{ stdenv, lib }:
let
  fs = lib.fileset;
- sourceFiles = ./hello.txt;
+ sourceFiles = ./.;
in

fs.trace sourceFiles

stdenv.mkDerivation {
  name = "fileset";
  src = fs.toSource {
    root = ./.;
    fileset = sourceFiles;
  };
  postInstall = ''
    mkdir $out
-   cp -v hello.txt $out
+   cp -v {hello,world}.txt $out
  '';
}
```

This will work as expected:

```
$ nix-build
trace: /home/user/fileset (all files in directory)
this derivation will be built:
  /nix/store/fsihp8872vv9ngbkc7si5jcbigs81727-fileset.drv
...
'hello.txt' -> '/nix/store/wmsxfgbylagmf033nkazr3qfc96y7mwk-fileset/hello.txt'
'world.txt' -> '/nix/store/wmsxfgbylagmf033nkazr3qfc96y7mwk-fileset/world.txt'
...
/nix/store/wmsxfgbylagmf033nkazr3qfc96y7mwk-fileset
```

However, if you run `nix-build` again, the output path will be different!

```
$ nix-build
trace: /home/user/fileset (all files in directory)
this derivation will be built:
  /nix/store/nlh7ismrf27xsnl3m20vfz6rvwlbbcca-fileset.drv
...
'hello.txt' -> '/nix/store/xknflcvjaa8dj6a6vkg629zmcrgz10rh-fileset/hello.txt'
'world.txt' -> '/nix/store/xknflcvjaa8dj6a6vkg629zmcrgz10rh-fileset/world.txt'
...
/nix/store/xknflcvjaa8dj6a6vkg629zmcrgz10rh-fileset
```

The problem here is that `nix-build` by default creates a `result` symlink in the working directory, which points to the store path just produced:

```
$ ls -l result
result -> /nix/store/xknflcvjaa8dj6a6vkg629zmcrgz10rh-fileset
```

Since `src` refers to the whole directory, and its contents change when `nix-build` succeeds, Nix will have to start over every time.

Note

This will also happen without the file set library, e.g. when setting `src = ./.;` directly.

The `difference`¹²² function subtracts one file set from another. The result is a new file set that contains all files from the first argument that aren't in the second argument.

Use it to filter out `./result` by changing the `sourceFiles` definition:

Listing 12: `package.nix`

```
{ stdenv, lib }:
let
  fs = lib.fileset;
- sourceFiles = ./.;
+ sourceFiles = fs.difference ./. ./result;
in
```

Building this, the file set library will specify which files are taken from the directory:

```
$ nix-build
trace: /home/user/fileset
trace: - package.nix (regular)
trace: - default.nix (regular)
trace: - hello.txt (regular)
trace: - npins (all files in directory)
trace: - world.txt (regular)
this derivation will be built:
  /nix/store/zr19bv51085zz005yk7pw4s9sglmafvn-fileset.drv
...
'hello.txt' -> '/nix/store/vhyhk6ij39gjapqavz1j1x3zbiy3qc1a-fileset/hello.txt'
'world.txt' -> '/nix/store/vhyhk6ij39gjapqavz1j1x3zbiy3qc1a-fileset/world.txt'
...
/nix/store/vhyhk6ij39gjapqavz1j1x3zbiy3qc1a-fileset
```

An attempt to repeat the build will re-use the existing store path:

¹²² <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.fileset.difference>

```
$ nix-build
trace: /home/user/fileset
trace: - package.nix (regular)
trace: - default.nix (regular)
trace: - hello.txt (regular)
trace: - npins (all files in directory)
trace: - world.txt (regular)
/nix/store/vhyhk6ij39gjapqavz1j1x3zbiy3qc1a-fileset
```

2.6.5 Missing files

Removing the `./result` symlink creates a new problem, though:

```
$ rm result
$ nix-build
error: lib.fileset.difference: Second argument (negative set)
  (/home/user/fileset/result) is a path that does not exist.
  To create a file set from a path that may not exist, use
  ↳ `lib.fileset.maybeMissing`.
```

Follow the instructions in the error message, and use `maybeMissing`¹²³ to create a file set from a path that may not exist (in which case the file set will be empty):

Listing 13: `package.nix`

```
{ stdenv, lib }:
let
  fs = lib.fileset;
- sourceFiles = fs.difference ../. ./result;
+ sourceFiles = fs.difference ../. (fs.maybeMissing ../result);
in
```

This now works, using the whole directory since `./result` is not present:

```
$ nix-build
trace: /home/user/fileset (all files in directory)
this derivation will be built:
  /nix/store/zr19bv51085zz005yk7pw4s9sglmafvn-fileset.drv
...
/nix/store/vhyhk6ij39gjapqavz1j1x3zbiy3qc1a-fileset
```

Another build attempt will produce a different trace, but the same output path:

```
$ nix-build
trace: /home/user/fileset
trace: - package.nix (regular)
trace: - default.nix (regular)
trace: - hello.txt (regular)
trace: - npins (all files in directory)
trace: - world.txt (regular)
/nix/store/vhyhk6ij39gjapqavz1j1x3zbiy3qc1a-fileset
```

¹²³ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.fileset.maybeMissing>

2.6.6 Union (explicitly exclude files)

There is still a problem: Changing *any* of the included files causes the derivation to be built again, even though it doesn't depend on those files.

Append an empty line to `package.nix`:

```
$ echo >> package.nix
```

Again, Nix will start from scratch:

```
$ nix-build
trace: /home/user/fileset
trace: - default.nix (regular)
trace: - npins (all files in directory)
trace: - package.nix (regular)
trace: - string.txt (regular)
this derivation will be built:
  /nix/store/zmgrpqlpfz2jq0w9rdacsnp8ni4n77cn-filesets.drv
...
/nix/store/6pffjljjy3c7kla60nljk3fad4q4kkzn-filesets
```

One way to fix this is to use `unions`¹²⁴.

Create a file set containing a union of the files to exclude (`fs.unions [ ... ]`), and subtract it (difference) from the complete directory (`./.`):

Listing 14: `package.nix`

```
sourceFiles =
  fs.difference
    ./
    (fs.unions [
      (fs.maybeMissing ./result)
      ./default.nix
      ./package.nix
      ./npins
    ]);
```

This will work as expected:

```
$ nix-build
trace: /home/user/fileset
trace: - hello.txt (regular)
trace: - world.txt (regular)
this derivation will be built:
  /nix/store/gr2hw3gdjc28fmv0as1ikpj7lya4r51f-fileset.drv
...
/nix/store/ckn40y7hgqphhbhyrq64h9r6rvdh973r-fileset
```

Changing any of the excluded files now doesn't necessarily cause a new build anymore:

```
$ echo >> package.nix
```

```
$ nix-build
trace: /home/user/fileset
trace: - hello.txt (regular)
trace: - world.txt (regular)
/nix/store/ckn40y7hgqphhbhyrq64h9r6rvdh973r-fileset
```

¹²⁴ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.fileset.unions>

2.6.7 Filter

The `fileFilter`¹²⁵ function allows filtering file sets such that each included file satisfies the given criteria.

Use it to select all files with a name ending in `.nix`:

Listing 15: `package.nix`

```
sourceFiles =
  fs.difference
    ./
    (fs.unions [
      (fs.maybeMissing ./result)
-     ./default.nix
-     ./package.nix
+     (fs.fileFilter (file: file.hasExt "nix") ./.)
      ./npins
    ]);
```

This does not change the result, even if we add a new `.nix` file.

```
$ nix-build
trace: /home/user/fileset
trace: - hello.txt (regular)
trace: - world.txt (regular)
/nix/store/ckn40y7hgqphhbhyrq64h9r6rvdh973r-fileset
```

Notably, the approach of using `difference ./` explicitly selects the files to *exclude*, which means that new files added to the source directory are included by default. Depending on your project, this might be a better fit than the alternative in the next section.

2.6.8 Union (explicitly include files)

To contrast the previous approach, `unions` can also be used to select only the files to *include*. This means that new files added to the current directory would be ignored by default.

Create some additional files:

```
$ mkdir src
$ touch build.sh src/select.{c,h}
```

Then create a file set from only the files to be included explicitly:

Listing 16: `package.nix`

```
{ stdenv, lib }:
let
  fs = lib.fileset;
  sourceFiles = fs.unions [
    ./hello.txt
    ./world.txt
    ./build.sh
    (fs.fileFilter
      (file: file.hasExt "c" || file.hasExt "h")
      ./src
    )
  ];
in
```

(continues on next page)

¹²⁵ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.fileset.fileFilter>

(continued from previous page)

```
fs.trace sourceFiles

stdenv.mkDerivation {
  name = "fileset";
  src = fs.toSource {
    root = ./.;
    fileset = sourceFiles;
  };
  postInstall = ''
    cp -vr . $out
  '';
}
```

The `postInstall` script is simplified to rely on the sources to be pre-filtered appropriately:

```
$ nix-build
trace: /home/user/fileset
trace: - build.sh (regular)
trace: - hello.txt (regular)
trace: - src (all files in directory)
trace: - world.txt (regular)
this derivation will be built:
  /nix/store/sjzkn07d6a4qfp60p6dc64pzvmmdafff-fileset.drv
...
'.' -> '/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset'
'./build.sh' -> '/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset/build.sh'
'./hello.txt' -> '/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset/hello.txt'
'./world.txt' -> '/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset/world.txt'
'./src' -> '/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset/src'
'./src/select.c' -> '/'
↪nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset/src/select.c'
'./src/select.h' -> '/'
↪nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset/src/select.h'
...
/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset
```

Only the specified files are used, even when a new one is added:

```
$ touch src/select.o README.md

$ nix-build
trace: - build.sh (regular)
trace: - hello.txt (regular)
trace: - src
trace:   - select.c (regular)
trace:   - select.h (regular)
trace: - world.txt (regular)
/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset
```

2.6.9 Matching files tracked by Git

If a directory is part of a Git repository, passing it to `gitTracked`¹²⁶ gives you a file set that only includes files tracked by Git.

Create a local Git repository and add all files except `src/select.o` and `./result` to it:

¹²⁶ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.fileset.gitTracked>

```
$ git init
Initialized empty Git repository in /home/user/fileset/.git/
$ git add -A
$ git reset src/select.o result
```

Re-use this selection of files with `gitTracked`:

Listing 17: `package.nix`

```
sourceFiles = fs.gitTracked ./.;
```

Build it again:

```
$ nix-build
warning: Git tree '/home/user/fileset' is dirty
trace: /home/vg/src/nix.dev/fileset
trace: - README.md (regular)
trace: - package.nix (regular)
trace: - build.sh (regular)
trace: - default.nix (regular)
trace: - hello.txt (regular)
trace: - npins (all files in directory)
trace: - src
trace:   - select.c (regular)
trace:   - select.h (regular)
trace: - world.txt (regular)
this derivation will be built:
  /nix/store/p9aw3fl5xcjbgg9yagykywvskzgrmk5y-fileset.drv
...
/nix/store/cw4bza1r27iimzrdbfl4yn5xr36d6k5l-fileset
```

This includes too much though, as not all of these files are needed to build the derivation as originally intended.

Note

When using the `flakes` and `nix-command` [experimental features](#)¹²⁷, this function isn't needed, because `nix build` by default only allows access to files tracked by Git. However, to provide the same developer experience for stable Nix, use of this function is nevertheless recommended.

2.6.10 Intersection

This is where `intersection` comes in. It allows creating a file set that consists only of files that are in *both* of two given file sets.

Select all files that are both tracked by Git *and* relevant for the build:

Listing 18: `package.nix`

```
sourceFiles =
  fs.intersection
    (fs.gitTracked ./.)
    (fs.unions [
      ./hello.txt
      ./world.txt
      ./build.sh
```

(continues on next page)

¹²⁷ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-flake>

(continued from previous page)

```
./src
});
```

This will produce the same output as in the other approach and therefore re-use a previous build result:

```
$ nix-build
warning: Git tree '/home/user/fileset' is dirty
trace: - build.sh (regular)
trace: - hello.txt (regular)
trace: - src
trace:   - select.c (regular)
trace:   - select.h (regular)
trace: - world.txt (regular)
/nix/store/zl4n1g6is4cmsqf02dci5b2h5zd0ia4r-fileset
```

2.6.11 Conclusion

We have shown some examples on how to use all of the fundamental file set functions. For more complex use cases, they can be composed as needed.

For the complete list and more details, see the [lib.fileset reference documentation](#)¹²⁸.

2.7 Cross compilation

Nixpkgs provides tools to cross-compile software for different system types.

2.7.1 What do you need?

- Experience using C compilers
- Basic knowledge of the *Nix language* (page 12)

2.7.2 Platforms

When compiling code, there is a distinction between the **build platform**, where the executable is *built*, and the **host platform**, where the compiled executable *runs*.¹³⁷

Native compilation is the special case where those two platforms are the same. **Cross compilation** is the general case where those two platforms are not.

Cross compilation is needed when the host platform has limited resources (such as CPU) or when it's not easily accessible for development.

Nixpkgs has well-tested cross compilation support.

2.7.3 What's a target platform?

There is a third concept for a platform called the **target platform**.

The target platform is relevant to cases where you want to build a compiler binary. In such cases, you would build a compiler on the *build platform*, run it to compile code on the *host platform*, and run the final executable on the *target platform*.

Since this is rarely needed, this tutorial assumes that the target is identical to the host.

¹²⁸ <https://nixos.org/manual/nixpkgs/stable/#sec-functions-library-fileset>

¹³⁷ Terminology for cross compilation platforms differs between build systems. We have chosen to follow [autoconf terminology](#)¹³⁸.

¹³⁸ https://www.gnu.org/software/autoconf/manual/autoconf-2.69/html_node/Hosts-and-Cross_002dCompilation.html

2.7.4 Determining the host platform config

The build platform is determined automatically by Nix during the configure phase.

The host platform is best determined by running this command on the host platform:

```
$ $(nix-build '<nixpkgs>' -I nixpkgs=channel:nixos-23.11 -A gnu-config) /
↳ config.guess
aarch64-unknown-linux-gnu
```

In case this is not possible (for example, when the host platform is not easily accessible for development), the platform config has to be constructed manually via the following template:

```
<cpu>-<vendor>-<os>-<abi>
```

This string representation is used in `nixpkgs` for historic reasons.

Note that `<vendor>` is often `unknown` and `<abi>` is optional. There's also no unique identifier for a platform, for example `unknown` and `pc` are interchangeable (which is why the script is called `config.guess`).

If you can't install Nix, find a way to run `config.guess` (usually comes with the `autoconf` package) from the OS you're able to run on the host platform.

Some other common examples of platform configs:

- `aarch64-apple-darwin14`
- `aarch64-pc-linux-gnu`
- `x86_64-w64-mingw32`
- `aarch64-apple-ios`

Note

macOS/Darwin is a special case, as not the whole OS is open-source. It's only possible to cross compile between `aarch64-darwin` and `x86_64-darwin`. `aarch64-darwin` support was recently added, so cross compilation is barely tested.

2.7.5 Choosing the host platform with Nix

`nixpkgs` comes with a set of predefined host platforms for cross compilation called `pkgsCross`.

It is possible to explore them in `nix repl`:

Note

Starting with Nix 2.19¹²⁹, `nix repl` requires the `-f / --file` flag:

```
$ nix repl -f '<nixpkgs>' -I nixpkgs=channel:nixos-23.11
```

```
$ nix repl '<nixpkgs>' -I nixpkgs=channel:nixos-23.11
Welcome to Nix 2.18.1. Type :? for help.

Loading '<nixpkgs>'...
Added 14200 variables.

nix-repl> pkgsCross.<TAB>
pkgsCross.aarch64-android          pkgsCross.musl-power
```

(continues on next page)

¹²⁹ <https://nix.dev/manual/nix/latest/release-notes/r1-2.19>

(continued from previous page)

pkgsCross.aarch64-android-prebuilt	pkgsCross.musl32
pkgsCross.aarch64-darwin	pkgsCross.musl64
pkgsCross.aarch64-embedded	pkgsCross.muslpi
pkgsCross.aarch64-multiplatform	pkgsCross.or1k
pkgsCross.aarch64-multiplatform-musl	pkgsCross.pogoplug4
pkgsCross.aarch64be-embedded	pkgsCross.powernv
pkgsCross.amd64-netbsd	pkgsCross.ppc-embedded
pkgsCross.arm-embedded	pkgsCross.ppc64
pkgsCross.armhf-embedded	pkgsCross.ppc64-musl
pkgsCross.armv7a-android-prebuilt	pkgsCross.ppcle-embedded
pkgsCross.armv7l-hf-multiplatform	pkgsCross.raspberryPi
pkgsCross.avr	pkgsCross.remarkable1
pkgsCross.ben-nanonote	pkgsCross.remarkable2
pkgsCross.fuloongminipc	pkgsCross.riscv32
pkgsCross.ghcjs	pkgsCross.riscv32-embedded
pkgsCross.gnu32	pkgsCross.riscv64
pkgsCross.gnu64	pkgsCross.riscv64-embedded
pkgsCross.i686-embedded	pkgsCross.scaleway-c1
pkgsCross.iphone32	pkgsCross.sheevaplug
pkgsCross.iphone32-simulator	pkgsCross.vc4
pkgsCross.iphone64	pkgsCross.wasi32
pkgsCross.iphone64-simulator	pkgsCross.x86_64-embedded
pkgsCross.mingw32	pkgsCross.x86_64-netbsd
pkgsCross.mingwW64	pkgsCross.x86_64-netbsd-llvm
pkgsCross.mmix	pkgsCross.x86_64-unknown-redox
pkgsCross.msp430	

These attribute names for cross compilation packages have been chosen somewhat freely over the course of time. They usually do not match the corresponding platform config string.

You can retrieve the platform string from `pkgsCross.<platform>.stdenv.hostPlatform.config`:

```
nix-repl> pkgsCross.aarch64-multiplatform.stdenv.hostPlatform.config
"aarch64-unknown-linux-gnu"
```

If the host platform you seek hasn't been defined yet, please [contribute it upstream](#)¹³⁰.

2.7.6 Specifying the host platform

The mechanism for setting up cross compilation works as follows:

1. Take the build platform configuration and apply it to the current package set, called `pkgs` by convention.

The build platform is implied in `pkgs = import <nixpkgs> {}` to be the current system. This produces a build environment `pkgs.stdenv` with all the dependencies present to compile on the build platform.

2. Apply the appropriate host platform configuration to all the packages in `pkgsCross`.

Taking `pkgs.pkgsCross.<host>.hello` will produce the package `hello` compiled on the build platform to run on the `<host>` platform.

There are multiple equivalent ways to access packages targeted to the host platform.

1. Explicitly pick the host platform package from within the build platform environment:

```
1 let
2   nixpkgs = fetchTarball
3   ↪ "https://github.com/NixOS/nixpkgs/tarball/release-23.11";
4   pkgs = import nixpkgs {};
```

(continues on next page)

¹³⁰ <https://github.com/NixOS/nixpkgs/blob/master/lib/systems/examples.nix>

(continued from previous page)

```

4 in
5 pkgs.pkgsCross.aarch64-multiplatform.hello

```

2. Pass the host platform to `crossSystem` when importing `nixpkgs`. This configures `nixpkgs` such that all its packages are built for the host platform:

```

1 let
2   nixpkgs = fetchTarball
3     ↪ "https://github.com/NixOS/nixpkgs/tarball/release-23.11";
4   pkgs = import nixpkgs { crossSystem = { config = "aarch64-unknown-linux-gnu";
5     ↪ }; };
6 in
7 pkgs.hello

```

Equivalently, you can pass the host platform as an argument to `nix-build`:

```

$ nix-build '<nixpkgs>' -I nixpkgs=channel:nixos-23.11 \
  --arg crossSystem '{ config = "aarch64-unknown-linux-gnu"; }' \
  -A hello

```

2.7.7 Cross compiling for the first time

To cross compile a package like `hello`¹³¹, pick the platform attribute — `aarch64-multiplatform` in our case — and run:

```

$ nix-build '<nixpkgs>' -I nixpkgs=channel:nixos-23.11 \
  -A pkgsCross.aarch64-multiplatform.hello
...
/nix/store/1dx87l5rav8679lqigf9xxkb7wvh2m4k-hello-aarch64-unknown-linux-gnu-2.12.1

```

Note

The hash of the package in the store path changes with the updates to the channel.

Search for a package¹³² attribute name to find the one you're interested in building.

2.7.8 Real-world cross compiling of a Hello World example

The following example cross compiles a Hello World program as static executables to `armv6l-unknown-linux-gnueabi` and `x86_64-w64-mingw32` (Windows) platforms, and runs the resulting executable with an emulator¹³³.

Given we have a `cross-compile.nix`:

```

1 let
2   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/release-23.11";
3   pkgs = import nixpkgs {};
4
5   # Create a C program that prints Hello World
6   helloWorld = pkgs.writeText "hello.c" ''
7     #include <stdio.h>
8

```

(continues on next page)

¹³¹ <https://www.gnu.org/software/hello/>

¹³² <https://search.nixos.org/packages>

¹³³ <https://en.wikipedia.org/wiki/Emulator>

(continued from previous page)

```

9     int main (void)
10    {
11        printf ("Hello, world!\n");
12        return 0;
13    }
14    '';
15
16    # A function that takes host platform packages
17    crossCompileFor = hostPkgs:
18        # Run a simple command with the compiler available
19        hostPkgs.runCommandCC "hello-world-cross-test" {} ''
20            # Wine requires home directory
21            HOME=$PWD
22
23            # Compile our example using the compiler specific to our host platform
24            $CC ${helloWorld} -o hello
25
26            # Run the compiled program using user mode emulation (Qemu/Wine)
27            # buildPackages is passed so that emulation is built for the build platform
28            ${hostPkgs.stdenv.hostPlatform.emulator hostPkgs.buildPackages} hello > $out
29
30            # print to stdout
31            cat $out
32        '';
33    in {
34        # Statically compile our example using the two platform hosts
35        rpi = crossCompileFor pkgs.pkgsCross.raspberryPi;
36        windows = crossCompileFor pkgs.pkgsCross.mingwW64;
37    }

```

If we build this example and print both resulting derivations, we should see “Hello, world!” for each:

```

$ cat $(nix-build cross-compile.nix)
Hello, world!
Hello, world!

```

2.7.9 Developer environment with a cross compiler

In the *tutorial for declarative reproducible environments* (page 8), we looked at how Nix helps us provide tooling and system libraries for our project.

It’s also possible to provide an environment with a compiler configured for **cross-compilation to static binaries using musl**.

Given we have a shell.nix:

```

1  let
2      nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/release-23.11";
3      pkgs = (import nixpkgs {}).pkgsCross.aarch64-multiplatform;
4  in
5
6      # callPackage is needed due to https://github.com/NixOS/nixpkgs/pull/126844
7      pkgs.pkgsStatic.callPackage ({ mkShell, zlib, pkg-config, file }: mkShell {
8          # these tools run on the build platform, but are configured to target the host
9          ↪platform
10          nativeBuildInputs = [ pkg-config file ];
11          # libraries needed for the host platform

```

(continues on next page)

(continued from previous page)

```

11   buildInputs = [ zlib ];
12 }) {}

```

And `hello.c`:

```

#include <stdio.h>

int main (void)
{
    printf ("Hello, world!\n");
    return 0;
}

```

We can cross compile it:

```
$ nix-shell --run '$CC hello.c -o hello' shell.nix
```

And confirm it's aarch64:

```

$ nix-shell --run 'file hello' shell.nix
hello: ELF 64-bit LSB executable, ARM aarch64, version 1 (SYSV), statically_
↳ linked, with debug_info, not stripped

```

2.7.10 Next steps

- The [official binary cache](https://cache.nixos.org)¹³⁴ has a limited number of binaries for packages that are cross compiled, so to save time recompiling, configure *your own binary cache and CI with GitHub Actions* (page 143).
- While many compilers in Nixpkgs support cross compilation, not all of them do.
Additionally, supporting cross compilation is not trivial work and due to many possible combinations of what would need to be tested, some packages might not build.
A detailed explanation of how cross compilation is implemented in Nix¹³⁵ can help with fixing those issues.
- The Nix community has a [dedicated Matrix room](https://matrix.to/#/#cross-compiling:nixos.org)¹³⁶ for help with cross compiling.

2.8 Module system

Much of the power in Nixpkgs and NixOS comes from the module system.

The module system is a Nix language library that enables you to

- Declare one attribute set using many separate Nix expressions.
- Imposes type constraints on values in that attribute set.
- Define values for the same attribute in different Nix expressions and merge these values automatically according to their type.

These Nix expressions are called modules and must have a particular structure.

In this tutorial series you'll learn

- What a module is and how to create one.
- What options are and how to declare them.
- How to express dependencies between modules.

¹³⁴ <https://cache.nixos.org>

¹³⁵ <https://nixos.org/manual/nixpkgs/stable/#chap-cross>

¹³⁶ <https://matrix.to/#/#cross-compiling:nixos.org>

2.8.1 What do you need?

- Familiarity with data types and general programming concepts
- A *Nix installation* (page 1) to run the examples
- Intermediate proficiency in reading and writing the *Nix language* (page 12)

2.8.2 How long will it take?

This is a very long tutorial. Prepare for at least 3 hours of work.

A basic module

What is a module?

- A module is a function that takes an attribute set and returns an attribute set.
- It may declare options, telling which attributes are allowed in the final outcome.
- It may define values, for options declared by itself or other modules.
- When evaluated by the module system, it produces an attribute set based on the declarations and definitions.

The simplest possible module is a function that takes any attributes and returns an empty attribute set:

Listing 19: options.nix

```
{ ... }:  
{  
}
```

To define any values, the module system first has to know which ones are allowed. This is done by declaring *options* that specify which attributes can be set and used elsewhere.

Declaring options

Options are declared under the top-level `options` attribute with `lib.mkOption`¹³⁹.

Listing 20: options.nix

```
{ lib, ... }:  
{  
  options = {  
    name = lib.mkOption { type = lib.types.str; };  
  };  
}
```

Note

The `lib` argument is passed automatically by the module system. This makes *Nixpkgs library functions*¹⁴⁰ available in each module's function body.

The ellipsis `...` is necessary because the module system can pass arbitrary arguments to modules.

The attribute `type` in the argument to `lib.mkOption` specifies which values are valid for an option. There are several types available under `lib.types`¹⁴¹.

Here we have declared an option `name` of type `str`: The module system will expect a string when a value is defined.

¹³⁹ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.options.mkOption>

¹⁴⁰ <https://nixos.org/manual/nixpkgs/stable/#chap-functions>

¹⁴¹ <https://nixos.org/manual/nixos/stable/#sec-option-types-basic>

Now that we have declared an option, we would naturally want to give it a value.

Defining values

Options are set or *defined* under the top-level `config` attribute:

Listing 21: config.nix

```
{ ... }:  
{  
  config = {  
    name = "Boaty McBoatface";  
  };  
}
```

In our option declaration, we created an option `name` with a string type. Here, in our option definition, we have set that same option to a string.

Option declarations and option definitions don't need to be in the same file. Which modules will contribute to the resulting attribute set is specified when setting up module system evaluation.

Evaluating modules

Modules are evaluated by `lib.evalModules`¹⁴² from the Nixpkgs library. It takes an attribute set as an argument, where the `modules` attribute is a list of modules to merge and evaluate.

The output of `evalModules` contains information about all evaluated modules, and the final values appear in the attribute `config`.

Listing 22: default.nix

```
let  
  pkgs = import <nixpkgs> { };  
  result = pkgs.lib.evalModules {  
    modules = [  
      ./options.nix  
      ./config.nix  
    ];  
  };  
in  
result.config
```

Here's a helper script to parse and evaluate our `default.nix` file with `nix-instantiate --eval`¹⁴³ and print the output as JSON:

Listing 23: eval.bash

```
nix-shell -p jq --run "nix-instantiate --eval --json --strict | jq"
```

As long as every definition has a corresponding declaration, evaluation will be successful. If there is an option definition that has not been declared, or the defined value has the wrong type, the module system will throw an error.

Running the script (`./eval.bash`) should show an output that matches what we have configured:

```
{  
  "name": "Boaty McBoatface"  
}
```

¹⁴² <https://nixos.org/manual/nixpkgs/stable/#module-system-lib-evalModules>

¹⁴³ <https://nix.dev/manual/nix/stable/command-ref/nix-instantiate>

Module system deep dive

Or: *Wrapping the world in modules*

In this tutorial you will follow an extensive demonstration of how to wrap an existing API with Nix modules.

Overview

This tutorial follows [@infinisil¹⁴⁴](#)'s [presentation on modules¹⁴⁵](#) ([source¹⁴⁶](#)) for participants of [Summer of Nix¹⁴⁷](#) 2021.

It may help to play it alongside this tutorial to better keep track of changes to the code you will work on.

What will you learn?

You'll write modules to interact with the [Google Maps API¹⁴⁸](#), declaring module options which represent map geometry, location pins, and more.

During the tutorial, you will first write some *incorrect* configurations, creating opportunities to discuss the resulting error messages and how to resolve them, particularly when discussing type checking.

What do you need?

You will use two helper scripts for this exercise. Download `map.sh` and `geocode.sh` to your working directory.

Warning

To run the examples in this tutorial, you will need a [Google API key¹⁴⁹](#) in `$XDG_DATA_HOME/google-api/key`.

The empty module

Write the following into a file called `default.nix`:

Listing 24: `default.nix`

```
{ ... }:  
{  
  
}
```

Declaring options

We will need some helper functions, which will come from the [Nixpkgs library¹⁵⁰](#), which is passed by the module system as `lib`:

Listing 25: `default.nix`

```
- { ... }:  
+ { lib, ... }:  
{
```

(continues on next page)

¹⁴⁴ <https://github.com/infinisil>

¹⁴⁵ <https://infinisil.com/modules.mp4>

¹⁴⁶ <https://github.com/tweag/summer-of-nix-modules>

¹⁴⁷ <https://github.com/ngi-nix/summer-of-nix>

¹⁴⁸ <https://developers.google.com/maps/documentation/maps-static>

¹⁴⁹ <https://developers.google.com/maps/documentation/maps-static/start#before-you-begin>

¹⁵⁰ <https://github.com/NixOS/nixpkgs/tree/master/lib>

(continued from previous page)

```
}
```

Using `lib.mkOption`¹⁵¹, declare the `scripts.output` option to have the type `lines`:

Listing 26: default.nix

```
{ lib, ... }: {  
  
+ options = {  
+   scripts.output = lib.mkOption {  
+     type = lib.types.lines;  
+   };  
+ };  
  
}
```

The `lines` type means that the only valid values are strings, and that multiple definitions should be joined with newlines.

Note

The name and attribute path of the option is arbitrary. Here we use `scripts`, because we will add another script later, and call this one `output`, because it will output the resulting map.

Evaluating modules

Write a new file `eval.nix` to call `lib.evalModules`¹⁵² and evaluate the module in `default.nix`:

Listing 27: eval.nix

```
let  
  nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";  
  pkgs = import nixpkgs { config = {}; overlays = []; };  
in  
pkgs.lib.evalModules {  
  modules = [  
    ./default.nix  
  ];  
}
```

Run the following command:

¹⁵¹ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.options.mkOption>

¹⁵² <https://nixos.org/manual/nixpkgs/unstable/#module-system-lib-evalModules>

Warning

This will result in an error.

```
nix-instantiate --eval eval.nix -A config.scripts.output
```

Detailed explanation

`nix-instantiate --eval`¹⁵³ parses and evaluates the Nix file at the specified path, and prints the result. `evalModules` produces an attribute set where the final configuration values appear in the `config` attribute. Therefore we evaluate the Nix expression in `eval.nix` at the [attribute path](#)¹⁵⁴ `config.scripts.output`.

The error message indicates that the `scripts.output` option is used but not defined: a value must be set for the option before accessing it. You will do this in the next steps.

Type checking

As previously mentioned, the `lines` type only permits string values.

Warning

In this section, you will set an invalid value and encounter a type error.

What happens if you instead try to assign an integer to the option?

Add the following lines to `default.nix`:

Listing 28: `default.nix`

```
{ lib, ... }: {

  options = {
    scripts.output = lib.mkOption {
      type = lib.types.lines;
    };
  };

+ config = {
+   scripts.output = 42;
+ };
}
```

Now try to execute the previous command, and witness your first module error:

```
$ nix-instantiate --eval eval.nix -A config.scripts.output
error:
...
    error: A definition for option `scripts.output' is not of type `strings_
↳ concatenated with "\n". Definition values:
    - In `/home/nix-user/default.nix': 42
```

The definition `scripts.output = 42;` caused a type error: integers are not strings concatenated with the newline character.

¹⁵³ <https://nix.dev/manual/nix/stable/command-ref/nix-instantiate>

¹⁵⁴ <https://nix.dev/manual/nix/stable/language/operators#attribute-selection>

To make this module pass the type checks and successfully evaluate the `scripts.output` option, you will now assign a string to `scripts.output`.

In this case, you will assign a shell command that runs the `map` script in the current directory. That in turn calls the Google Maps Static API to generate a world map. The output is passed on to display it with `feh`¹⁵⁵, a minimalistic image viewer.

Update `default.nix` by changing the value of `scripts.output` to the following string:

Listing 29: default.nix

```
config = {
-   scripts.output = 42;
+   scripts.output = ''
+     ./map.sh size=640x640 scale=2 | feh -
+     '';
};
```

Interlude: reproducible scripts

That simple command will likely not work as intended on your system, as it may lack the required dependencies (`curl` and `feh`). We can solve this by packaging the raw `map` script with `pkgs.writeShellApplication`.

First, make available a `pkgs` argument in your module evaluation by adding a module that sets `config._module.args`:

Listing 30: eval.nix

```
pkgs.lib.evalModules {
  modules = [
+   ({ config, ... }: { config._module.args = { inherit pkgs; }; })
    ./default.nix
  ];
}
```

Note

This mechanism is currently only documented in the module system code¹⁵⁶, and that documentation is incomplete and out of date.

Then change `default.nix` to have the following contents:

Listing 31: default.nix

```
{ pkgs, lib, ... }: {

  options = {
    scripts.output = lib.mkOption {
      type = lib.types.package;
    };
  };

  config = {
    scripts.output = pkgs.writeShellApplication {
      name = "map";
      runtimeInputs = with pkgs; [ curl feh ];
    };
  };
}
```

(continues on next page)

¹⁵⁵ <https://feh.finalrewind.org/>

¹⁵⁶ <https://github.com/NixOS/nixpkgs/blob/master/lib/modules.nix#L140-L182>

(continued from previous page)

```

    text = ''
        ${./map.sh} size=640x640 scale=2 | feh -
    '';
};
}

```

This will access the previously added `pkgs` argument so we can use dependencies, and copy the `map` file in the current directory into the Nix store so it's available to the wrapped script, which will also live in the Nix store.

Run the script with:

```

nix-build eval.nix -A config.scripts.output
./result/bin/map

```

To iterate more quickly, open a new terminal and set up `entr`¹⁵⁷ to re-run the script whenever any source file in the current directory changes:

```

nix-shell -p entr findutils bash --run \
"ls *.nix | \
  entr -rs ' \
    nix-build eval.nix -A config.scripts.output --no-out-link \
    | xargs printf -- \"%s/bin/map\" \
    | xargs bash \
  ' \
"

```

This command does the following:

- List all `.nix` files
- Make `entr` watch them for changes. Terminate the invoked command on each change with `-r`.
- On each change:
 - Run the `nix-build` invocation as above, but without adding a `./result` symlink
 - Take the resulting store path and append `/bin/map` to it
 - Run the executable at the path constructed this way

Declaring more options

Rather than setting all script parameters directly, we will do that through the module system. This will not just add some safety through type checking, but also allow building abstractions to manage growing complexity and changing requirements.

Let's begin by introducing another option, `requestParams`, which will represent the parameters of the request made to the Google Maps API.

Its type will be `listOf <elementType>`, which is a list of elements of one type.

Instead of `lines`, in this case you will want the type of the list elements to be `str`, a generic string type.

The difference between `str` and `lines` is in their merging behavior: Module option types not only check for valid values, but also specify how multiple definitions of an option are to be combined into one.

- For `lines`, multiple definitions get merged by concatenation with newlines.
- For `str`, multiple definitions are not allowed. This is not a problem here, since one can't define a list element multiple times.

Make the following additions to your `default.nix` file:

¹⁵⁷ <https://github.com/eradman/entr>

Listing 32: default.nix

```

    scripts.output = lib.mkOption {
      type = lib.types.package;
    };
+
+   requestParams = lib.mkOption {
+     type = lib.types.listOf lib.types.str;
+   };
+
+   };

  config = {
    scripts.output = pkgs.writeShellApplication {
      name = "map";
      runtimeInputs = with pkgs; [ curl feh ];
      text = ''
        ${./map.sh} size=640x640 scale=2 | feh -
      '';
    };
+
+   requestParams = [
+     "size=640x640"
+     "scale=2"
+   ];
+
+   };
}

```

Dependencies between options

A given module generally declares one option that produces a result to be used elsewhere, in this case `scripts.output`.

Options can depend on other options, making it possible to build more useful abstractions.

Here, we want the `scripts.output` option to use the values of `requestParams` as arguments to the `./map` script.

Accessing option values

To make option values available to a module, the arguments of the function declaring the module must include the `config` attribute.

Update `default.nix` to add the `config` attribute:

Listing 33: default.nix

```

-{ pkgs, lib, ... }: {
+{ pkgs, lib, config, ... }: {

```

When a module that sets options is evaluated, the resulting values can be accessed by their corresponding attribute names under `config`.

Note

Option values can't be accessed directly from the same module.

The module system evaluates all modules it receives, and any of them can define a particular option's value. What happens when an option is set by multiple modules is determined by that option's type.

Warning

The `config` *argument* is **not** the same as the `config` *attribute*:

- The `config` *argument* holds the result of the module system's lazy evaluation, which takes into account all modules passed to `evalModules` and their imports.
- The `config` *attribute* of a module exposes that particular module's option values to the module system for evaluation.

Now make the following changes to `default.nix`:

Listing 34: `default.nix`

```
config = {
  scripts.output = pkgs.writeShellApplication {
    name = "map";
    runtimeInputs = with pkgs; [ curl feh ];
    text = ''
-     ${./map.sh} size=640x640 scale=2 | feh -
+     ${./map.sh} ${lib.concatStringsSep " "
+       config.requestParams} | feh -
    '';
  }
```

Here, the value of the `config.requestParams` attribute is populated by the module system based on the definitions in the same file.

Note

Lazy evaluation in the Nix language allows the module system to make a value available in the `config` argument passed to the module which defines that value.

`lib.concatStringsSep " "` is then used to join each list element from the value of `config.requestParams` into a single string, with the list elements of `requestParams` separated by a space character.

The result of this represents the list of command line arguments to pass to the `./map` script.

Conditional definitions

Sometimes, you will want option values to be optional. This can be useful when defining a value for an option is not required, as in the following case.

You will define a new option, `map.zoom`, to control the zoom level of the map. The Google Maps API will infer a zoom level if no corresponding argument is passed, a situation you can represent with the `nullOr <type>`, which represents values of type `<type>` or `null`. This *does not* automatically mean that when the option isn't defined, the value of such an option is `null` – we still need to define a default value.

Add the `map` attribute set with the `zoom` option into the top-level `options` declaration, like so:

Listing 35: `default.nix`

```
requestParams = lib.mkOption {
  type = lib.types.listOf lib.types.str;
};

+
+ map = {
+   zoom = lib.mkOption {
+     type = lib.types.nullOr lib.types.int;
+     default = null;
+   }
```

(continues on next page)

(continued from previous page)

```
+     };
+     };
+ };
```

To make use of this, use the `mkIf <condition> <definition>` function, which only adds the definition if the condition evaluates to `true`. Make the following additions to the `requestParams` list in the `config` block:

Listing 36: default.nix

```
requestParams = [
  "size=640x640"
  "scale=2"
+   (lib.mkIf (config.map.zoom != null)
+     "zoom=${toString config.map.zoom}")
];
```

This will only add a `zoom` parameter to the script invocation if the value of `config.map.zoom` is not `null`.

Default values

Let's say that in our application we want to have a different default behavior that sets the zoom level to 10, such that automatic zooming has to be enabled explicitly.

This can be done with the `default` argument to `mkOption`¹⁵⁸. Its value will be used if the value of the option declaring it is not specified otherwise.

Modify the corresponding line:

Listing 37: default.nix

```
map = {
  zoom = lib.mkOption {
    type = lib.types.nullOr lib.types.int;
-   default = null;
+   default = 10;
  };
};
```

Wrapping shell commands

You have now declared options controlling the map dimensions and zoom level, but have not provided a way to specify where the map should be centered.

Add the `center` option now, possibly with your own location as default value:

Listing 38: default.nix

```
type = lib.types.nullOr lib.types.int;
default = 10;
};
+
+   center = lib.mkOption {
+     type = lib.types.nullOr lib.types.str;
+     default = "switzerland";
+   };
```

(continues on next page)

¹⁵⁸ <https://github.com/NixOS/nixpkgs/blob/master/lib/options.nix>

(continued from previous page)

```
};
};
```

To implement this behavior, you will use the `geocode` utility, which turns location names into coordinates. There are multiple ways of making a new package accessible, but as an exercise, you will add it as an option in the module system.

First, add a new option to accommodate the package:

Listing 39: default.nix

```
options = {
  scripts.output = lib.mkOption {
    type = lib.types.package;
  };
+
+   scripts.geocode = lib.mkOption {
+     type = lib.types.package;
+   };
+ }
```

Then define the value for that option where you make the raw script reproducible by wrapping a call to it in `writeShellApplication`:

Listing 40: default.nix

```
config = {
+   scripts.geocode = pkgs.writeShellApplication {
+     name = "geocode";
+     runtimeInputs = with pkgs; [ curl jq ];
+     text = ''exec ${./geocode.sh} "$@"'';
+   };
+
  scripts.output = pkgs.writeShellApplication {
    name = "map";
    runtimeInputs = with pkgs; [ curl feh ];
  };
}
```

Add another `mkIf` call to the list of `requestParams` now where you access the wrapped package through `config.scripts.geocode`, and run the executable `/bin/geocode` inside:

Listing 41: default.nix

```
"scale=2"
(lib.mkIf (config.map.zoom != null)
  "zoom=${toString config.map.zoom}")
+ (lib.mkIf (config.map.center != null)
+   "center=\"${config.scripts.geocode}/bin/geocode ${
+     lib.escapeShellArg config.map.center
+   }\"" )
+ ];
};
```

This time, you've used `escapeShellArg` to pass the `config.map.center` value as a command-line argument to `geocode`, string interpolating the result back into the `requestParams` string which sets the `center` value.

Wrapping shell command execution in Nix modules is a helpful technique for controlling system changes, as it uses the more ergonomic attributes and values interface rather than dealing with the peculiarities of escaping manually.

Splitting modules

The `module schema`¹⁵⁹ includes the `imports` attribute, which allows incorporating further modules, for example to split a large configuration into multiple files.

In particular, this allows you to separate option declarations from where they are used in your configuration.

Create a new module, `marker.nix`, where you can declare options for defining location pins and other markers on the map:

Listing 42: `marker.nix`

```
{ lib, config, ... }: {
}
```

Reference this new file in `default.nix` using the `imports` attribute:

Listing 43: `default.nix`

```
{ pkgs, lib, config, ... }: {
+ imports = [
+   ./marker.nix
+ ];
+ }
```

The submodule type

We want to set multiple markers on the map. A marker is a complex type with multiple fields.

This is where one of the most useful types included in the module system's type system comes into play: `submodule`. This type allows you to define nested modules with their own options.

Here, you will define a new `map.markers` option whose type is a list of submodules, each with a nested `location` type, allowing you to define a list of markers on the map.

Each assignment of markers will be type-checked during evaluation of the top-level `config`.

Make the following changes to `marker.nix`:

Listing 44: `marker.nix`

```
-{ lib, config, ... }: {
+{ lib, config, ... }:
+let
+  markerType = lib.types.submodule {
+    options = {
+      location = lib.mkOption {
+        type = lib.types.nullOr lib.types.str;
+        default = null;
+      };
+    };
+  };
+in {
+  options = {
+    map.markers = lib.mkOption {
+      type = lib.types.listOf markerType;
```

(continues on next page)

¹⁵⁹ <https://nixos.org/manual/nixos/stable/#sec-writing-modules>

(continued from previous page)

```
+ };
+ };
```

Defining options in other modules

Because of the way the module system composes option definitions, you can freely assign values to options defined in other modules.

In this case, you will use the `map.markers` option to produce and add new elements to the `requestParams` list, making your declared markers appear on the returned map – but from the module declared in `marker.nix`.

To implement this behavior, add the following `config` block to `marker.nix`:

Listing 45: `marker.nix`

```
+ config = {
+
+   map.markers = [
+     { location = "new york"; }
+   ];
+
+   requestParams = let
+     paramForMarker =
+       builtins.map (marker: "${config.scripts.geocode}/bin/geocode ${
+         lib.escapeShellArg marker.location})" config.map.markers;
+   in [ "markers=\"${lib.concatStringsSep " " paramForMarker}\"" ];
+ };
```

Warning

To avoid confusion with the `map` option setting and the final `config.map` configuration value, here we use the `map` function explicitly as `builtins.map`.

Here, you again used `escapeShellArg` and string interpolation to generate a Nix string, this time producing a pipe-separated list of geocoded location attributes.

The `requestParams` value was also set to the resulting list of strings, which gets appended to the `requestParams` list defined in `default.nix`, thanks to the default merging behavior of the `list` type.

When defining multiple markers, determining an appropriate center or zoom level for the map may be challenging; it's easier to let the API do this for you.

To achieve this, make the following additions to `marker.nix`, above the `requestParams` declaration:

Listing 46: `marker.nix`

```
+   map.center = lib.mkIf
+     (lib.length config.map.markers >= 1)
+     null;
+
+   map.zoom = lib.mkIf
+     (lib.length config.map.markers >= 2)
+     null;
+
+   requestParams = let
+     paramForMarker = marker:
+       let
```

In this case, the default behavior of the Google Maps API when not passed a center or zoom level is to pick the geometric center of all the given markers, and to set a zoom level appropriate for viewing all markers at once.

Nested submodules

Next, we want to allow multiple named users to define a list of markers each.

For that you'll add a `users` option with type `lib.types.attrsOf <subtype>`, which will allow you to define users as an attribute set, whose values have type `<subtype>`.

Here, that subtype will be another submodule which allows declaring a departure marker, suitable for querying the API for the recommended route for a trip.

This will again make use of the `markerType` submodule, giving a nested structure of submodules.

To propagate marker definitions from `users` to the `map.markers` option, make the following changes.

In the `let` block:

Listing 47: `marker.nix`

```
+ userType = lib.types.submodule {
+   options = {
+     departure = lib.mkOption {
+       type = markerType;
+       default = {};
+     };
+   };
+ };
+
+ in {
```

This defines a submodule type for a user, with a `departure` option of type `markerType`.

In the `options` block, above `map.markers`:

Listing 48: `marker.nix`

```
+ users = lib.mkOption {
+   type = lib.types.attrsOf userType;
+ };
```

That allows adding a `users` attribute set to `config` in any submodule that imports `marker.nix`, where each attribute will be of type `userType` as declared in the previous step.

In the `config` block, above `map.center`:

Listing 49: `marker.nix`

```
config = {

-   map.markers = [
-     { location = "new york"; }
-   ];
+   map.markers = lib.filter
+     (marker: marker.location != null)
+     (lib.concatMap (user: [
+       user.departure
+     ]) (lib.attrValues config.users));

  map.center = lib.mkIf
    (lib.length config.map.markers >= 1)
```


(continued from previous page)

```

+         lib.escapeShellArg marker.location
+     }) "
+
+     };
+     in "markers=\"${lib.concatStringsSep " | " attributes}\"";
+     in
+     builtins.map paramForMarker config.map.markers;

```

Note how we now create a unique marker for each user by concatenating the `label` and `location` attributes together, and assigning them to the `requestParams`. The label for each marker is only propagated to the CLI parameters if `marker.style.label` is set.

Functions as submodule arguments

Right now, if a label is not explicitly set, none will show up. But since every `users` attribute has a name, we could use that as an automatic value instead.

This `firstUpperAlnum` function allows you to retrieve the first character of the username, with the correct type for passing to `departure.style.label`:

Listing 52: marker.nix

```

{ lib, config, ... }:
let
+   # Returns the uppercased first letter
+   # or number of a string
+   firstUpperAlnum = str:
+     lib.mapNullable lib.head
+     (builtins.match "[^A-Z0-9]*([A-Z0-9]).*"
+     (lib.toUpper str));

  markerType = lib.types.submodule {
    options = {

```

By transforming the argument to `lib.types.submodule` into a function, you can access arguments within it.

One special argument automatically available to submodules is `name`, which when used in `attrsOf`, gives you the name of the attribute the submodule is defined under:

Listing 53: marker.nix

```

-   userType = lib.types.submodule {
+   userType = lib.types.submodule ({ name, ... }: {
    options = {
      departure = lib.mkOption {
        type = markerType;
        default = {};
      };
    };
-   };

```

In this case, you don't easily have access to the name from the marker submodules `label` option, where you otherwise could set a default value.

Instead you can use the `config` section of the `user` submodule to set a default, like so:

Listing 54: marker.nix

```

+
+   config = {

```

(continues on next page)

(continued from previous page)

```

+     departure.style.label = lib.mkDefault
+       (firstUpperAlnum name);
+   };
+ });

in {

```

Note

Module options have a *priority*, represented as an integer, which determines the precedence for setting the option to a particular value. When merging values, the priority with lowest numeric value wins.

The `lib.mkDefault` modifier sets the priority of its argument value to 1000, the lowest precedence.

This ensures that other values set for the same option will prevail.

The `either` and `enum` types

For better visual contrast, it would be helpful to have a way to change the *color* of a marker.

Here you will use two new type-functions for this:

- `either <this> <that>`, which takes two types as arguments, and allows either of them
- `enum [ <allowed values> ]`, which takes a list of allowed values, and allows any of them

In the `let` block, add the following `colorType` option, which can hold strings containing either some given color names or an RGB value, add the new compound type:

Listing 55: marker.nix

```

...
(builtins.match "[^A-Z0-9]*([A-Z0-9]).*"
(lib.toUpper str));

+ # Either a color name or `0xRRGGBB`
+ colorType = lib.types.either
+   (lib.types.strMatching "0x[0-9A-F]{6}")
+   (lib.types.enum [
+     "black" "brown" "green" "purple" "yellow"
+     "blue" "gray" "orange" "red" "white" ]);
+
markerType = lib.types.submodule {
  options = {
    location = lib.mkOption {

```

This allows either strings that match a 24-bit hexadecimal number or are equal to one of the specified color names.

At the bottom of the `let` block, add the `style.color` option and specify a default value:

Listing 56: marker.nix

```

    (lib.types.strMatching "[A-Z0-9]");
    default = null;
  };

+
+   style.color = lib.mkOption {
+     type = colorType;
+     default = "red";

```

(continues on next page)

(continued from previous page)

```
+     };
+     };
+     };
```

Now add an entry to the `paramForMarker` list which makes use of the new option:

Listing 57: marker.nix

```
        (marker.style.label != null)
        "label:${marker.style.label}"
++ [
+     "color:${marker.style.color}"
+     "${(config.scripts.geocode)/bin/geocode ${
+         lib.escapeShellArg marker.location
+     }}"
```

In case you set many different markers, it would be helpful to have the ability to change their size individually.

Add a new `style.size` option to `marker.nix`, allowing you to choose from the set of pre-defined sizes:

Listing 58: marker.nix

```
        type = colorType;
        default = "red";
    };
+
+     style.size = lib.mkOption {
+         type = lib.types.enum
+         [ "tiny" "small" "medium" "large" ];
+         default = "medium";
+     };
+
+ };
+
+ };
```

Now add a mapping for the size parameter in `paramForMarker`, which selects an appropriate string to pass to the API:

Listing 59: marker.nix

```
requestParams = let
    paramForMarker = marker:
        let
+         size = {
+             tiny = "tiny";
+             small = "small";
+             medium = "mid";
+             large = null;
+         }.${marker.style.size};
+
+ 
```

Finally, add another `lib.optional` call to the `attributes` string, making use of the selected size:

Listing 60: marker.nix

```
attributes =
    lib.optional
        (marker.style.label != null)
        "label:${marker.style.label}"
```

(continues on next page)

(continued from previous page)

```

+         ++ lib.optional
+         (size != null)
+         "size:${size}"
+     ++ [
+         "color:${marker.style.color}"
+         "${config.scripts.geocode}/bin/geocode ${

```

The `pathType` submodule

So far, you've created an option for declaring a *departure* marker, as well as several options for configuring the marker's visual representation.

Now we want to compute and display a route from the user's location to some destination.

The new option defined in the next section will allow you to set an *arrival* marker, which together with a departure allows you to draw *paths* on the map using the new module defined below.

To start, create a new `path.nix` file with the following contents:

Listing 61: `path.nix`

```

{ lib, config, ... }:
let
  pathType = lib.types.submodule {
    options = {
      locations = lib.mkOption {
        type = lib.types.listOf lib.types.str;
      };
    };
  };
in
{
  options = {
    map.paths = lib.mkOption {
      type = lib.types.listOf pathType;
    };
  };
  config = {
    requestParams =
      let
        attrForLocation = loc:
          "${config.scripts.geocode}/bin/geocode ${lib.escapeShellArg loc}";
        paramForPath = path:
          let
            attributes =
              builtins.map attrForLocation path.locations;
          in
            "'path=${lib.concatStringsSep "|" attributes}";
      in
        builtins.map paramForPath config.map.paths;
  };
}

```

The `path.nix` module declares an option for defining a list of paths on our map, where each path is a list of strings for geographic locations.

In the `config` attribute we augment the API call by setting the `requestParams` option value with the coordinates transformed appropriately, which will be concatenated with request parameters set elsewhere.

Now import this new `path.nix` module from your `marker.nix` module:

Listing 62: `marker.nix`

```
in {  
  
+ imports = [  
+   ./path.nix  
+ ];  
+  
  options = {  
  
    users = lib.mkOption {
```

Copy the `departure` option declaration to a new `arrival` option in `marker.nix`, to complete the initial path implementation:

Listing 63: `marker.nix`

```
      type = markerType;  
      default = {};  
    };  
+  
+   arrival = lib.mkOption {  
+     type = markerType;  
+     default = {};  
+   };  
};
```

Next, add an `arrival.style.label` attribute to the `config` block, mirroring the `departure.style.label`:

Listing 64: `marker.nix`

```
  config = {  
    departure.style.label = lib.mkDefault  
      (firstUpperAlnum name);  
+    arrival.style.label = lib.mkDefault  
+      (firstUpperAlnum name);  
  };  
});
```

Finally, update the return list in the function passed to `concatMap` in `map.markers` to also include the `arrival` marker for each user:

Listing 65: `marker.nix`

```
  map.markers = lib.filter  
    (marker: marker.location != null)  
    (lib.concatMap (user: [  
-     user.departure  
+     user.departure user.arrival  
    ]) (lib.attrValues config.users));  
  
  map.center = lib.mkIf
```

Now you have the basis to define paths on the map, connecting pairs of departure and arrival points.

In the `path` module, define a path connecting every user's departure and arrival locations:

Listing 66: path.nix

```

config = {
+
+   map.paths = builtins.map (user: {
+       locations = [
+         user.departure.location
+         user.arrival.location
+       ];
+     }) (lib.filter (user:
+       user.departure.location != null
+       && user.arrival.location != null
+     ) (lib.attrValues config.users));
+
  requestParams = let
    attrForLocation = loc:
      "$(geocode ${lib.escapeShellArg loc})";

```

The new `map.paths` attribute contains a list of all valid paths defined for all users.

A path is valid only if the `departure` and `arrival` attributes are set for that user.

The between constraint on integer values

Your users have spoken, and they demand the ability to customize the styles of their paths with a `weight` option.

As before, you'll now declare a new submodule for the path style.

While you could also directly declare the `style.weight` option, in this case you should use the submodule to be able to reuse the path style type later.

Add the `pathStyleType` submodule option to the `let` block in `path.nix`:

Listing 67: path.nix

```

{ lib, config, ... }:
let
+
+   pathStyleType = lib.types.submodule {
+     options = {
+       weight = lib.mkOption {
+         type = lib.types.ints.between 1 20;
+         default = 5;
+       };
+     };
+   };
+
+   pathType = lib.types.submodule {

```

Note

The `ints.between <lower> <upper>` type allows integers in the given (inclusive) range.

The path weight will default to 5, but can be set to any integer value in the 1 to 20 range, with higher weights producing thicker paths on the map.

Now add a `style` option to the `options` set further down the file:

Listing 68: path.nix

```

options = {
  locations = lib.mkOption {
    type = lib.types.listOf lib.types.str;
  };
+
+   style = lib.mkOption {
+     type = pathStyleType;
+     default = {};
+   };
};

};

```

Finally, update the `attributes` list in `paramForPath`:

Listing 69: path.nix

```

paramForPath = path:
  let
    attributes =
-     builtins.map attrForLocation path.locations;
+     [
+       "weight:${toString path.style.weight}"
+     ]
+     ++ builtins.map attrForLocation path.locations;
  in "path=\"${lib.concatStringsSep "|" attributes}\"";

```

The `pathStyle` submodule

Users still cannot actually customize the path style yet. Introduce a new `pathStyle` option for each user.

The module system allows you to declare values for an option multiple times, and if the types permit doing so, takes care of merging each declaration's values together.

This makes it possible to have a definition for the `users` option in the `marker.nix` module, as well as a `users` definition in `path.nix`:

Listing 70: path.nix

```

in {
  options = {
+
+   users = lib.mkOption {
+     type = lib.types.attrsOf (lib.types.submodule {
+       options.pathStyle = lib.mkOption {
+         type = pathStyleType;
+         default = {};
+       };
+     });
+   };
+
  map.paths = lib.mkOption {
    type = lib.types.listOf pathType;
  };
}

```

Then add a line using the `user.pathStyle` option in `map.paths` where each user's paths are processed:

Listing 71: path.nix

```

        user.departure.location
        user.arrival.location
    ];
+   style = user.pathStyle;
}) (lib.filter (user:
    user.departure.location != null
    && user.arrival.location != null

```

Path styling: color

As with markers, paths should have customizable colors.

You can accomplish this using types you've already encountered by now.

Add a new `colorType` block to `path.nix`, specifying the allowed color names and RGB/RGBA hexadecimal values:

Listing 72: path.nix

```

{ lib, config, ... }:
let
+   # Either a color name, `0xRRGGBB` or `0xRRGGBBAA`
+   colorType = lib.types.either
+     (lib.types.strMatching "0x[0-9A-F]{6}([0-9A-F]{2})?")
+     (lib.types.enum [
+       "black" "brown" "green" "purple" "yellow"
+       "blue" "gray" "orange" "red" "white"
+     ]);
+
+   pathStyleType = lib.types.submodule {

```

Under the `weight` option, add a new `color` option to use the new `colorType` value:

Listing 73: path.nix

```

        type = lib.types.ints.between 1 20;
        default = 5;
    };
+
+   color = lib.mkOption {
+     type = colorType;
+     default = "blue";
+   };
+
+   };
};

```

Finally, add a line using the `color` option to the `attributes` list:

Listing 74: path.nix

```

        attributes =
        [
            "weight:${toString path.style.weight}"
+           "color:${path.style.color}"
        ]

```

(continues on next page)

(continued from previous page)

```

    ++ map attrForLocation path.locations;
  in "path=${

```

Further styling

Now that you’ve got this far, to further improve the aesthetics of the rendered map, add another style option allowing paths to be drawn as *geodesics*, the shortest “as the crow flies” distance between two points on Earth.

Since this feature can be turned on or off, you can do this using the `bool` type, which can be `true` or `false`.

Make the following changes to `path.nix` now:

Listing 75: `path.nix`

```

    type = colorType;
    default = "blue";
  };
+
+   geodesic = lib.mkOption {
+     type = lib.types.bool;
+     default = false;
+   };
+   };
+ };
+ };

```

Make sure to also add a line to use that value in `attributes` list, so the option value is included in the API call:

Listing 76: `path.nix`

```

    [
      "weight:${toString path.style.weight}"
      "color:${path.style.color}"
+     "geodesic:${lib.boolToString path.style.geodesic}"
    ]
    ++ map attrForLocation path.locations;
  in "path=${

```

Wrapping up

In this tutorial, you’ve learned how to write custom Nix modules to bring external services under declarative control, with the help of several new utility functions from the Nixpkgs `lib`.

You defined several modules in multiple files, each with separate submodules making use of the module system’s type checking.

These modules exposed features of the external API in a declarative way.

You can now conquer the world with Nix.

2.9 NixOS

Learn how to configure, test, and install or deploy NixOS.

2.9.1 Creating NixOS images

- *NixOS virtual machines* (page 97)
- *Building a bootable ISO image* (page 102)

- *Building and running Docker images* (page 103)

2.9.2 Testing and deploying NixOS configurations

- *Integration testing with NixOS virtual machines* (page 105)
- *Provisioning remote machines via SSH* (page 111)
- *Installing NixOS on a Raspberry Pi* (page 116)
- *Deploying NixOS using Terraform* (page 120)

2.9.3 Scaling up

- *Setting up an HTTP binary cache* (page 123)
- *Setting up distributed builds* (page 127)

NixOS virtual machines

One of the most important features of NixOS is the ability to configure the entire system declaratively, including packages to be installed, services to be run, as well as other settings and options.

NixOS configurations can be used to test and use NixOS using a virtual machine, which is a lighter weight option compared to a full “bare metal” installation.

What will you learn?

This tutorial serves as an introduction to creating NixOS virtual machines. Virtual machines are a practical tool for experimenting with or debugging NixOS configurations.

What do you need?

- A Linux system with virtualisation support
- (optional) A graphical environment for running a graphical virtual machine
- A working Nix installation¹⁶¹
- Basic knowledge of the *Nix language* (page 12)

Important

A NixOS configuration is a Nix language function following the *NixOS module*¹⁶² convention. For a thorough treatment of the module system, check the *Module system deep dive* (page 75) tutorial.

Starting from a default NixOS configuration

Note

This tutorial starts with building up your `configuration.nix` from first principles, explaining each step. If you prefer, you can skip ahead to the *sample configuration* (page 98) section.

We start with a minimal `configuration.nix`:

¹⁶¹ <https://nix.dev/install-nix>

¹⁶² <https://nixos.org/manual/nixos/stable/index.html#sec-writing-modules>

```

1 { config, pkgs, ... }:
2
3 {
4   boot.loader.systemd-boot.enable = true;
5   boot.loader.efi.canTouchEfiVariables = true;
6
7   system.stateVersion = "24.05";
8 }

```

To be able to log in, add the following lines to the returned attribute set:

```

1 users.users.alice = {
2   isNormalUser = true;
3   extraGroups = [ "wheel" ];
4 };

```

Additionally, you need to specify a password for this user. For the purpose of demonstration only, you specify an insecure, plain text password by adding the `initialPassword` option to the user configuration:

```

1   initialPassword = "test";

```

We add two lightweight programs as an example:

```

1 environment.systemPackages = with pkgs; [
2   cowsay
3   lolcat
4 ];

```

Warning

Do not use plain text passwords outside of this example unless you know what you are doing. See `initialHashedPassword`¹⁶³ or `ssh.authorizedKeys`¹⁶⁴ for more secure alternatives.

Sample configuration

The complete `configuration.nix` file looks like this:

```

1 { config, pkgs, ... }:
2 {
3   boot.loader.systemd-boot.enable = true;
4   boot.loader.efi.canTouchEfiVariables = true;
5
6   users.users.alice = {
7     isNormalUser = true;
8     extraGroups = [ "wheel" ]; # Enable 'sudo' for the user.
9     initialPassword = "test";
10  };
11
12  environment.systemPackages = with pkgs; [
13    cowsay
14    lolcat
15  ];
16

```

(continues on next page)

¹⁶³ https://nixos.org/manual/nixos/stable/options.html#opt-users.extraUsers._name_.initialHashedPassword

¹⁶⁴ https://nixos.org/manual/nixos/stable/options.html#opt-users.extraUsers._name_.openssh.authorizedKeys.keys

(continued from previous page)

```

17   system.stateVersion = "24.05";
18 }

```

Creating a QEMU based virtual machine from a NixOS configuration

A NixOS virtual machine is created with the `nix-build` command:

```

$ nix-build '<nixpkgs/nixos>' -A vm -I nixpkgs=channel:nixos-24.05 -I
↪nixos-config=./configuration.nix

```

This command builds the attribute `vm` from the `nixos-24.05` release of NixOS, using the NixOS configuration as specified in the relative path.

Detailed explanation

- The positional argument to `nix-build`¹⁶⁵ is a path to the derivation to be built. That path can be obtained from *a Nix expression that evaluates to a derivation* (page 36).

The virtual machine build helper is defined in NixOS, which is part of the `nixpkgs` repository¹⁶⁶. Therefore we use the *lookup path* (page 25) `<nixpkgs/nixos>`.

- The `-A` option¹⁶⁷ specifies the attribute to pick from the provided Nix expression `<nixpkgs/nixos>`.

To build the virtual machine, we choose the `vm` attribute as defined in `nixos/default.nix`¹⁶⁸.

- The `-I` option¹⁶⁹ prepends entries to the search path.

Here we set `nixpkgs` to refer to a *specific version of Nixpkgs* (page 156) and set `nix-config` to the `configuration.nix` file in the current directory.

Running the virtual machine

The previous command created a link with the name `result` in the working directory. It links to the directory that contains the virtual machine.

```

$ ls -R ./result
result:
bin system

result/bin:
run-nixos-vm

```

Run the virtual machine:

```

$ QEMU_KERNEL_PARAMS=console=ttyS0 ./result/bin/run-nixos-vm -nographic; reset

```

This command will run QEMU in the current terminal due to `-nographic`. `console=ttyS0` will also show the boot process, which ends at the console login screen.

Log in as `alice` with the password `test`. Check that the programs are indeed available as specified:

```

$ cowsay hello | lolcat

```

Exit the virtual machine by shutting it down:

¹⁶⁵ <https://nix.dev/manual/nix/stable/command-ref/nix-build.html>

¹⁶⁶ <https://github.com/NixOS/nixpkgs>

¹⁶⁷ <https://nix.dev/manual/nix/stable/command-ref/opt-common.html#opt-attr>

¹⁶⁸ <https://github.com/NixOS/nixpkgs/blob/7c164f4bea71d74d98780ab7be4f9105630a2eba/nixos/default.nix#L19>

¹⁶⁹ <https://nix.dev/manual/nix/stable/command-ref/opt-common.html#opt-I>

```
$ sudo poweroff
```

Note

If you forgot to add the user to `wheel` or didn't set a password, stop the virtual machine from a different terminal:

```
$ sudo pkill qemu
```

Running the virtual machine will create a `nixos.qcow2` file in the current directory. This disk image file contains the dynamic state of the virtual machine. It can interfere with debugging as it keeps the state of previous runs, for example the user password.

Delete this file when you change the configuration:

```
$ rm nixos.qcow2
```

Running GNOME on a graphical VM

To create a virtual machine with a graphical user interface, add the following lines to the configuration:

```
1 # Enable the X11 windowing system.
2 services.xserver.enable = true;
3
4 # Enable the GNOME Desktop Environment.
5 services.xserver.displayManager.gdm.enable = true;
6 services.xserver.desktopManager.gnome.enable = true;
```

These three lines activate X11, the GDM display manager (to be able to login) and Gnome as desktop manager.

Tip

You can also use the `installation-cd-graphical-gnome.nix` module to generate the configuration file from scratch:

```
nix-shell -I nixpkgs=channel:nixos-24.05 -p "$(cat <<EOF
  let
    pkgs = import <nixpkgs> { config = {}; overlays = []; };
    iso-config = pkgs.path + /
    ↪nixos/modules/installer/cd-dvd/installation-cd-graphical-gnome.nix;
    nixos = pkgs.nixos iso-config;
  in nixos.config.system.build.nixos-generate-config
EOF
) "
```

```
$ nixos-generate-config --dir ./
```

The complete `configuration.nix` file looks like this:

```
1 { config, pkgs, ... }:
2 {
3   boot.loader.systemd-boot.enable = true;
4   boot.loader.efi.canTouchEfiVariables = true;
5
6   services.xserver.enable = true;
7
```

(continues on next page)

(continued from previous page)

```

8  services.xserver.displayManager.gdm.enable = true;
9  services.xserver.desktopManager.gnome.enable = true;
10
11  users.users.alice = {
12    isNormalUser = true;
13    extraGroups = [ "wheel" ];
14    initialPassword = "test";
15  };
16
17  system.stateVersion = "24.05";
18 }

```

To get graphical output, run the virtual machine without special options:

```

$ nix-build '<nixpkgs/nixos>' -A vm -I nixpkgs=channel:nixos-24.05 -I
↪nixos-config=./configuration.nix
$ ./result/bin/run-nixos-vm

```

Running Sway as Wayland compositor on a VM

To change to a Wayland compositor, disable `services.xserver.desktopManager.gnome` and enable `programs.sway`:

Listing 77: configuration.nix

```

- services.xserver.desktopManager.gnome.enable = true;
+ programs.sway.enable = true;

```

Note

Running Wayland compositors in a virtual machine might lead to complications with the display drivers used by QEMU. You need to choose from the available drivers one that is compatible with Sway. See [QEMU User Documentation](#)¹⁷⁰ for options. One possibility is the `virtio-vga` driver:

```
$ ./result/bin/run-nixos-vm -device virtio-vga
```

Arguments to QEMU can also be added to the configuration file:

```

1  { config, pkgs, ... }:
2  {
3    boot.loader.systemd-boot.enable = true;
4    boot.loader.efi.canTouchEfiVariables = true;
5
6    services.xserver.enable = true;
7
8    services.xserver.displayManager.gdm.enable = true;
9    programs.sway.enable = true;
10
11    imports = [ <nixpkgs/nixos/modules/virtualisation/qemu-vm.nix> ];
12    virtualisation.qemu.options = [
13      "-device virtio-vga"
14    ];
15
16    users.users.alice = {
17      isNormalUser = true;
18      extraGroups = [ "wheel" ];
19      initialPassword = "test";
20    };
21
22    system.stateVersion = "24.05";
23  }

```

The NixOS manual has chapters on [X11](#)¹⁷¹ and [Wayland](#)¹⁷² listing alternative window managers.

References

- [NixOS Manual: NixOS Configuration](#)¹⁷³.
- [NixOS Manual: Modules](#)¹⁷⁴.
- [NixOS Manual Options reference](#)¹⁷⁵.
- [NixOS Manual: Changing the configuration](#)¹⁷⁶.
- [NixOS source code: configuration template in tools.nix](#)¹⁷⁷.
- [NixOS source code: vm attribute in default.nix](#)¹⁷⁸.
- [Nix manual: nix-build](#)¹⁷⁹.
- [Nix manual: common command-line options](#)¹⁸⁰.
- [QEMU User Documentation](#)¹⁸¹ for more runtime options
- [NixOS option search: virtualisation.qemu](#)¹⁸² for declarative virtual machine configuration

Next steps

- [Module system deep dive](#) (page 75)
- [Integration testing with NixOS virtual machines](#) (page 105)
- [Building a bootable ISO image](#) (page 102)

Building a bootable ISO image

Note

If you need to build images for a different platform, see [Cross compiling](#)¹⁸³.

You may find that an official installation image lacks some hardware support.

The solution is to create `myimage.nix` to point to the latest kernel using the minimal installation ISO:

```
1 { pkgs, modulesPath, lib, ... }: {
2   imports = [
3     "${modulesPath}/installer/cd-dvd/installation-cd-minimal.nix"
4   ];
5 }
```

(continues on next page)

¹⁷⁰ <https://www.qemu.org/docs/master/system/qemu-manpage.html>

¹⁷¹ <https://nixos.org/manual/nixos/stable/#sec-x11>

¹⁷² <https://nixos.org/manual/nixos/stable/#sec-wayland>

¹⁷³ <https://nixos.org/manual/nixos/stable/index.html#ch-configuration>

¹⁷⁴ <https://nixos.org/manual/nixos/stable/index.html#sec-writing-modules>

¹⁷⁵ <https://nixos.org/manual/nixos/stable/options.html>

¹⁷⁶ <https://nixos.org/manual/nixos/stable/#sec-changing-config>

¹⁷⁷ <https://github.com/NixOS/nixpkgs/blob/4e0525a8cdb370d31c1e1ba2641ad2a91fded57d/nixos/modules/installer/tools/tools.nix#L122-L226>

¹⁷⁸ <https://github.com/NixOS/nixpkgs/blob/master/nixos/default.nix>

¹⁷⁹ <https://nix.dev/manual/nix/stable/command-ref/nix-build.html>

¹⁸⁰ <https://nix.dev/manual/nix/stable/command-ref/opt-common.html>

¹⁸¹ <https://www.qemu.org/docs/master/system/qemu-manpage.html>

¹⁸² <https://search.nixos.org/options?query=virtualisation.qemu>

¹⁸³ <https://github.com/nix-community/nixos-generators#user-content-cross-compiling>

(continued from previous page)

```

6  # use the latest Linux kernel
7  boot.kernelPackages = pkgs.linuxPackages_latest;
8
9  # Needed for https://github.com/NixOS/nixpkgs/issues/58959
10 boot.supportedFilesystems = lib.mkForce [ "btrfs" "reiserfs" "vfat" "f2fs" "xfs"
    ↪ "ntfs" "cifs" ];
11 }

```

Generate an ISO with the above configuration:

```

$ _
↪ NIX_PATH=nixpkgs=https://github.com/NixOS/nixpkgs/archive/74e2faf5965a12e8fa5cff799b1b19c6cd26b
↪ nix-shell -p nixos-generators --run "nixos-generate --format iso --configuration
↪ ./myimage.nix -o result"

```

Copy the new image to your USB stick by replacing `sdX` with the name of your device:

```

$ dd if=result/iso/*.iso of=/dev/sdX status=progress
$ sync

```

Next steps

- Take a look at this [list of formats that the generators support](#)¹⁸⁴ to find your cloud provider or virtualization technology.
- Take a look at the [alternative guide to create a NixOS live CD](#)¹⁸⁵

Building and running Docker images

Docker¹⁸⁶ is a set of tools and services used to build, manage and deploy containers.

Many cloud platforms offer Docker-based container hosting. Creating Docker containers is a common task when building reproducible software. In this tutorial, you learn how to build Docker containers using Nix.

Prerequisites

You will need both Nix and Docker¹⁸⁷ installed. Docker is available in `nixpkgs`, which is the preferred way to install it on NixOS. However, you can also use the native Docker installation of your OS, if you are on another Linux distribution or macOS.

Build your first container

Nixpkgs¹⁸⁸ provides `dockerTools` to create Docker images:

```

1 { pkgs ? import <nixpkgs> { }
2 , pkgsLinux ? import <nixpkgs> { system = "x86_64-linux"; }
3 }:
4
5 pkgs.dockerTools.buildImage {
6   name = "hello-docker";
7   config = {
8     Cmd = [ "${pkgsLinux.hello}/bin/hello" ];

```

(continues on next page)

¹⁸⁴ <https://github.com/nix-community/nixos-generators#user-content-supported-formats>

¹⁸⁵ https://wiki.nixos.org/wiki/Creating_a_NixOS_live_CD

¹⁸⁶ <https://www.docker.com/>

¹⁸⁷ <https://docs.docker.com/get-docker/>

¹⁸⁸ <https://github.com/NixOS/nixpkgs>

(continued from previous page)

```

9     };
10  }
```

Note

If you're running **macOS** or any platform other than `x86_64-linux`, you'll need to either:

- *Set up a remote build machine* (page 127) to build on Linux
- *Cross compile to Linux* (page 67) by replacing `pkgsLinux.hello` with `pkgs.pkgsCross.musl64.hello`

We call the `dockerTools.buildImage` and pass in some parameters:

- a name for our image
- the `config` including the command `Cmd` that should be run inside the container once the image is started. Here we reference the GNU `hello` package from `nixpkgs` and run its executable in the container.

Save this in `hello-docker.nix` and build it:

```

$ nix-build hello-docker.nix
these derivations will be built:
  /nix/store/qpgdp0qpd8ddi1ld72w02zkmm7n87b92-docker-layer-hello-docker.drv
  /nix/store/m4xyfyviwbi38sfplq3xx54j6k7mccfb-runtime-deps.drv
  /nix/store/v0bvy9qxa79izc7s03fhqp5nqs2h4sr5-docker-image-hello-docker.tar.gz.drv
warning: unknown setting 'experimental-features'
building '/nix/store/qpgdp0qpd8ddi1ld72w02zkmm7n87b92-docker-layer-hello-docker.drv'
↳ ...
No contents to add to layer.
Packing layer...
Computing layer checksum...
Finished building layer 'hello-docker'
building '/nix/store/m4xyfyviwbi38sfplq3xx54j6k7mccfb-runtime-deps.drv'...
building '/'
↳ nix/store/v0bvy9qxa79izc7s03fhqp5nqs2h4sr5-docker-image-hello-docker.tar.gz.drv'.
↳ ..
Adding layer...
tar: Removing leading `/' from member names
Adding meta...
Cooking the image...
Finished.
/nix/store/y74sb4nrhxr975xs7h83izgm8z75x5fc-docker-image-hello-docker.tar.gz
```

The image tag (`y74sb4nrhxr975xs7h83izgm8z75x5fc`) refers to the Nix build hash and makes sure that the Docker image corresponds to our Nix build. The store path in the last line of the output references the Docker image.

Run the container

To work with the container, load this image into Docker's image registry from the default `result` symlink created by `nix-build`:

```

$ docker load < result
Loaded image: hello-docker:y74sb4nrhxr975xs7h83izgm8z75x5fc
```

You can also use the store path to load the image to avoid depending on the presence of `result`:

```
$ docker load < /
↪nix/store/y74sb4nrhxr975xs7h83izgm8z75x5fc-docker-image-hello-docker.tar.gz
Loaded image: hello-docker:y74sb4nrhxr975xs7h83izgm8z75x5fc
```

Even more conveniently, you can do everything in one command. The advantage of this approach is that `nix-build` will rebuild the image if there are any changes and pass the new store path to `docker load`:

```
$ docker load < $(nix-build hello-docker.nix)
Loaded image: hello-docker:y74sb4nrhxr975xs7h83izgm8z75x5fc
```

Now that you have loaded the image into Docker, you can run it:

```
$ docker run -t hello-docker:y74sb4nrhxr975xs7h83izgm8z75x5fc
Hello, world!
```

Working with Docker images

A general introduction to working with Docker images is not part of this tutorial. The [official Docker documentation](#)¹⁸⁹ is a much better place for that.

Note that when you build your Docker images with Nix, you will probably not write a `Dockerfile` as Nix replaces the Dockerfile functionality within the Docker ecosystem. Nonetheless, understanding the anatomy of a Dockerfile may still be useful to understand how Nix replaces each of its functions. Using the Docker CLI, Docker Compose, Docker Swarm or Docker Hub on the other hand may still be relevant, depending on your use case.

Next steps

- More details on how to use `dockerTools` can be found in the [reference documentation](#)¹⁹⁰.
- You might like to browse through more [examples of Docker images built with Nix](#)¹⁹¹.
- Take a look at [Arion](#)¹⁹², a `docker-compose` wrapper with first-class support for Nix.
- Build docker images on a *CI with GitHub Actions* (page 143).

Integration testing with NixOS virtual machines

What will you learn?

This tutorial introduces `Nixpkgs` functionality for testing NixOS configurations. It also shows how to set up distributed test scenarios that involve multiple machines.

What do you need?

- A working *Nix installation* (page 1) on Linux, or [NixOS](#)¹⁹³
- Basic knowledge of the *Nix language* (page 12)
- Basic knowledge of *NixOS configuration* (page 97)

Introduction

`Nixpkgs` provides a [test environment](#)¹⁹⁴ to automate integration testing for distributed systems. It allows defining tests based on a set of declarative NixOS configurations and using a Python shell to interact with them through [QEMU](#)¹⁹⁵

¹⁸⁹ <https://docs.docker.com/>

¹⁹⁰ <https://nixos.org/nixpkgs/manual/#sec-pkgs-dockerTools>

¹⁹¹ <https://github.com/NixOS/nixpkgs/blob/master/pkgs/build-support/docker/examples.nix>

¹⁹² <https://docs.hercules-ci.com/arion/>

¹⁹³ <https://nixos.org/manual/nixos/stable/index.html#sec-installation>

¹⁹⁴ <https://nixos.org/manual/nixos/stable/index.html#sec-nixos-tests>

¹⁹⁵ <https://www.qemu.org/>

as the backend. Those tests are widely used to ensure that NixOS works as intended, so in general they are called [NixOS Tests](#)¹⁹⁶. They can be written and launched outside of NixOS, on any Linux machine²⁰⁶.

Nix's design properties make integration tests reproducible, which makes them valuable in a continuous integration (CI) pipeline.

The `testers.runNixOSTest` function

NixOS VM tests are defined using the `testers.runNixOSTest` function. The pattern for NixOS VM tests looks like this:

```

1 let
2   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
3   pkgs = import nixpkgs { config = {}; overlays = []; };
4 in
5
6 pkgs.testers.runNixOSTest {
7   name = "test-name";
8   nodes = {
9     machine1 = { config, pkgs, ... }: {
10      # ...
11    };
12     machine2 = { config, pkgs, ... }: {
13      # ...
14    };
15  };
16   testScript = { nodes, ... }: ''
17     # ...
18   '';
19 }
```

The function `testers.runNixOSTest` takes a [module](#)¹⁹⁷ to specify the [test options](#)¹⁹⁸. Because this module only sets configuration values, one can use the abbreviated module notation.

The following configuration values must be set:

- [name](#)¹⁹⁹ defines the name of the test.
- [nodes](#)²⁰⁰ contains a set of named configurations, because a test script can involve more than one virtual machine. Each virtual machine is created from a NixOS configuration.
- [testScript](#)²⁰¹ defines the Python test script, either as literal string or as a function that takes a `nodes` attribute. This Python test script can access the virtual machines via the names used for the `nodes`. It has super user rights in the virtual machines. In the Python script each virtual machine is accessible via the `machine` object. NixOS provides [methods](#)²⁰² to run tests on these configurations.

The test framework automatically starts the virtual machines and runs the Python script.

¹⁹⁶ <https://nixos.org/manual/nixos/stable/index.html#sec-nixos-tests>

²⁰⁶ Support for [running NixOS VM tests on macOS](#)²⁰⁷ is also implemented but [currently undocumented](#)²⁰⁸.

²⁰⁷ <https://github.com/NixOS/nixpkgs/issues/108984>

²⁰⁸ <https://github.com/NixOS/nixpkgs/issues/254552>

¹⁹⁷ <https://nixos.org/manual/nixos/stable/#sec-writing-modules>

¹⁹⁸ <https://nixos.org/manual/nixos/stable/index.html#sec-test-options-reference>

¹⁹⁹ <https://nixos.org/manual/nixos/stable/index.html#test-opt-name>

²⁰⁰ <https://nixos.org/manual/nixos/stable/index.html#test-opt-nodes>

²⁰¹ <https://nixos.org/manual/nixos/stable/index.html#test-opt-testScript>

²⁰² <https://nixos.org/manual/nixos/stable/index.html#ssec-machine-objects>

Minimal example

As a minimal test on the default configuration, we will check if the user `root` and `alice` can run Firefox. We will build the example up from scratch.

1. Use a *pinned version of Nixpkgs* (page 156), and *explicitly set configuration options and overlays* (page 147) to avoid them being inadvertently overridden by global configuration:

```
1 let
2   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11
  ↳";
3   pkgs = import nixpkgs { config = {}; overlays = []; };
4 in
5
6 pkgs.testers.runNixOSTest {
7   # ...
8 }
```

2. Label the test with a descriptive name:

```
1 name = "minimal-test";
```

3. Because this example only uses one virtual machine, the node we specify is simply called `machine`. This name is arbitrary and can be chosen freely. As configuration you use the relevant parts of the default configuration, *which we used in a previous tutorial* (page 97):

```
1 nodes.machine = { config, pkgs, ... }: {
2   users.users.alice = {
3     isNormalUser = true;
4     extraGroups = [ "wheel" ];
5     packages = with pkgs; [
6       firefox
7       tree
8     ];
9   };
10
11   system.stateVersion = "23.11";
12 };
```

4. This is the test script:

```
1 machine.wait_for_unit("default.target")
2 machine.succeed("su -- alice -c 'which firefox'")
3 machine.fail("su -- root -c 'which firefox'")
```

This Python script refers to `machine` which is the name chosen for the virtual machine configuration used in the `nodes` attribute set.

The script waits until `systemd` reaches `default.target`. It uses the `su` command to switch between users and the `which` command to check if the user has access to `firefox`. It expects that the command `which firefox` to succeed for user `alice` and to fail for `root`.

This script will be the value of the `testScript` attribute.

The complete `minimal-test.nix` file content looks like the following:

```
1 let
2   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
3   pkgs = import nixpkgs { config = {}; overlays = []; };
4 in
5
```

(continues on next page)

(continued from previous page)

```

6  pkgs.testers.runNixOSTest {
7      name = "minimal-test";
8
9      nodes.machine = { config, pkgs, ... }: {
10
11          users.users.alice = {
12              isNormalUser = true;
13              extraGroups = [ "wheel" ];
14              packages = with pkgs; [
15                  firefox
16                  tree
17              ];
18          };
19
20          system.stateVersion = "23.11";
21      };
22
23      testScript = ''
24          machine.wait_for_unit("default.target")
25          machine.succeed("su -- alice -c 'which firefox'")
26          machine.fail("su -- root -c 'which firefox'")
27      '';
28  }

```

Running tests

To set up all machines and run the test script:

```
$ nix-build minimal-test.nix
```

```

...
test script finished in 10.96s
cleaning up
killing machine (pid 10)
(0.00 seconds)
/nix/store/bx7z3imvxxpwkka10vb23czhw7873w2-vm-test-run-minimal-test

```

Interactive Python shell in the virtual machine

When developing tests or when something breaks, it's useful to interactively tinker with the test or access a terminal for a machine.

To start an interactive Python session with the testing framework:

```
$ $(nix-build -A driverInteractive minimal-test.nix)/bin/nixos-test-driver
```

Here you can run any of the testing operations. Execute the `testScript` attribute from `minimal-test.nix` with the `test_script()` function.

If a virtual machine is not yet started, the test environment takes care of it on the first call of a method on a `machine` object.

But you can also manually trigger the start of the virtual machine with:

```
>>> machine.start()
```

for a specific node,

or

```
>>> start_all()
```

for all nodes.

You can enter an interactive shell on the virtual machine using:

```
>>> machine.shell_interact()
```

and run shell commands like:

```
uname -a
```

```
Linux server 5.10.37 #1-NixOS SMP Fri May 14 07:50:46 UTC 2021 x86_64 GNU/Linux
```

Re-running successful tests

Because test results are kept in the Nix store, a successful test is cached. This means that Nix will not run the test a second time as long as the test setup (node configuration and test script) stays semantically the same. Therefore, to run a test again, one needs to remove the result.

If you would try to delete the result using the symbolic link, you will get the following error:

```
nix-store --delete ./result
```

```
finding garbage collector roots...
0 store paths deleted, 0.00 MiB freed
error: Cannot delete path '/'
↳nix/store/4klj06bsilkqkn6h2sia8dcsi72wbcfl-vm-test-run-unnamed' since it is
↳still alive. To find out why, use: nix-store --query --roots
```

Instead, remove the symbolic link and only then remove the cached result:

```
rm ./result
nix-store --delete /nix/store/4klj06bsilkqkn6h2sia8dcsi72wbcfl-vm-test-run-unnamed
```

This can be also done with one command:

```
result=$(readlink -f ./result) rm ./result && nix-store --delete $result
```

Tests with multiple virtual machines

Tests can involve multiple virtual machines, for example to test client-server-communication.

The following example setup includes:

- A virtual machine named `server` running `nginx`²⁰³ with default configuration.
- A virtual machine named `client` that has `curl` available to make an HTTP request.
- A testScript orchestrating testing logic between `client` and `server`.

The complete `client-server-test.nix` file content looks like the following:

```
let
  nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
  pkgs = import nixpkgs { config = {}; overlays = []; };
in
```

(continues on next page)

²⁰³ <https://nginx.org/en/>

(continued from previous page)

```

pkgs.testers.runNixOSTest {
  name = "client-server-test";

  nodes.server = { pkgs, ... }: {
    networking = {
      firewall = {
        allowedTCPPorts = [ 80 ];
      };
    };
    services.nginx = {
      enable = true;
      virtualHosts."server" = {};
    };
  };

  nodes.client = { pkgs, ... }: {
    environment.systemPackages = with pkgs; [
      curl
    ];
  };

  testScript = ''
    server.wait_for_unit("default.target")
    client.wait_for_unit("default.target")
    client.succeed("curl http://server/ | grep -o \"Welcome to nginx!\"")
  '';
}

```

The test script performs the following steps:

- 1) Start the server and wait for it to be ready.
- 2) Start the client and wait for it to be ready.
- 3) Run `curl` on the client and use `grep` to check the expected return string. The test passes or fails based on the return value.

Run the test:

```
$ nix-build client-server-test.nix
```

Additional information regarding NixOS tests

- Running integration tests on CI requires hardware acceleration, which many CIs do not support. To run integration tests in *GitHub Actions* (page 143) see [how to disable hardware acceleration](#)²⁰⁴.
- NixOS comes with a large set of tests that can serve as educational examples. A good inspiration is *Matrix bridging with an IRC*²⁰⁵.

Next steps

- *Module system deep dive* (page 75)
- *Building a bootable ISO image* (page 102)
- *Building and running Docker images* (page 103)

²⁰⁴ <https://github.com/cachix/install-nix-action#how-do-i-run-nixos-tests>

²⁰⁵ <https://github.com/NixOS/nixpkgs/blob/master/nixos/tests/matrix/appservice-irc.nix>

Provisioning remote machines via SSH

It is possible to replace any Linux installation with a NixOS configuration on running systems using `nixos-anywhere`²⁰⁹ and `disko`²¹⁰.

Introduction

In this tutorial, you deploy a NixOS configuration to a running computer.

What will you learn?

You'll learn how to

- Specify a minimal NixOS configuration with a declarative disk layout and SSH access
- Check that a configuration is valid
- Deploy and update a NixOS configuration on a remote machine

What do you need?

- Familiarity with the *Nix language* (page 12)
- Familiarity with the *Module system* (page 72)

For a successful unattended installation, ensure for the *target machine* that:

- It is a QEMU virtual machine running Linux
 - With `kexec`²¹¹ support
 - On the `x86-64` or `aarch64` instruction set architecture (ISA)
 - With at least 1 GB of RAM

This may also be a live system booted from USB, such as the *NixOS installer*²¹².

- The IP address is configured automatically with DHCP
- You can login via SSH
 - With public key authentication (preferred), or password
 - As user `root` or another user with `sudo` permissions

The *local machine* only needs a working *Nix installation* (page 1).

We call the *target machine* `target-machine` in this tutorial. Replace it with the actual hostname or IP address.

Prepare the environment

Create a new project directory and enter it with your shell:

```
mkdir remote
cd remote
```

Specify dependencies (page 136) on `nixpkgs`, `disko`, and `nixos-anywhere`:

²⁰⁹ <https://nix-community.github.io/nixos-anywhere/>

²¹⁰ <https://github.com/nix-community/disko>

²¹¹ <https://en.wikipedia.org/wiki/Kexec>

²¹² <https://nixos.org/download/#download-nixos-accordion>

```
$ nix-shell -p npins
[nix-shell:remote]$ npins init
[nix-shell:remote]$ npins add github nix-community disko
[nix-shell:remote]$ npins add github nix-community nixos-anywhere
```

Create a new file `shell.nix` which provides all needed tooling using the pinned dependencies:

```
let
  sources = import ./npins;
  pkgs = import sources.nixpkgs {};
in

pkgs.mkShell {
  nativeBuildInputs = with pkgs; [
    npins
    nixos-anywhere
    nixos-rebuild
  ];
  shellHook = ''
    export NIX_PATH="nixpkgs=${sources.nixpkgs}:nixos-config=
↪$PWD/configuration.nix"
  '';
}
```

Now exit the temporary environment and enter the newly specified one:

```
[nix-shell:remote]$ exit
$ nix-shell
```

This shell environment is ready to use well-defined versions of Nixpkgs with `nixos-anywhere` and `nixos-rebuild`.

Important

Run all following commands in this environment.

Create a NixOS configuration

The new NixOS configuration will consist of the general system configuration and a disk layout specification.

The disk layout in this example describes a single disk with a [master boot record](https://en.wikipedia.org/wiki/Master_boot_record)²¹³ (MBR) and [EFI system partition](https://en.wikipedia.org/wiki/EFI_system_partition)²¹⁴ (ESP) partition, and a root file system that takes all remaining available space. It will work on both EFI and BIOS systems.

Create a new file `single-disk-layout.nix` with the disk layout specification:

```
1 { ... }:
2
3 {
4   disk.devices.disk.main = {
5     type = "disk";
6     content = {
7       type = "gpt";
8       partitions = {
9         MBR = {
```

(continues on next page)

²¹³ https://en.wikipedia.org/wiki/Master_boot_record

²¹⁴ https://en.wikipedia.org/wiki/EFI_system_partition

(continued from previous page)

```

10     priority = 0;
11     size = "1M";
12     type = "EF02";
13 };
14 ESP = {
15     priority = 1;
16     size = "500M";
17     type = "EF00";
18     content = {
19         type = "filesystem";
20         format = "vfat";
21         mountpoint = "/boot";
22     };
23 };
24 root = {
25     priority = 2;
26     size = "100%";
27     content = {
28         type = "filesystem";
29         format = "ext4";
30         mountpoint = "/";
31     };
32 };
33 };
34 };
35 };
36 }

```

Create the file `configuration.nix`, which imports the disk layout definition and specifies which disk to format:

Tip

If you don't know the target disk's device identifier, list all devices on the *target machine* with `lsblk`:

```

$ ssh target-machine lsblk
NAME        MAJ:MIN RM   SIZE RO TYPE MOUNTPOINTS
sda          8:0    0   256G  0 disk
├─sda1       8:1    0  248.5G  0 part /nix/store
│
└─sda2       8:2    0    7.5G  0 part [SWAP]
sr0         11:0    1   1024M  0 rom

```

In this example, the disk name is `sda`. The block device path is then `/dev/sda`. Note that value for later.

```

1 { modulesPath, ... }:
2
3 let
4     diskDevice = "/dev/sda";
5     sources = import ./npins;
6 in
7 {
8     imports = [
9         (modulesPath + "/profiles/qemu-guest.nix")
10        (sources.disko + "/module.nix")
11        ./single-disk-layout.nix
12    ];

```

(continues on next page)

(continued from previous page)

```

13
14     disko.devices.disk.main.device = diskDevice;
15
16     boot.loader.grub = {
17         devices = [ diskDevice ];
18         efiSupport = true;
19         efiInstallAsRemovable = true;
20     };
21
22     services.openssh.enable = true;
23
24     users.users.root.openssh.authorizedKeys.keys = [
25         "<your SSH key here>"
26     ];
27
28     system.stateVersion = "24.11";
29 }

```

Important

Replace `/dev/sda` with your disk block device path.

Replace the `<your SSH key here>` string with the SSH public key that you want to use for future logins as user `root`.

Detailed explanation

The `diskDevice` variable in the `let` block defines the path of the disk block device:

```

3  let
4      diskDevice = "/dev/sda";
5      sources = import ./npins;
6  in

```

It is used to set the target for the partitioning and formatting as described in the disk layout specification. It is also used in the boot loader configuration to make it bootable on both legacy BIOS as well as UEFI systems:

```

14     disko.devices.disk.main.device = diskDevice;
15
16     boot.loader.grub = {
17         devices = [ diskDevice ];
18         efiSupport = true;
19         efiInstallAsRemovable = true;
20     };

```

The `qemu-guest.nix` module makes this system compatible for running inside a QEMU virtual machine:

```

8  imports = [
9      (modulesPath + "/profiles/qemu-guest.nix")
10     (sources.disko + "/module.nix")
11     ./single-disk-layout.nix
12 ];

```

From a disk layout specification, the `disko` library generates a partitioning script and the portion of the NixOS configuration that mounts the partitions accordingly at boot time. The first line imports the library, the second line applies the disk layout:

```

8 imports = [
9   (modulesPath + "/profiles/qemu-guest.nix")
10  (sources.disko + "/module.nix")
11  ./single-disk-layout.nix
12 ];

```

Test the disk layout

Check that the disk layout is valid:

```
nix-build -E "((import <nixpkgs> {}).nixos [ ./configuration.nix ]).installTest"
```

This command runs the complete installation in a virtual machine by building a derivation in the `installTest` attribute provided by the `disko` module.

Deploy the system

To deploy the system, build the configuration and the corresponding disk formatting script, and run `nixos-anywhere` using the results:

Important

Replace `target-host` with the hostname or IP address of your *target machine*.

```

toplevel=$(nixos-rebuild build --no-flake)
diskoScript=$(nix-build -E "((import <nixpkgs> {}).nixos [ ./configuration.nix ↵
↵]).diskoScript")
nixos-anywhere --store-paths "$diskoScript" "$toplevel" root@target-host

```

Note

If you don't have public key authentication: Set the environment variable `SSH_PASS` to your password then append the `--env-password` flag to the `nixos-anywhere` command.

`nixos-anywhere` will now log into the target system, partition, format, and mount the disk, and install the NixOS configuration. Then, it reboots the system.

Update the system

To update the system, run `npins` and re-deploy the configuration:

```

npins update nixpkgs
nixos-rebuild switch --no-flake --target-host root@target-host

```

`nixos-anywhere` is not needed any more, unless you want to change the disk layout.

Next steps

- [Setting up an HTTP binary cache](#) (page 123)
- [Setting up post-build hooks](#) (page 141)

References

- [nixos-anywhere project page](#)²¹⁵
- [disko project repository](#)²¹⁶
- [Collection of disk layout examples](#)²¹⁷

Installing NixOS on a Raspberry Pi

This tutorial assumes you have a Raspberry Pi 4 Model B with 4GB RAM²¹⁸.

Before starting this tutorial, make sure you have all the necessary hardware²¹⁹:

- HDMI cable/adaptor.
- 8GB+ SD card.
- SD card reader (in case your machine doesn't have an SD slot).
- Power cable for your Raspberry Pi.
- USB keyboard.

Note

This tutorial was written for the Raspberry Pi 4B. Using a previously supported model like the 3B or 3B+ is possible with some modifications to this tutorial.

Bootting NixOS live image

Note

Bootting from USB may require an EEPROM firmware upgrade. This tutorial boots from an SD card to avoid such hiccups.

To prepare the AArch64 image on another device with Nix, run the following commands:

```
$ nix-shell -p wget zstd

[nix-shell:~]$ wget \
↪https://hydra.nixos.org/build/226381178/download/1/nixos-sd-image-23.11pre500597.0f9be93c5a7c-aarch64-linux.img.zst
[nix-shell:~]$ zstd -d \
↪nixos-sd-image-23.11pre500597.0f9be93c5a7c-aarch64-linux.img.zst
[nix-shell:~]$ dmesg --follow
```

Note

You can download a recent image from [Hydra](#)²²⁰, clicking on the latest successful build (marked with a green checkmark), and copying the link to the build product image.

²¹⁵ <https://nix-community.github.io/nixos-anywhere/>

²¹⁶ <https://github.com/nix-community/disko>

²¹⁷ <https://github.com/nix-community/disko/tree/master/example>

²¹⁸ <https://www.raspberrypi.org/products/raspberry-pi-4-model-b/>

²¹⁹ <https://projects.raspberrypi.org/en/projects/raspberry-pi-setting-up/1>

²²⁰ https://hydra.nixos.org/job/nixos/trunk-combined/nixos.sd_image.aarch64-linux

Note

It may be more convenient to use a software like [Etcher](#)²²¹ to flash the image to your SD card if you are on a system where it's available.

Your terminal should be printing kernel messages as they come in.

Plug in your SD card and your terminal should print what device it got assigned, for example `/dev/sdX`.

Press `Ctrl+C` to stop `dmesg --follow`.

Copy NixOS to your SD card by replacing `sdX` with the name of your device in the following command:

```
[nix-shell:~]$ sudo dd_
↪if=nixos-sd-image-23.11pre500597.0fbc93c5a7c-aarch64-linux.img of=/dev/sdX_
↪bs=4096 conv=fsync status=progress
```

Once that command exits, **move the SD card into your Raspberry Pi and power it on.**

You should be greeted with a fresh shell.

In case the image doesn't boot, it's worth [updating the firmware](#)²²² and booting the image again.

Getting internet connection

Run `sudo -i` to get a root shell for the rest of the tutorial.

At this point you'll need an internet connection. If you can use an ethernet cable, plug it in and skip to the next section.

If you're connecting to wifi, run `ip link` to find the name of your wireless network interface. Look for an interface starting with `wl` (commonly `wlan0`).

Replace `SSID` and `passphrase` with your wifi credentials and run:

```
# wpa_supplicant -B -i wlan0 -c <(wpa_passphrase 'SSID' 'passphrase') &
```

Wait for `wpa_supplicant` to establish the connection. Then assign a static IP address to enable internet access. Replace `192.168.1.X` with an available IP address on your network and `192.168.1.1` with your router's gateway address:

```
# ip addr add 192.168.1.X/24 dev wlan0
# ip route add default via 192.168.1.1
```

Now you can download and run `dhcpcd` to obtain a proper IP address:

```
# nix-shell -p dhcpcd
# dhcpcd wlan0
```

After a few seconds, verify the connection by running:

```
# host nixos.org
```

If DNS resolution succeeds, you have internet connectivity and can proceed to the next section.

In case you've made a typo, run `kill wpa_supplicant` and start over.

²²¹ <https://www.balena.io/etcher/>

²²² https://www.raspberrypi.com/documentation/computers/raspberry-pi.html#bootloader_update_stable

Updating firmware

To benefit from updates and bug fixes from the vendor, we'll start by updating Raspberry Pi firmware:

```
# nix-shell -p raspberrypi-eeeprom
# mount /dev/disk/by-label/FIRMWARE /mnt
# BOOTFS=/mnt FIRMWARE_RELEASE_STATUS=stable rpi-eeeprom-update -d -a
```

Installing and configuring NixOS

Now we'll install NixOS with our own configuration, here creating a guest user and enabling the SSH daemon.

In the `let` binding below, change the value of the `SSID` and `SSIDpassword` variables to the `SSID` and `passphrase` values you used previously:

```
1 { config, pkgs, lib, ... }:
2
3 let
4   user = "guest";
5   password = "guest";
6   SSID = "mywifi";
7   SSIDpassword = "mypassword";
8   interface = "wlan0";
9   hostname = "myhostname";
10 in {
11
12   boot = {
13     kernelPackages = pkgs.linuxKernel.packages.linux_rpi4;
14     initrd.availableKernelModules = [ "xhci_pci" "usbhid" "usb_storage" ];
15     loader = {
16       grub.enable = false;
17       generic-extlinux-compatible.enable = true;
18     };
19   };
20
21   fileSystems = {
22     "/" = {
23       device = "/dev/disk/by-label/NIXOS_SD";
24       fsType = "ext4";
25       options = [ "noatime" ];
26     };
27   };
28
29   networking = {
30     hostName = hostname;
31     wireless = {
32       enable = true;
33       networks."${SSID}".psk = SSIDpassword;
34       interfaces = [ interface ];
35     };
36   };
37
38   environment.systemPackages = with pkgs; [ vim ];
39
40   services.openssh.enable = true;
41
42   users = {
43     mutableUsers = false;
```

(continues on next page)

(continued from previous page)

```

44     users."${user}" = {
45         isNormalUser = true;
46         password = password;
47         extraGroups = [ "wheel" ];
48     };
49 };
50
51 hardware.enableRedistributableFirmware = true;
52 system.stateVersion = "23.11";
53 }

```

To save time on typing the whole configuration, download it:

```

# curl -L https://tinyurl.com/tutorial-nixos-install-rpi4 > /
  ↪etc/nixos/configuration.nix

```

Note

Credentials you write into a NixOS configuration will be stored in plain text in your `/nix/store` when that configuration is built.

If you **don't** want this to happen, you can enter your credentials at a console or use one of the community's solutions for encrypted secrets.

Due to the way the `nixos-sd-image` is designed, NixOS is actually *already installed* at this point, so we only need to `nixos-rebuild` with our new configuration:

```

# nixos-rebuild boot
# reboot

```

If your system doesn't boot, select the oldest configuration in the bootloader menu to get back to the live image and start over.

Making changes

It booted, congratulations.

To make further changes to the configuration, search through NixOS options²²³, edit `/etc/nixos/configuration.nix`, and update your system:

```

$ sudo -i
# nixos-rebuild switch

```

Next steps

- Once you have a working OS, try upgrading it with `nixos-rebuild switch --upgrade` to install more recent package versions, and reboot to the old configuration if something broke.
- To enable hardware acceleration for a nice graphical desktop experience, add the `nixos-hardware`²²⁴ module to your configuration:

```

1 imports = [
2     "${fetchTarball "https://github.com/NixOS/nixos-hardware/tarball/master"}"
  ↪raspberrypi/4"
3 ];

```

²²³ <https://search.nixos.org/options>

²²⁴ <https://github.com/nixos/nixos-hardware>

We recommend pinning the reference to `nixos-hardware`: *Pinning Nixpkgs* (page 156)

- To tweak bootloader options affecting hardware, see `config.txt` options²²⁵. You can change these options by running `mount /dev/disk/by-label/FIRMWARE /mnt` and opening `/mnt/config.txt`.

Deploying NixOS using Terraform

This tutorial assumes you're familiar with the basics of Terraform²²⁶. By the end, you will have provisioned an Amazon Web Services (AWS) instance with Terraform and used Nix to deploy incremental changes to NixOS running on the instance.

We'll look at how to boot a NixOS machine and how to deploy the incremental changes.

Booting NixOS image

1. Start by providing the Terraform executable:

```
$ nix-shell -p terraform
```

2. We are using Terraform Cloud²²⁷ as a state/locking backend²²⁸:

```
$ terraform login
```

3. Make sure to create an organization²²⁹, like `myorganization`, in your Terraform Cloud account.
4. Inside `myorganization`, create a workspace²³⁰ by choosing **CLI-driven workflow** and pick a name, like `myapp`.
5. Inside your workspace, under Settings / General, change Execution Mode to Local.
6. Inside a new directory, create a `main.tf` file with the following contents. This will start an AWS instance with the NixOS image using one SSH keypair and an SSH security group:

```
terraform {
  backend "remote" {
    organization = "myorganization"

    workspaces {
      name = "myapp"
    }
  }
}

provider "aws" {
  region = "eu-central-1"
}

module "nixos_image" {
  source =
  ↪ "git::https://github.com/tweag/terraform-nixos.git/aws_image_nixos?ref=5f5a0408b299874d6a29d12
  release = "20.09"
}

resource "aws_security_group" "ssh_and_egress" {
  ingress {
```

(continues on next page)

²²⁵ <https://www.raspberrypi.org/documentation/configuration/config-txt/>

²²⁶ <https://www.terraform.io/intro/index.html>

²²⁷ <https://app.terraform.io>

²²⁸ <https://www.terraform.io/docs/state/purpose.html>

²²⁹ <https://app.terraform.io/app/organizations/new>

²³⁰ <https://app.terraform.io/app/cachix/workspaces/new>

(continued from previous page)

```

        from_port    = 22
        to_port      = 22
        protocol      = "tcp"
        cidr_blocks   = [ "0.0.0.0/0" ]
    }

    egress {
        from_port      = 0
        to_port        = 0
        protocol        = "-1"
        cidr_blocks     = ["0.0.0.0/0"]
    }
}

resource "tls_private_key" "state_ssh_key" {
    algorithm = "RSA"
}

resource "local_file" "machine_ssh_key" {
    sensitive_content = tls_private_key.state_ssh_key.private_key_pem
    filename          = "${path.module}/id_rsa.pem"
    file_permission   = "0600"
}

resource "aws_key_pair" "generated_key" {
    key_name =
    ↪ "generated-key-${sha256(tls_private_key.state_ssh_key.public_key_openssh)}"
    public_key = tls_private_key.state_ssh_key.public_key_openssh
}

resource "aws_instance" "machine" {
    ami            = module.nixos_image.ami
    instance_type  = "t3.micro"
    security_groups = [ aws_security_group.ssh_and_egress.name ]
    key_name       = aws_key_pair.generated_key.key_name

    root_block_device {
        volume_size = 50 # GiB
    }
}

output "public_dns" {
    value = aws_instance.machine.public_dns
}

```

The only NixOS specific snippet is:

```

module "nixos_image" {
    source =
    ↪ "git::https://github.com/tweag/terraform-nixos.git/aws_image_nixos?ref=5f5a0408b299874d6a29d127
    release = "20.09"
}

```

Note

The `aws_image_nixos` module will return a NixOS AMI given a NixOS release number²³¹ so that the

`aws_instance` resource can reference the AMI in the `instance_type`²³² argument.

5. Make sure to [configure AWS credentials](#)²³³.
6. Applying the Terraform configuration should get you a running NixOS:

```
$ terraform init
$ terraform apply
```

Deploying NixOS changes

Once the AWS instance is running a NixOS image via Terraform, we can teach Terraform to always build the latest NixOS configuration and apply those changes to your instance.

1. Create `configuration.nix` with the following contents:

```
1 { config, lib, pkgs, ... }: {
2   imports = [ <nixpkgs/nixos/modules/virtualisation/amazon-image.nix> ];
3
4   # Open https://search.nixos.org/options for all options
5 }
```

2. Append the following snippet to your `main.tf`:

```
module "deploy_nixos" {
  source =
  ↪ "git::https://github.com/tweag/terraform-nixos.git//deploy_nixos?ref=5f5a0408b299874d6a29d1271e"
  nixos_config = "${path.module}/configuration.nix"
  target_host = aws_instance.machine.public_ip
  ssh_private_key_file = local_file.machine_ssh_key.filename
  ssh_agent = false
}
```

3. Deploy:

```
$ terraform init
$ terraform apply
```

Caveats

- The `deploy_nixos` module requires NixOS to be installed on the target machine and Nix on the host machine.
- The `deploy_nixos` module doesn't work when the client and target architectures are different (unless you use [distributed builds](#)²³⁴).
- If you need to inject a value into Nix, there is no elegant solution.
- Each machine is evaluated separately, so note that your memory requirements will grow linearly with the number of machines.

Next steps

- It's possible to [switch to Google Compute Engine](#)²³⁵.
- The `deploy_nixos` module²³⁶ supports a number of arguments, for example to upload keys.

²³¹ <https://status.nixos.org>

²³² https://registry.terraform.io/providers/hashicorp/aws/latest/docs/resources/instance#instance_type

²³³ <https://registry.terraform.io/providers/hashicorp/aws/latest/docs#authentication>

²³⁴ <https://nix.dev/manual/nix/stable/advanced-topics/distributed-builds.html>

²³⁵ https://github.com/tweag/terraform-nixos/tree/master/google_image_nixos#readme

²³⁶ https://github.com/tweag/terraform-nixos/tree/master/deploy_nixos#readme

Setting up an HTTP binary cache

A binary cache stores pre-built [Nix store objects](#)²³⁷ and provides them to other machines over the network. Any machine with a Nix store can be a binary cache for other machines.

Introduction

In this tutorial you set up a Nix binary cache that serves store objects from a NixOS machine over HTTP or HTTPS.

What will you learn?

You'll learn how to:

- Set up signing keys for your cache
- Enable the right services on the NixOS machine serving the cache
- Check that the setup works as intended

What do you need?

- A working [Nix installation](#) (page 1) on your local machine
- SSH access to a NixOS machine to use as a cache

If you're new to NixOS, learn about the [module system](#) (page 72) and configure your first system with [NixOS virtual machines](#) (page 97).

- (optional) A public IP and DNS domain

If you don't host yourself, check [NixOS-friendly hosts](#)²³⁸ on the NixOS Wiki. Follow the tutorial on [Provisioning remote machines via SSH](#) (page 111) to deploy your NixOS configuration.

For a cache on a local network, we assume:

- The hostname is `cache` (replace it with yours, or an IP address)
- The host serves store objects via HTTP on port 80 (this is the default)

For a publicly accessible cache, we assume:

- The domain name is `cache.example.com` (replace it with yours)
- The host serves store objects via HTTPS on port 443 (this is the default)

How long will it take?

- 25 minutes

Set up services

For the NixOS machine hosting the cache, create a new configuration module in `binary-cache.nix`:

```
{ config, ... }:

{
  services.nix-serve = {
    enable = true;
    secretKeyFile = "/var/secrets/cache-private-key.pem";
  };

  services.nginx = {
```

(continues on next page)

²³⁷ <https://nix.dev/manual/nix/latest/store/store-object>

²³⁸ https://wiki.nixos.org/wiki/NixOS_friendly_hosts

(continued from previous page)

```

enable = true;
recommendedProxySettings = true;
virtualHosts.cache = {
    locations."/".proxyPass = "http://${config.services.nix-serve.bindAddress}:${
↪toString config.services.nix-serve.port}";
};
};

networking.firewall.allowedTCPPorts = [
    config.services.nginx.defaultHTTPListenPort
];
}

```

The options under `services.nix-serve`²³⁹ configure the binary cache service.

`nix-serve` doesn't support IPv6 or SSL/HTTPS. The `services.nginx`²⁴⁰ options are used to set up a proxy, which does support IPv6, to handle requests to the hostname `cache`.

Important

There is an *optional HTTPS section* (page 125) at the end of this tutorial.

Add the new NixOS module to the existing machine configuration:

```

{ config, ... }:

{
    imports = [
        ./binary-cache.nix
    ];

    # ...
}

```

From your local machine, deploy the new configuration:

```
nixos-rebuild switch --no-flake --target-host root@cache
```

Note

The binary cache daemon will report errors because there is no secret key file yet.

Generate a signing key pair

You need a pair of private and public keys to ensure that the store objects in the cache are authentic.

To generate a key pair for the binary cache, replace the example hostname `cache.example.com` with your hostname:

```

nix-store --generate-binary-cache-key cache.example.com cache-private-key.pem
↪cache-public-key.pem

```

`cache-private-key.pem` will be used by the binary cache daemon to sign the binaries as they are served. Copy it to the location configured in `services.nix-serve.secretKeyFile` on the machine hosting the cache:

²³⁹ <https://search.nixos.org/options?query=services.nix-serve>

²⁴⁰ <https://search.nixos.org/options?query=services.nginx>

```
scp cache-private-key.pem root@cache:/var/secrets/cache-private-key.pem
```

Up until now, the binary cache daemon was in a restart loop due to the missing secret key file. Check that it now works correctly:

```
ssh root@cache systemctl status nix-serve.service
```

Important

Configure Nix to use a custom binary cache (page 133) using `cache-public-key.pem` on your local machine.

Test availability

The following steps check if everything is set up correctly and may help with identifying problems.

Check general availability

Test if the binary cache, reverse proxy, and firewall rules work as intended by querying the cache:

```
$ curl http://cache/nix-cache-info
StoreDir: /nix/store
WantMassQuery: 1
Priority: 30
```

Check store object signing

To test if store objects are signed correctly, inspect the metadata of a sample derivation. On the binary cache host, build the `hello` package and get the `.narinfo` file from the cache:

```
$ hash=$(nix-build '<nixpkgs>' -A pkgs.hello | awk -F '/' '{print $4}' | awk -F '-'
↳ '{print $1}')
$ curl "http://cache/$hash.narinfo" | grep "Sig: "
...
Sig:↳
↳cache.example.org:GyBFzocLAeLEFd0hr2noK84VzPUw0ArCNYEnrm1YXakdsC5FkO2Bkj2JH8Xjou+wxexMjFKa0YP2A...
```

Make sure that the output contains this line prefixed with `Sig:` and shows the public key you generated.

Serving the binary cache via HTTPS

If the binary cache is publicly accessible, it is possible to enforce HTTPS with [Let's Encrypt](https://letsencrypt.org/)²⁴¹ SSL certificates. Edit your `binary-cache.nix` like this and make sure to replace the example URL and mail address with yours:

```
services.nginx = {
  enable = true;
  recommendedProxySettings = true;
-  virtualHosts.cache = {
+  virtualHosts."cache.example.com" = {
+    enableACME = true;
+    forceSSL = true;
    locations."/" = {
      proxyPass =
↳"http://${config.services.nix-serve.bindAddress}:${toString}
↳config.services.nix-serve.port}";
    };
  };
};
```

(continues on next page)

²⁴¹ <https://letsencrypt.org/>

(continued from previous page)

```

};

+ security.acme = {
+   acceptTerms = true;
+   certs = {
+     "cache.example.com".email = "you@example.com";
+   };
+ };

networking.firewall.allowedTCPPorts = [
  config.services.nginx.defaultHTTPListenPort
+ config.services.nginx.defaultSSLListenPort
];

```

Rebuild the system to deploy these changes:

```
nixos-rebuild switch --no-flake --target-host root@cache.example.com
```

Next steps

If your binary cache is already a [remote build machine](#)²⁴², it will serve all store objects in its Nix store.

- [Configure Nix to use a custom binary cache](#) (page 133) using the binary cache's hostname and the generated public key
- [Setting up post-build hooks](#) (page 141) to upload store objects to the binary cache
- [Setting up distributed builds](#) (page 127)

To save storage space, please refer to the following NixOS configuration attributes:

- `nix.gc`²⁴³: Options for automatic garbage collection
- `nix.optimise`²⁴⁴: Options for periodic Nix store optimisation

Alternatives

- `nix-serve-ng`²⁴⁵: A drop-in replacement for `nix-serve`, written in Haskell
- The [SSH Store](#)²⁴⁶, [Experimental SSH Store](#)²⁴⁷, and the [S3 Binary Cache Store](#)²⁴⁸ can also be used to serve a cache. There are many commercial providers for S3-compatible storage, for example:
 - Amazon S3
 - Tigris
 - Cloudflare R2
- [attic](#)²⁴⁹: Nix binary cache server backed by an S3-compatible storage provider
- [Cachix](#)²⁵⁰: Nix binary cache as a service

²⁴² <https://nix.dev/manual/nix/latest/advanced-topics/distributed-builds>

²⁴³ <https://search.nixos.org/options?query=nix.gc>

²⁴⁴ <https://search.nixos.org/options?query=nix.optimise>

²⁴⁵ <https://github.com/aristanetworks/nix-serve-ng>

²⁴⁶ <https://nix.dev/manual/nix/latest/store/types/ssh-store>

²⁴⁷ <https://nix.dev/manual/nix/latest/store/types/experimental-ssh-store>

²⁴⁸ <https://nix.dev/manual/nix/latest/store/types/s3-binary-cache-store>

²⁴⁹ <https://github.com/zhaofengli/attic>

²⁵⁰ <https://www.cachix.org>

References

- [Nix Manual on HTTP Binary Cache Store](#)²⁵¹
- [services.nix-serve module options](#)²⁵²
- [services.nginx module options](#)²⁵³

Setting up distributed builds

Nix can speed up builds by spreading the work across multiple computers at once.

Introduction

In this tutorial, you'll set up a separate build machine and configure your local machine to offload builds to it.

What will you learn?

You'll learn how to

- Create a new user for remote build access from a local machine to the remote builder
- Configure remote builders with a sustainable setup
- Test remote builder connectivity and authentication
- Configure the local machine to automatically distribute builds

What do you need?

- Familiarity with the *Nix language* (page 12)
- Familiarity with the *Module system* (page 72)
- A *local machine* (example hostname: `localmachine`)

The computer *with Nix installed* (page 1) that distributes builds to other machines.

- A *remote machine* (example hostname: `remotemachine`)

A computer running NixOS that accepts build jobs from the *local machine*. Follow *Provisioning remote machines via SSH* (page 111) to set up a remote NixOS system.

How long will it take?

- 25 minutes

Create an SSH key pair

The *local machine's* Nix daemon runs as the `root` user and will need the *private* key file to authenticate itself to remote machines. The *remote machine* will need the *public* key to recognize the *local machine*.

On the *local machine*, run the following command as `root` to create an SSH key pair:

```
# ssh-keygen -f /root/.ssh/remotebuild
```

Note

The name and location of the key pair files can be freely chosen.

²⁵¹ <https://nix.dev/manual/nix/latest/store/types/http-binary-cache-store>

²⁵² <https://search.nixos.org/options?query=services.nix-serve>

²⁵³ <https://search.nixos.org/options?query=services.nginx>

Set up the remote builder

In the NixOS configuration directory of the *remote machine*, create the file `remote-builder.nix`:

```
{
  users.users.remotebuild = {
    isSystemUser = true;
    group = "remotebuild";
    useDefaultShell = true;

    openssh.authorizedKeys.keyFiles = [ ./remotebuild.pub ];
  };

  users.groups.remotebuild = {};

  nix.settings.trusted-users = [ "remotebuild" ];
}
```

Copy the file `remotebuild.pub` into this directory.

This configuration module creates a new user `remotebuild` with no home directory. The `root` user on the *local machine* will be able to log into the remote builder via SSH using the previously generated SSH key.

Add the new NixOS module to the existing configuration of the *remote machine*:

```
{
  imports = [
    ./remote-builder.nix
  ];

  # ...
}
```

Activate the new configuration as root:

```
nixos-rebuild switch --no-flake --target-host root@remotemachine
```

Test authentication

Make sure that the SSH connection and authentication work. On the *local machine*, run as root:

```
# ssh remotebuild@remotemachine -i /root/.ssh/remotebuild "echo hello"
hello
```

If the `hello` message is visible, the authentication works.

This test login also adds the host key of the remote builder to the `/root/.ssh/known_hosts` file of the local machine. Future logins will not be interrupted by host key checks.

Set up distributed builds

Note

If your *local machine* runs NixOS, skip this section and *configure Nix through module options* (page 129).

Configure Nix to use the remote builder by adding to the [Nix configuration file](#)²⁵⁴ as root:

²⁵⁴ <https://nix.dev/manual/nix/2.23/command-ref/conf-file>

```
# cat << EOF >> /etc/nix/nix.conf
builders = ssh-ng://remotebuild@remotebuilder $(nix-instantiate --eval -E
↳builtins.currentSystem) /root/.ssh/remotemachine - - nixos-test, big-parallel, kvm
builders-use-substitutes = true
```

Detailed explanation

The first line registers the remote machine as a remote builder by specifying

- The protocol, user, and hostname
- The *local machine's system type*²⁵⁵

This will delegate jobs for that system type to the *remote machine*.

- The location of the SSH key
- A list of *supported system features*²⁵⁶

This particular list must be specified to delegate building compilers and running *NixOS VM tests* (page 105) to remote machines.

See the [reference documentation on the builders setting](#)²⁵⁷ for details.

The second line instructs all remote builders to obtain dependencies from its own binary caches instead of from the *local machine*. This assumes that the remote builders' internet connection is at least as fast as the local machine's internet connection.

To activate this configuration, restart the Nix daemon:

Linux

On Linux with `systemd`, run as `root`:

```
# systemctl restart nix-daemon.service
```

macOS

On macOS, run as `root`:

```
# sudo launchctl stop org.nixos.nix-daemon
# sudo launchctl start org.nixos.nix-daemon
```

NixOS

If your *local machine* runs NixOS, in its configuration directory create the file `distributed-builds.nix`:

```
{ pkgs, ... }:
{
  nix.distributedBuilds = true;
  nix.settings.builders-use-substitutes = true;

  nix.buildMachines = [
    {
      hostName = "remotebuilder";
      sshUser = "remotebuild";
      sshKey = "/root/.ssh/remotebuild";
      system = pkgs.stdenv.hostPlatform.system;
    }
  ]
```

²⁵⁵ <https://nix.dev/manual/nix/2.23/command-ref/conf-file#conf-system>

²⁵⁶ <https://nix.dev/manual/nix/2.23/command-ref/conf-file#conf-system-features>

²⁵⁷ <https://nix.dev/manual/nix/2.23/command-ref/conf-file#conf-builders>

```

    supportedFeatures = [ "nixos-test" "big-parallel" "kvm" ];
  }
];
}

```

Detailed explanation

This configuration module enables distributed builds and adds the remote builder, specifying:

- The SSH hostname and username
- The location of the SSH key
- Which *local machine's* system type²⁵⁸

This will delegate jobs for that system type to the *remote machine*.

- A list of supported system features²⁵⁹

This particular list must be specified to delegate building compilers and running *NixOS VM tests* (page 105) to remote machines.

See the [NixOS option documentation on `nix.buildMachines`](#)²⁶⁰ for details.

The `builders-use-substitutes` instructs all remote builders to obtain dependencies from its own binary caches instead of from the *local machine*. This assumes that the remote builders' internet connection is at least as fast as the local machine's internet connection.

Add the new NixOS module to the existing machine configuration:

```

{
  imports = [
    ./distributed-builds.nix
  ];

  # ...
}

```

Activate the new configuration as root:

```
# nixos-rebuild switch
```

Test distributed builds

Try building a new derivation on the *local machine*:

```

$ nix-build --max-jobs 0 -E "$(cat << EOF
(import <nixpkgs> {}).writeText "test" "$(date)"
EOF
)"
this derivation will be built:
  /nix/store/9csjdxv6ir8ccnjl6ijs36izswjgchn0-test.drv
building '/nix/store/9csjdxv6ir8ccnjl6ijs36izswjgchn0-test.drv' on
↳ 'ssh://remotebuilder'...
copying 0 paths...
copying 1 paths...
copying path '/nix/store/hvj5vyg4723nly1qh5a8daifbi1yisb3-test' from
↳ 'ssh://remotebuilder'...
/nix/store/hvj5vyg4723nly1qh5a8daifbi1yisb3-test

```

²⁵⁸ <https://nix.dev/manual/nix/2.23/command-ref/conf-file#conf-system>

²⁵⁹ <https://nix.dev/manual/nix/2.23/command-ref/conf-file#conf-system-features>

²⁶⁰ <https://search.nixos.org/options?query=nix.buildMachines>

The resulting derivation changes on every invocation because it depends on the current system time, and thus can never be in the local cache. The `--max-jobs 0` [command line argument](#)²⁶¹ forces Nix to build it on the remote builder.

The last output line contains the output path and indicates that build distribution works as expected.

Optimise the remote builder configuration

To maximise parallelism, enable automatic garbage collection, and prevent Nix builds from consuming all memory, add the following lines to your `remote-builder.nix` configuration module:

```
{
  users.users.remotebuild = {
    isNormalUser = true;
    createHome = false;
    group = "remotebuild";

    openssh.authorizedKeys.keyFiles = [ ./remotebuild.pub ];
  };

  users.groups.remotebuild = {};

- nix.settings.trusted-users = [ "remotebuild" ];
+ nix = {
+   nrBuildUsers = 64;
+   settings = {
+     trusted-users = [ "remotebuild" ];
+   };
+   min-free = 10 * 1024 * 1024;
+   max-free = 200 * 1024 * 1024;

+   max-jobs = "auto";
+   cores = 0;
+ };
+ };

+ systemd.services.nix-daemon.serviceConfig = {
+   MemoryAccounting = true;
+   MemoryMax = "90%";
+   OOMScoreAdjust = 500;
+ };
}
```

Tip

Refer to the [Nix reference manual](#)²⁶² for details on the options available in `nix.settings`²⁶³.

Remote builders can have different performance characteristics. For each `nix.buildMachines` item, set the `maxJobs`, `speedFactor`, and `supportedFeatures` attributes correctly for each different remote builder. This helps Nix on the *local machine* distributing builds the optimal way.

²⁶¹ <https://nix.dev/manual/nix/2.23/command-ref/conf-file#conf-max-jobs>

²⁶² <https://nix.dev/manual/nix/latest/command-ref/conf-file>

²⁶³ <https://search.nixos.org/options?show=nix.settings>

Tip

Refer to the NixOS option documentation on `nix.buildMachines`²⁶⁴ for details.

Set the `nix.buildMachines.*.publicHostKey` field to each remote builder's public host key to secure build distribution against man-in-the-middle scenarios.

Next steps

- *Configure Nix to use a custom binary cache* (page 133) on each remote builder
- *Setting up post-build hooks* (page 141) to upload store objects to a binary cache

To set up multiple builders, repeat the instructions in the *Set up the remote builder* (page 128) section for each remote builder. Add all new remote builders to the `nix.buildMachines` attribute shown in the *Set up distributed builds* (page 128) section.

Tip

Configure remote build machines to *host a binary cache* (page 123) and use them as *preferred binary caches* (page 133) to reduce your external traffic.

Alternatives

- `nixbuild.net`²⁶⁵ - Nix remote builders as a service
- `Hercules CI`²⁶⁶ - Continuous integration with automatic build distribution
- `garnix`²⁶⁷ - Hosted continuous integration with build distribution

References

- Nix reference manual: Settings for distributed builds²⁶⁸

²⁶⁴ <https://search.nixos.org/options?query=nix.buildMachines>

²⁶⁵ <https://nixbuild.net>

²⁶⁶ <https://hercules-ci.com/>

²⁶⁷ <https://garnix.io/>

²⁶⁸ <https://nix.dev/manual/nix/latest/command-ref/conf-file#conf-builders>

These sections contain guides to getting things done.

3.1 Recipes

3.1.1 Configure Nix to use a custom binary cache

Nix can be configured to use a binary cache with the `substituters`²⁶⁹ and `trusted-public-keys`²⁷⁰ settings, either exclusively or in addition to `cache.nixos.org`²⁷¹.

Tip

Follow the tutorial to *set up an HTTP binary cache* (page 123) and create a key pair for signing store objects.

For example, given a binary cache at `https://example.org` with public key `My56...Q==%`, and some derivation in `default.nix`, make Nix exclusively use that cache once by passing settings as command line flags²⁷²:

```
$ nix-build --substituters https://example.org --trusted-public-keys_
↪example.org:My56...Q==%
```

To permanently configure trying the custom cache before the public cache, add it as `extra-substituters` with lower priority value to the Nix configuration file²⁷³:

```
$ echo "extra-substituters = https://example.org?priority=30" >> /etc/nix/nix.conf
$ echo "extra-trusted-public-keys = example.org:My56...Q==%" >> /etc/nix/nix.conf
```

To always use only the custom cache:

```
$ echo "substituters = https://example.org" >> /etc/nix/nix.conf
$ echo "trusted-public-keys = example.org:My56...Q==%" >> /etc/nix/nix.conf
```

NixOS

On NixOS, Nix is configured through the `nix.settings`²⁷⁴ option:

```
1 { ... }: {
2   nix.settings = {
3     substituters = [ "https://example.org?priority=30" ];
4     trusted-public-keys = [ "example.org:My56...Q==%" ];
```

²⁶⁹ <https://nix.dev/manual/nix/latest/command-ref/conf-file.html#conf-substituters>

²⁷⁰ <https://nix.dev/manual/nix/latest/command-ref/conf-file.html#conf-trusted-public-keys>

²⁷¹ <http://cache.nixos.org>

²⁷² <https://nix.dev/manual/nix/latest/command-ref/conf-file#command-line-flags>

²⁷³ <https://nix.dev/manual/nix/latest/command-ref/conf-file#configuration-file>

```

5     };
6 }

```

Tip

Use *remote build machines* (page 127) as preferred binary caches to reduce your external traffic.

3.1.2 Automatic environment activation with direnv

Instead of manually activating the environment for each project, you can reload a *declarative shell* (page 8) every time you enter the project's directory or change the `shell.nix` inside it.

1. Make `nix-direnv` available²⁷⁵
2. Hook it into your shell²⁷⁶

For example, write a `shell.nix` with the following contents:

```

1 let
2   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
3   pkgs = import nixpkgs { config = {}; overlays = []; };
4 in
5
6 pkgs.mkShellNoCC {
7   packages = with pkgs; [
8     hello
9   ];
10 }

```

From the top-level directory of your project, run:

```
$ echo "use nix" > .envrc && direnv allow
```

The next time you launch your terminal and enter the top-level directory of your project, `direnv` will automatically launch the shell defined in `shell.nix`.

```

$ cd myproject
$ which hello
/nix/store/1gxz5nfzfnhyxjdyzi04r86sh61y4i00-hello-2.12.1/bin/hello

```

`direnv` will also check for changes to the `shell.nix` file.

Make the following addition:

```

let
  nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
  pkgs = import nixpkgs { config = {}; overlays = []; };
in

pkgs.mkShellNoCC {
  packages = with pkgs; [
    hello
  ];
+

```

(continues on next page)

²⁷⁴ <https://search.nixos.org/options?show=nix.settings>

²⁷⁵ <https://github.com/nix-community/nix-direnv>

²⁷⁶ <https://direnv.net/docs/hook.html>

(continued from previous page)

```
+ shellHook = ''
+   hello
+ '';
}
```

The running environment should reload itself after the first interaction (run any command or press Enter).

```
Hello, world!
```

3.1.3 Dependencies in the development shell

When *packaging software in default.nix* (page 40), you'll want a *development environment in shell.nix* (page 8) to enter conveniently with `nix-shell` or *automatically with direnv* (page 134).

How to share the package's dependencies in `default.nix` with the development environment in `shell.nix`?

Summary

Use the `inputsFrom` attribute to `pkgs.mkShellNoCC`²⁷⁷:

```
1 # default.nix
2 let
3   pkgs = import <nixpkgs> {};
4   myPackage = pkgs.callPackage ./package.nix {};
5 in
6 {
7   inherit myPackage;
8   shell = pkgs.mkShellNoCC {
9     inputsFrom = [ myPackage ];
10  };
11 }
```

Import the `shell` attribute in `shell.nix`:

```
1 # shell.nix
2 (import ../.).shell
```

Complete example

Assume your package is defined in `package.nix`:

```
1 # package.nix
2 { cowsay, runCommand }:
3 runCommand "cowsay-output" { buildInputs = [ cowsay ]; } ''
4   cowsay Hello, Nix! > $out
5   ''
```

In this example, `cowsay` is declared as a build-time dependency using `buildInputs`.

Further assume your project is defined in `default.nix`:

```
1 # default.nix
2 let
3   nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
4   pkgs = import nixpkgs { config = {}; overlays = []; };
5 in
```

(continues on next page)

²⁷⁷ <https://nixos.org/manual/nixpkgs/stable/#sec-pkgs-mkShell-attributes>

(continued from previous page)

```

6 {
7   myPackage = pkgs.callPackage ./package.nix {};
8 }

```

Add an attribute to `default.nix` specifying an environment:

```

let
  nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
  pkgs = import nixpkgs { config = {}; overlays = []; };
in
{
  myPackage = pkgs.callPackage ./package.nix {};
+ shell = pkgs.mkShellNoCC {
+ };
}

```

Move the `myPackage` attribute into the `let` binding to be able to re-use it. Then take the package's dependencies into the environment with `inputsFrom`²⁷⁸:

```

let
  nixpkgs = fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11";
  pkgs = import nixpkgs { config = {}; overlays = []; };
+ myPackage = pkgs.callPackage ./package.nix {};
in
{
- myPackage = pkgs.callPackage ./package.nix {};
+ inherit myPackage;
  shell = pkgs.mkShellNoCC {
+   inputsFrom = [ myPackage ];
  };
}

```

Finally, import the `shell` attribute in `shell.nix`:

```

1 # shell.nix
2 (import ../.).shell

```

Check the development environment, it contains the build-time dependency `cowsay`:

```

$ nix-shell --pure
[nix-shell]$ cowsay shell.nix

```

Next steps

- *Towards reproducibility: pinning Nixpkgs* (page 11)
- *Automatic environment activation with direnv* (page 134)
- *Setting up a Python development environment* (page 139)
- *Packaging existing software with Nix* (page 40)

3.1.4 Automatically managing remote sources with `npins`

The Nix language describes dependencies between files that Nix manages. Nix expressions themselves can depend on remote sources, and there are multiple ways to specify their origin, as shown in *Towards reproducibility: pinning Nixpkgs* (page 11).

²⁷⁸ <https://nixos.org/manual/nixpkgs/stable/#sec-pkgs-mkShell-attributes>

For more automation around handling remote sources, set up `npins`²⁷⁹ in your project:

```
$ nix-shell -p npins --run "npins init --bare; npins add github nixos nixpkgs --
↳branch nixos-23.11"
```

This command will fetch the latest revision of the Nixpkgs 23.11 release branch. In the current directory it will generate `npins/sources.json`, which will contain a pinned reference to the obtained revision. It will also create `npins/default.nix`, which exposes those dependencies as an attribute set.

Import the generated `npins/default.nix` as the default value for the argument to the function in `default.nix` and use it to refer to the Nixpkgs source directory:

```
1 {
2   sources ? import ./npins,
3   system ? builtins.currentSystem,
4   pkgs ? import sources.nixpkgs { inherit system; config = {}; overlays = []; },
5 }:
6 {
7   package = pkgs.hello;
8 }
```

`nix-build` will call the top-level function with the empty attribute set `{}`, or with the attributes passed via `--arg`²⁸⁰ or `--argstr`²⁸¹. This pattern allows *overriding remote sources* (page 137) programmatically.

Add `npins` to the development environment for your project to have it readily available:

```
{
  sources ? import ./npins,
  system ? builtins.currentSystem,
  pkgs ? import sources.nixpkgs { inherit system; config = {}; overlays = []; },
}:
- {
+ rec {
  package = pkgs.hello;
+ shell = pkgs.mkShellNoCC {
+   inputsFrom = [ package ];
+   packages = with pkgs; [
+     npins
+   ];
+ };
}
```

Also add a `shell.nix` to enter that environment more conveniently:

```
1 (import ../. {}).shell
```

See *Dependencies in the development shell* (page 135) for details, and note that here you have to pass an empty attribute set to the imported expression, since `default.nix` now contains a function.

Overriding sources

As an example, we will use the previously created expression with an older version of Nixpkgs.

Enter the development environment, create a new directory, and set up `npins` with a different version of Nixpkgs:

```
$ nix-shell
[nix-shell]$ mkdir old
```

(continues on next page)

²⁷⁹ <https://github.com/andir/npins/>

²⁸⁰ <https://nix.dev/manual/nix/stable/command-ref/nix-build#opt-arg>

²⁸¹ <https://nix.dev/manual/nix/stable/command-ref/nix-build#opt-argstr>

(continued from previous page)

```
[nix-shell]$ cd old
[nix-shell]$ npins init --bare
[nix-shell]$ npins add github nixos nixpkgs --branch nixos-21.11
```

Create a file `default.nix` in the new directory to import the original one with the sources you just created.

```
import ../default.nix { sources = import ./npins; }
```

This will result in a different version being built:

```
$ nix-build -A build
$ ./result/bin/hello --version | head -1
hello (GNU Hello) 2.10
```

Sources can also be overridden on the command line:

```
nix-build .. -A build --arg sources 'import ./npins'
```

Migrating from niv

A previous version of this guide recommended using `niv`²⁸², a similar pin manager written in Haskell.

If you have a project using `niv`, you can import remote source definitions into `npins`:

```
npins import-niv
```

Warning

All the imported entries will be updated, so they won't necessarily point to the same commits as before.

Managing NixOS configurations

NixOS defaults to using channels to locate `nixpkgs`. You can instead pin a version using `npins` from the `system`. `nix` endpoint (available since 26.05):

```
1 let
2   sources = import ./npins;
3 in
4 import "${sources.nixpkgs}/nixos" {
5   configuration = ./configuration.nix;
6 }
```

Before NixOS 26.05's `system.nix` use:

```
sudo NIX_PATH="nixos-config=configuration.nix:nixpkgs=$(nix-instantiate --raw --
↪eval npins -A nixpkgs.outPath)" nixos-rebuild switch
```

If you use `npins` with `system.nix`, disable channels in your configuration:

```
1 # configuration.nix
2 {
3   # ...
4   nix.channel.enable = false;
5 }
```

²⁸² <https://github.com/nmattia/niv/>

To make such pinned dependencies available as [look-up paths](#)²⁸³ (like `<nixpkgs>`) while using the NixOS configuration, one may use:

```
1 # configuration.nix
2 { lib, ... }:
3 let
4   sources = import ./npins;
5 in
6 {
7   # ...
8   nix.nixPath = lib.mapAttrsToList (k: v: "${k}=${v}") sources;
9 }
```

To use the [v3 command line](#)²⁸⁴ and run programs from dependencies exposing packages through a [flake](#)²⁸⁵, like `nix run nixpkgs#hello`, you can enable flakes and add the pins to the flake registry like:

```
1 # configuration.nix
2 { lib, ... }:
3 let
4   sources = import ./npins;
5 in
6 {
7   # ...
8   experimental-features = "nix-command flakes";
9   nix.registry = lib.mapAttrs (_: path: {
10     to = {
11       type = "path";
12       inherit path;
13     };
14   }) sources;
```

Next steps

- Check the built-in help for more information:

```
npins --help
```

- For more details and examples of the different ways to specify remote sources, see *Towards reproducibility: pinning Nixpkgs* (page 11).

3.1.5 Setting up a Python development environment

In this example you will build a Python web application using the [Flask](#)²⁸⁶ web framework as an exercise. To make the best use of it, you should be familiar with *defining declarative shell environments* (page 8).

Create a new file called `myapp.py` and add the following code:

```
#!/usr/bin/env python

from flask import Flask

app = Flask(__name__)

@app.route("/")
```

(continues on next page)

²⁸³ <https://nix.dev/tutorials/nix-language.html#lookup-paths>

²⁸⁴ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix.html>

²⁸⁵ <https://nix.dev/concepts/flakes>

²⁸⁶ <https://flask.palletsprojects.com>

(continued from previous page)

```
def hello():
    return {
        "message": "Hello, Nix!"
    }

def run():
    app.run(host="0.0.0.0", port=5000)

if __name__ == "__main__":
    run()
```

This is a simple Flask application which serves a JSON document with the message "Hello, Nix!".

Create a new file `shell.nix` to declare the development environment:

```
{ pkgs ? import (fetchTarball "https://github.com/NixOS/nixpkgs/tarball/nixos-23.11") {} }:
```

```
pkgs.mkShellNoCC {
  packages = with pkgs; [
    (python3.withPackages (ps: [ ps.flask ]))
    curl
    jq
  ];
}
```

This describes a shell environment with an instance of `python3` that includes the `flask` package using `python3.withPackages`²⁸⁷. It also contains `curl`²⁸⁸, a utility to perform web requests, and `jq`²⁸⁹, a tool to parse and format JSON documents.

Both of them are not Python packages. If you went with Python's `virtualenv`²⁹⁰, it would not be possible to add these utilities to the development environment without additional manual steps.

Run `nix-shell` to enter the environment you just declared:

```
$ nix-shell
these 2 derivations will be built:
  /nix/store/5yvz7zf8yzck6r9z4f1br9sh71vqkimk-builder.pl.drv
  /nix/store/aihggjkf856dbpjjqalgrdmxyd8a5j2m-python3-3.9.13-env.drv
these 93 paths will be fetched (109.50 MiB download, 468.52 MiB unpacked):
  /nix/store/0xxjx37fcy2nl3yz6igmv4mag2a7giq6-glibc-2.33-123
  /nix/store/138azk9hs5a2yp3zzx6iy1vdwi9q26wv-hook
...
[nix-shell:~]$
```

Start the web application within this shell environment:

```
[nix-shell:~]$ python ./myapp.py
* Serving Flask app 'myapp'
* Debug mode: off
WARNING: This is a development server. Do not use it in a production deployment.
  ↳ Use a production WSGI server instead.
* Running on all addresses (0.0.0.0)
```

(continues on next page)

²⁸⁷ <https://nixos.org/manual/nixpkgs/stable/#python.withpackages-function>

²⁸⁸ <https://search.nixos.org/packages?show=curl>

²⁸⁹ <https://search.nixos.org/packages?show=jq>

²⁹⁰ <https://virtualenv.pypa.io/en/latest/>

(continued from previous page)

```
* Running on http://127.0.0.1:5000
* Running on http://192.168.1.100:5000
Press CTRL+C to quit
```

You now have a running Python web application. Try it out.

Open a new terminal to start another session of the shell environment and follow the commands below:

```
$ nix-shell

[nix-shell:~]$ curl 127.0.0.1:5000
{"message":"Hello, Nix!"}

[nix-shell:~]$ curl 127.0.0.1:5000 | jq '.message'
```

% Total	% Received	% Xferd	Average	Speed	Time	Time	Time	Current
			Dload	Upload	Total	Spent	Left	Speed
100	26	100	26	0	0	13785	0	--:--:-- --:--:-- --:--:-- 26000

```
"Hello, Nix!"
```

As demonstrated, you can use both `curl` and `jq` to test the running web application without any manual installation.

You can commit the files we created to version control and share them with other people. Others can now use the same shell environment as long as they have *Nix installed* (page 1).

Next steps

- *Packaging existing software with Nix* (page 40)
- *Working with local files* (page 57)
- *Automatic environment activation with direnv* (page 134)
- *Automatically managing remote sources with npins* (page 136)

3.1.6 Setting up post-build hooks

This guide shows how to use the Nix `post-build-hook`²⁹¹ configuration option to automatically upload build results to an S3-compatible binary cache²⁹².

Implementation caveats

This is a simple and working example, but it is not suitable for all use cases.

The post-build hook program runs after each executed build, and blocks the build loop. The build loop exits if the hook program fails.

Concretely, this implementation will make Nix slow or unusable when the network connection is slow or unreliable. A more advanced implementation might pass the store paths to a user-supplied daemon or queue for processing the store paths outside of the build loop.

Prerequisites

This tutorial assumes you have [configured an S3-compatible binary cache](#)²⁹³, and that the `root` user's default AWS profile can upload to the bucket.

²⁹¹ <https://nix.dev/manual/nix/2.22/command-ref/conf-file#conf-post-build-hook>

²⁹² <https://nix.dev/manual/nix/2.22/store/types/s3-binary-cache-store>

²⁹³ <https://nix.dev/manual/nix/2.22/store/types/s3-binary-cache-store#authenticated-writes-to-your-s3-compatible-binary-cache>

Set up a signing key

Use `nix-store --generate-binary-cache-key`²⁹⁴ to create a pair of cryptographic keys. You will sign paths with the private key, and distribute the public key for verifying the authenticity of the paths.

```
$ nix-store --generate-binary-cache-key example-nix-cache-1 /etc/nix/key.private /
  ↳etc/nix/key.public
$ cat /etc/nix/key.public
example-nix-cache-1:1/cKDz3QCCOmwcztD2eV6Coggp6rqc9DGjWv7C0G+rM=
```

Configure Nix to use a custom binary cache (page 133) on any machine that will access the bucket. For example, add the cache URL to `substituters`²⁹⁵ and the public key to `trusted-public-keys`²⁹⁶ in `nix.conf`:

```
substituters = https://cache.nixos.org/ s3://example-nix-cache
trusted-public-keys = cache.nixos.org-
  ↳1:6NChdD59X431o0gWypbMrAURkbJ16ZPMQFGspcDShjY= example-nix-cache-1:/
  ↳cKDz3QCCOmwcztD2eV6Coggp6rqc9DGjWv7C0G+rM=
```

Machines that build for the cache must sign derivations using the private key. The path to the file containing the private key you just generated must be added to the `secret-key-files`²⁹⁷ setting for those machines:

```
secret-key-files = /etc/nix/key.private
```

Implementing the build hook

Write the following script to `/etc/nix/upload-to-cache.sh`:

```
#!/bin/sh
set -eu
set -f # disable globbing
export IFS=' '
echo "Uploading paths" $OUT_PATHS
exec nix copy --to "s3://example-nix-cache" $OUT_PATHS
```

The `$OUT_PATHS` variable is a space-separated list of Nix store paths. In this case, we expect and want the shell to perform word splitting to make each output path its own argument to `nix store sign`. Nix guarantees the paths will not contain any spaces, however a store path might contain glob characters. The `set -f` disables globbing in the shell.

Make sure the hook program is executable by the `root` user:

```
# chmod +x /etc/nix/upload-to-cache.sh
```

Updating Nix configuration

Set the `post-build-hook`²⁹⁸ configuration option on the local machine to run the hook:

```
post-build-hook = /etc/nix/upload-to-cache.sh
```

Then restart the `nix-daemon` on all involved machines, e.g. with

```
kill nix-daemon
```

²⁹⁴ <https://nix.dev/manual/nix/2.22/command-ref/nix-store/generate-binary-cache-key>

²⁹⁵ <https://nix.dev/manual/nix/2.22/command-ref/conf-file#conf-substituters>

²⁹⁶ <https://nix.dev/manual/nix/2.22/command-ref/conf-file#conf-trusted-public-keys>

²⁹⁷ <https://nix.dev/manual/nix/2.22/command-ref/conf-file#conf-secret-key-files>

²⁹⁸ <https://nix.dev/manual/nix/2.22/command-ref/conf-file#conf-post-build-hook>

Testing

Build any derivation, for example:

```
$ nix-build -E '(import <nixpkgs> {}).writeText "example" (builtins.toString_
↳builtins.currentTime)'
this derivation will be built:
  /nix/store/s4pnfbkalzy5qz57qs6yybna8wylkig6-example.drv
building '/nix/store/s4pnfbkalzy5qz57qs6yybna8wylkig6-example.drv'...
running post-build-hook '/home/grahamc/projects/github.com/NixOS/nix/post-hook.sh'.
↳...
post-build-hook: Signing paths /nix/store/ibcyipq5gf91838ldx40mjsp0b8w9n18-example
post-build-hook: Uploading paths /
↳nix/store/ibcyipq5gf91838ldx40mjsp0b8w9n18-example
/nix/store/ibcyipq5gf91838ldx40mjsp0b8w9n18-example
```

To check that the hook took effect, delete the path from the store, and try substituting it from the binary cache:

```
$ rm ./result
$ nix-store --delete /nix/store/ibcyipq5gf91838ldx40mjsp0b8w9n18-example
$ nix-store --realise /nix/store/ibcyipq5gf91838ldx40mjsp0b8w9n18-example
copying path '/nix/store/m8bmqrch6l3h8s0k3d673xpmipcdpsa-example from
↳'s3://example-nix-cache'...
warning: you did not specify '--add-root'; the result might be removed by the_
↳garbage collector
/nix/store/m8bmqrch6l3h8s0k3d673xpmipcdpsa-example
```

Conclusion

You have configured Nix to automatically sign and upload every local build to a remote S3-compatible binary cache.

Before deploying this to production, be sure to consider the *implementation caveats* (page 141).

3.1.7 Continuous integration with GitHub Actions

Set up [GitHub Actions](https://github.com/features/actions)²⁹⁹ as your continuous integration (CI) workflow for commits and pull requests.

Nix lets CI build and cache developer environments for every project on every branch using binary caches.

Build time is a key CI metric. Cachix (below) is the most straightforward caching option.

Caching builds using Cachix

Using [Cachix](https://cachix.org/)³⁰⁰ you'll never have to waste time building a derivation twice, and you'll share built derivations with all your developers.

After each job, just-built derivations are pushed to your binary cache.

Before each job, derivations to be built are first substituted (if they exist) from your binary cache.

1. Creating your first binary cache

It's recommended to have different binary caches per team, depending on who will have write/read access to it.

Fill out the form on the [create binary cache](https://cachix.org/)³⁰¹ page.

On your freshly created binary cache, follow the **Push binaries** tab instructions.

²⁹⁹ <https://github.com/features/actions>

³⁰⁰ <https://cachix.org/>

³⁰¹ <https://app.cachix.org/cache>

2. Setting up secrets

On your GitHub repository or organization (for use across all repositories):

1. Click on Settings.
2. Click on Secrets.
3. Add your previously generated secrets (CACHIX_SIGNING_KEY and/or CACHIX_AUTH_TOKEN).

3. Setting up GitHub Actions

Create `.github/workflows/test.yml` with:

```
name: "Test"
on:
  pull_request:
  push:
jobs:
  tests:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
      - uses: cachix/install-nix-action@v25
        with:
          nix_path: nixpkgs=channel:nixos-unstable
      - uses: cachix/cachix-action@v14
        with:
          name: mycache
          # If you chose signing key for write access
          signingKey: '${{ secrets.CACHIX_SIGNING_KEY }}'
          # If you chose API tokens for write access OR if you have a private cache
          authToken: '${{ secrets.CACHIX_AUTH_TOKEN }}'
      - run: nix-build
      - run: nix-shell --run "echo OK"
```

Once you commit and push to your GitHub repository, you should see status checks appearing on commits and PRs.

Next steps

- See [GitHub Actions workflow syntax](#)³⁰²
- To quickly set up a Nix project read through [Getting started Nix template](#)³⁰³.

3.2 Best practices

3.2.1 URLs

The Nix language syntax supports bare URLs, so one could write `https://example.com` instead of `"https://example.com"`

RFC 45³⁰⁴ was accepted to deprecate unquoted URLs and provides a number of arguments for how this feature does more harm than good.

Tip

Always quote URLs.

³⁰² <https://docs.github.com/en/actions/reference/workflow-syntax-for-github-actions>

³⁰³ <https://github.com/nix-dot-dev/getting-started-nix-template>

³⁰⁴ <https://github.com/NixOS/rfcs/pull/45>

3.2.2 Recursive attribute set `rec { ... }`

`rec` allows you to reference names within the same attribute set.

Example:

```
rec {
  a = 1;
  b = a + 2;
}
```

```
{ a = 1; b = 3; }
```

A common pitfall is to introduce a hard-to-debug error `infinite recursion` when shadowing a name. The simplest example for this is:

```
let a = 1; in rec { a = a; }
```

Tip

Avoid `rec`. Use `let ... in`.

Example:

```
let
  a = 1;
in {
  a = a;
  b = a + 2;
}
```

Tip

Self-reference can be achieved by explicitly naming the attribute set:

```
let
  argset = {
    a = 1;
    b = argset.a + 2;
  };
in
  argset
```

3.2.3 `with scopes`

It's still common to see the following expression in the wild:

```
with (import <nixpkgs> {});

# ... lots of code
```

This brings all attributes of the imported expression into scope of the current expression.

This approach has problems:

- Static analysis can't reason about the code, because it would have to actually evaluate this file to see which names are in scope.
- When more than one `with` is used, it's not clear anymore where the names are coming from.

- Scoping rules for `with` are not intuitive, see this [Nix issue for details](#)³⁰⁵.

Tip

Do not use `with` at the top of a Nix file. Explicitly assign names in a `let` expression.

Example:

```
let
  pkgs = import <nixpkgs> {};
  inherit (pkgs) curl jq;
in

# ...
```

Smaller scopes are usually less problematic, but can still lead to surprises due to scoping rules.

Tip

If you want to avoid `with` altogether, try replacing expressions of this form

```
buildInputs = with pkgs; [ curl jq ];
```

with the following:

```
buildInputs = builtins.attrValues {
  inherit (pkgs) curl jq;
};
```

3.2.4 <...> lookup paths

You will often encounter Nix language code samples that refer to `<nixpkgs>`.

`<...>` is special syntax that was [introduced in 2011](#)³⁰⁶ to conveniently access values from the environment variable `$NIX_PATH`³⁰⁷.

This means the value of a lookup path depends on external system state. When using lookup paths, the same Nix expression can produce different results.

In most cases, `$NIX_PATH` is set to the latest channel when Nix is installed, and is therefore likely to differ from machine to machine.

Note

[Channels](#)³⁰⁸ are a mechanism for referencing remote Nix expressions and retrieving their latest version.

The state of a subscribed channel is external to the Nix expressions relying on it. It is not easily portable across machines. This may limit reproducibility.

For example, two developers on different machines are likely to have `<nixpkgs>` point to different revisions of the *Nixpkgs* repository. Builds may work for one and fail for the other, causing confusion.

³⁰⁵ <https://github.com/NixOS/nix/issues/490>

³⁰⁶ <https://github.com/NixOS/nix/commit/1ecc97b6bdb27e56d832ca48cdafd3dbb5185a04>

³⁰⁷ https://nix.dev/manual/nix/stable/command-ref/env-common.html#env-NIX_PATH

³⁰⁸ <https://nix.dev/manual/nix/stable/command-ref/nix-channel.html>

Tip

Declare dependencies explicitly using the techniques shown in *Towards reproducibility: pinning Nixpkgs* (page 11).
Do not use lookup paths, except in minimal examples.

Some tools expect the lookup path to be set. In that case:

Tip

Set `$NIX_PATH` to a known value in a central location under version control.

NixOS

On NixOS, `$NIX_PATH` can be set permanently with the `nix.nixPath`³⁰⁹ option.

3.2.5 Reproducible Nixpkgs configuration

To quickly obtain packages for demonstration, we use the following concise pattern:

```
import <nixpkgs> { }
```

However, even when `<nixpkgs>` is replaced as shown in *Towards reproducibility: pinning Nixpkgs* (page 11), the result may still not be fully reproducible. This is because for historical reasons the Nixpkgs top-level expression³¹⁰ by default impurely reads from the file system to obtain configuration parameters. Systems that have the appropriate files populated may end up with different results.

It is a well-known problem that cannot be resolved without breaking existing setups.

Tip

Explicitly set `config`³¹¹ and `overlays`³¹² when importing Nixpkgs:

```
import <nixpkgs> { config = {}; overlays = []; }
```

This is what we do in our tutorials to ensure that the examples will behave exactly as expected. We skip it in minimal examples to reduce distractions.

3.2.6 Updating nested attribute sets

The attribute set update operator³¹³ merges two attribute sets.

Example:

```
{ a = 1; b = 2; } // { b = 3; c = 4; }
```

```
{ a = 1; b = 3; c = 4; }
```

However, names on the right take precedence, and updates are shallow.

Example:

³⁰⁹ <https://search.nixos.org/options?show=nix.nixPath>

³¹⁰ <https://github.com/NixOS/nixpkgs/blob/master/default.nix>

³¹¹ <https://nixos.org/manual/nixpkgs/stable/#chap-packageconfig>

³¹² <https://nixos.org/manual/nixpkgs/stable/#chap-overlays>

³¹³ <https://nix.dev/manual/nix/stable/language/operators.html#update>

```
{ a = { b = 1; }; } // { a = { c = 3; }; }
```

```
{ a = { c = 3; }; }
```

Here, key `b` was completely removed, because the whole `a` value was replaced.

Tip

Use the `pkgs.lib.recursiveUpdate`³¹⁴ Nixpkgs function:

```
let pkgs = import <nixpkgs> {}; in
pkgs.lib.recursiveUpdate { a = { b = 1; }; } { a = { c = 3; }; }

{ a = { b = 1; c = 3; }; }
```

3.2.7 Reproducible source paths

```
let pkgs = import <nixpkgs> {}; in

pkgs.stdenv.mkDerivation {
  name = "foo";
  src = ./.;
}
```

If the Nix file containing this expression is in `/home/myuser/myproject`, then the store path of `src` will be `/nix/store/<hash>-myproject`.

The problem is that now your build is no longer reproducible, as it depends on the parent directory name. That cannot be declared in the source code, and results in an impurity.

If someone builds the project in a directory with a different name, they will get a different store path for `src` and everything that depends on it. This can be the cause of needless rebuilds.

Tip

Use `builtins.path`³¹⁵ with the `name` attribute set to something fixed.

This will derive the symbolic name of the store path from `name` instead of the working directory:

```
let pkgs = import <nixpkgs> {}; in

pkgs.stdenv.mkDerivation {
  name = "foo";
  src = builtins.path { path = ./.; name = "myproject"; };
}
```

3.3 Troubleshooting

This page is a collection of tips to solve problems you may encounter when using Nix.

³¹⁴ <https://nixos.org/manual/nixpkgs/stable/#function-library-lib.attrsets.recursiveUpdate>

³¹⁵ <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-path>

3.3.1 What to do if a binary cache is down or unreachable?

Pass `--option substitute false`³¹⁶ to Nix commands.

3.3.2 How to force Nix to re-check if something exists in the binary cache?

Nix keeps track of what's available in binary caches so it doesn't have to query them on every command. This includes negative answers, that is, if a given store path cannot be substituted.

Pass the `--narinfo-cache-negative-ttl`³¹⁷ option to set the cache timeout in seconds.

3.3.3 How to fix: error: querying path in database: database disk image is malformed

This is a [known issue](#)³¹⁸. Try:

```
$ sqlite3 /nix/var/nix/db/db.sqlite "pragma integrity_check"
```

Which will print the errors in the [database](#)³¹⁹. If the errors are due to missing references, the following may work:

```
$ mv /nix/var/nix/db/db.sqlite /nix/var/nix/db/db.sqlite-bkp
$ sqlite3 /nix/var/nix/db/db.sqlite-bkp ".dump" | sqlite3 /nix/var/nix/db/db.sqlite
```

3.3.4 How to fix: error: current Nix store schema is version 10, but I only support 7

This is a [known issue](#)³²⁰.

It means that using a new version of Nix upgraded the SQLite schema of the [database](#)³²¹, and then you tried to use an older version of Nix.

The solution is to dump the database, and use the old Nix version to re-import the data:

```
$ /path/to/nix/unstable/bin/nix-store --dump-db > /tmp/db.dump
$ mv /nix/var/nix/db /nix/var/nix/db.toonew
$ mkdir /nix/var/nix/db
$ nix-store --load-db < /tmp/db.dump
```

3.3.5 How to fix: writing to file: Connection reset by peer

This may mean you are trying to import too large a file or directory into the [Nix store](#)³²², or your machine is running out of resources, such as disk space or memory.

Try to reduce the size of the directory to import, or run [garbage collection](#)³²³.

3.3.6 macOS update breaks Nix installation

This is a [known issue](#)³²⁴. The [Nix installer](#)³²⁵ modifies `/etc/zshrc`. When macOS is updated, it will typically overwrite `/etc/zshrc` again.

As a workaround, add the following code snippet to the end of `/etc/zshrc` and restart the shell:

³¹⁶ <https://nix.dev/manual/nix/stable/command-ref/conf-file#conf-substitute>

³¹⁷ <https://nix.dev/manual/nix/stable/command-ref/conf-file.html#conf-narinfo-cache-negative-ttl>

³¹⁸ <https://github.com/NixOS/nix/issues/1353>

³¹⁹ <https://nix.dev/manual/nix/stable/glossary#gloss-nix-database>

³²⁰ <https://github.com/NixOS/nix/issues/1251>

³²¹ <https://nix.dev/manual/nix/stable/glossary#gloss-nix-database>

³²² <https://nix.dev/manual/nix/stable/glossary#gloss-store>

³²³ <https://nix.dev/manual/nix/stable/command-ref/nix-collect-garbage>

³²⁴ <https://github.com/NixOS/nix/issues/3616>

³²⁵ <https://nix.dev/manual/nix/latest/installation/installing-binary>

```
if [ -e '/nix/var/nix/profiles/default/etc/profile.d/nix-daemon.sh' ]; then
  . '/nix/var/nix/profiles/default/etc/profile.d/nix-daemon.sh'
fi
```

3.4 Frequently Asked Questions

3.4.1 Nix

How to format Nix language code automatically?

`nixfmt`³²⁶ is the official formatter for *Nix language* code. Please refer to its source repository for installation instructions.

`nixfmt` is used to format all code³²⁷ in *Nixpkgs*.

How to convert between paths and strings in the Nix language?

See the Nix reference manual on string interpolation³²⁸ and operators on paths and strings³²⁹.

How to build reverse dependencies of a package?

```
$ nix-shell -p nixpkgs-review --run "nixpkgs-review wip"
```

How can I manage dotfiles in \$HOME with Nix?

See <https://github.com/nix-community/home-manager>

What's the recommended process for building custom packages?

Please read *Packaging existing software with Nix* (page 40).

How to use a clone of the Nixpkgs repository to update or write new packages?

Please read *Packaging existing software with Nix* (page 40) and the Nixpkgs contributing guide³³⁰.

3.4.2 NixOS

How to run non-nix executables?

NixOS cannot run dynamically linked executables intended for generic Linux environments out of the box. This is because, by design, it does not have a global library path, nor does it follow the *Filesystem Hierarchy Standard*³³¹ (FHS).

There are a few ways to resolve this mismatch in environment expectations:

- Use the version packaged in Nixpkgs, if there is one. You can search available packages at <https://search.nixos.org/packages>.
- Write a Nix expression for the program to package it in your own configuration.

There are multiple approaches to this:

- Build from source.

Many open-source programs are highly flexible at compile time in terms of where their files go. For an introduction to this, see *Packaging existing software with Nix* (page 40).

³²⁶ <https://github.com/NixOS/nixfmt>

³²⁷ <https://github.com/NixOS/nixpkgs/blob/master/ci/default.nix>

³²⁸ <https://nix.dev/manual/nix/2.19/language/string-interpolation>

³²⁹ <https://nix.dev/manual/nix/2.19/language/operators#string-concatenation>

³³⁰ <https://github.com/NixOS/nixpkgs/blob/master/CONTRIBUTING.md>

³³¹ https://refspecs.linuxfoundation.org/FHS_3.0/fhs/index.html

- Modify the program's ELF header³³² to include paths to libraries using `autoPatchelfHook`³³³.

Do this if building from source isn't feasible.

- Wrap the program to run in an FHS-like environment using `buildFHSEnv`³³⁴.

This is a last resort, but sometimes necessary, for example if the program downloads and runs other executables.

- Create a library path that only applies to unpackaged programs by using `nix-ld`³³⁵. Add this to your `configuration.nix`:

```
1 programs.nix-ld.enable = true;
2 programs.nix-ld.libraries = with pkgs; [
3   # Add any missing dynamic libraries for unpackaged programs
4   # here, NOT in environment.systemPackages
5 ];
```

Then run `nixos-rebuild switch`, and log out and back in again to propagate the new environment variables. (This is only necessary when enabling `nix-ld`; changes in included libraries take effect immediately on rebuild.)

Note

`nix-ld` does not work for 32-bit executables on `x86_64` machines.

- Run your program in the FHS-like environment made for the Steam package using `steam-run`³³⁶:

```
$ nix-shell -p steam-run --run "steam-run <command>"
```

How to build my own ISO?

See <http://nixos.org/nixos/manual/index.html#sec-building-image>

How do I connect to any of the machines in NixOS tests?

Apply the following patch:

```
diff --git a/nixos/lib/test-driver/test-driver.pl
< b/nixos/lib/test-driver/test-driver.pl
index 8ad0d67..838fbdd 100644
--- a/nixos/lib/test-driver/test-driver.pl
+++ b/nixos/lib/test-driver/test-driver.pl
@@ -34,7 +34,7 @@ foreach my $vlan (split / /, $ENV{VLANS} || "") {
    if ($pid == 0) {
        dup2(fileno($pty->slave), 0);
        dup2(fileno($stdoutW), 1);
-       exec "vde_switch -s $socket" or _exit(1);
+       exec "vde_switch -tap tap0 -s $socket" or _exit(1);
    }
    close $stdoutW;
    print $pty "version\n";
```

And then the `vde_switch` network should be accessible locally.

³³² https://en.wikipedia.org/wiki/Executable_and_Linkable_Format

³³³ <https://nixos.org/manual/nixpkgs/stable/#setup-hook-autopatchelfhook>

³³⁴ <https://nixos.org/manual/nixpkgs/stable/#sec-fhs-environments>

³³⁵ <https://github.com/Mic92/nix-ld>

³³⁶ <https://nixos.org/manual/nixpkgs/stable/#sec-steam-run>

How to bootstrap NixOS inside an existing Linux installation?

There are a couple of tools:

- <https://github.com/nix-community/nixos-anywhere>
- <https://github.com/jeaye/nixos-in-place>
- <https://github.com/elitak/nixos-infect>
- <https://github.com/cleverca22/nix-tests/tree/master/kexec>

REFERENCE

These sections contain collections of detailed technical descriptions.

4.1 Glossary

Nix

Build system and package manager.

Read /nix/ (“Nix”).

See also

- *Nix reference manual* (page 154)
- Nix source code³³⁷

Nix language

Programming language to declare packages and configurations for *Nix*.

See also

- *Nix language basics* (page 12)
- Nix language reference³³⁸

Nix expression

Expression written in the *Nix language*.

Nix file

File (`.nix`) containing a *Nix expression*.

Nixpkgs

Software distribution built with *Nix*.

Read /nix 'pækɪdʒɪz/ (“Nix packages”).

See also

- Nixpkgs reference manual³³⁹
- Nixpkgs source code³⁴⁰

³³⁷ <https://github.com/NixOS/nix>

³³⁸ <https://nix.dev/manual/nix/stable/language>

³³⁹ <https://nixos.org/manual/nixpkgs>

³⁴⁰ <https://github.com/NixOS/nixpkgs>

NixOS

Linux distribution based on *Nix* and *Nixpkgs*.

Read /nixs ɔs ɛs/ (“Niks Oh Es”).

See also

- [NixOS reference manual](#)³⁴¹
- [NixOS source code](#)³⁴²

4.2 Nix reference manual

The Nix reference manual is available for multiple versions:

- [Nix pre-release](#)³⁴³
Development build from the `master` branch of the [Nix repository](#)³⁴⁴
- [Nix 2.35](#)³⁴⁵ (single page³⁴⁶)
Latest Nix release
- [Nix 2.34](#)³⁴⁷ (single page³⁴⁸)
Shipped with the rolling release of *Nixpkgs* and *NixOS*
- [Nix 2.34](#)³⁴⁹ (single page³⁵⁰)
Shipped with the current stable release of *Nixpkgs* and *NixOS*: 26.05
- [Nix 2.31](#)³⁵¹ (single page³⁵²)
Shipped with the previous stable release of *Nixpkgs* and *NixOS*: 25.11

Tip

More information on Nixpkgs and NixOS releases: *Which channel branch should I use?* (page 164)

4.3 Further reading

4.3.1 Nix language tutorials

- [Nix language one-pager reference](#)³⁵³ (Vincent Ambo, 2019-2021)
Overview of common language features and widely used idioms.
- [A tour of Nix](#)³⁵⁴ (Joachim Schiele, 2015-2022)
Interactive exercises with the Nix language.

³⁴¹ <https://nixos.org/manual/nixos>

³⁴² <https://github.com/NixOS/nixpkgs/tree/master/nixos>

³⁴³ <https://nix.dev/manual/nix/development/>

³⁴⁴ <https://github.com/NixOS/nix>

³⁴⁵ <https://nix.dev/manual/nix/latest/>

³⁴⁶ <https://nix.dev/manual/nix/latest/nix-2.35.html>

³⁴⁷ <https://nix.dev/manual/nix/rolling/>

³⁴⁸ <https://nix.dev/manual/nix/rolling/nix-2.34.html>

³⁴⁹ <https://nix.dev/manual/nix/stable/>

³⁵⁰ <https://nix.dev/manual/nix/stable/nix-2.34.html>

³⁵¹ <https://nix.dev/manual/nix/prev-stable/>

³⁵² <https://nix.dev/manual/nix/prev-stable/nix-2.31.html>

³⁵³ <https://github.com/tazjin/nix-1p>

³⁵⁴ <https://nixcloud.io/tour>

- [Video: Nix language overview](#)³⁵⁵ (Wil Taylor, 2021)
Overview of language features.
- [Video: Reading the Nix language](#)³⁵⁶ (Jonas Chevalier, 2019)
Introduction to reading Nix language code.
- [Video: How and Why it Works](#)³⁵⁷ (Graham Christensen, 2019)
Introduction to writing derivations.
- [What You Need to Know About Lazy Evaluation in Nix](#), *Nixcademy*³⁵⁸ (Jacek Galowicz, 2024)

4.3.2 Other articles

- [Nix Pills](#)³⁵⁹
A low-level tutorial on building software packages with Nix, showing in detail how Nixpkgs is constructed.
- [Customizing packages in Nix](#)³⁶⁰ (2022)
An overview of different methods to customize Nix packages.
- [Manage your dot files with Home Manager](#)³⁶¹ (Mattia Gheda, 2021)
A tutorial for getting started with Home Manager.
- [Nix Shorts](#)³⁶²
A series of posts on the basics of how packaging with Nix works.
- [NixOS and Flakes - An unofficial book for beginners](#)³⁶³ (2023)
This tutorial is an introduction to *NixOS* using the experimental Nix *Flakes* (page 159) functionality.

4.3.3 Other videos

- [Nixology](#)³⁶⁴ (Burke Libbey, 2020)
Video series introducing fundamental Nix concepts.
- [The Nix Hour](#)³⁶⁵ (Silvan Mosberger, since 2022)
Weekly series exploring topics and answering questions from all around the Nix ecosystem.
- [Nixpkgs](#)³⁶⁶ (Jon Ringer, 2020-22)
Video series with tutorials on various activities around Nixpkgs.
- [NixOS](#)³⁶⁷ (Wil Taylor, 2021)
Series of tutorials on getting started with NixOS.
- [NixOS Foundation on YouTube](#)³⁶⁸
The official NixOS Foundation channel.

³⁵⁵ https://www.youtube.com/watch?v=eCapIx9heBw&list=PL-saUBvIJzOkjAw_vOac75v-x6EzNzZq-&index=5

³⁵⁶ <https://youtu.be/61MuMY9XFNo>

³⁵⁷ <https://youtu.be/lxtHH838yko>

³⁵⁸ <https://nixcademy.com/posts/what-you-need-to-know-about-laziness/>

³⁵⁹ <https://nixos.org/nixos/nix-pills/index.html>

³⁶⁰ <https://bobvanderlinden.me/customizing-packages-in-nix/>

³⁶¹ <https://ghedam.at/24353/tutorial-getting-started-with-home-manager-for-nix>

³⁶² <https://github.com/justinwoo/nix-shorts>

³⁶³ <https://nixos-and-flakes.thiscute.world>

³⁶⁴ https://www.youtube.com/playlist?list=PLRGI9KQ3_HP_OFRG6R-p4iFgMSK1t5BHs

³⁶⁵ <https://www.youtube.com/playlist?list=PLyzwHTVJIRc8yjlx4VR4LU5A5O44og9in>

³⁶⁶ <https://www.youtube.com/@jonringer117/videos>

³⁶⁷ https://www.youtube.com/playlist?list=PL-saUBvIJzOkjAw_vOac75v-x6EzNzZq-

³⁶⁸ <https://www.youtube.com/@NixOS-Foundation/playlists>

- [NixCon on YouTube](#)³⁶⁹

Recordings of NixCon talks and discussions.

4.4 Pinning Nixpkgs

Specifying remote Nix expressions, such as the one provided by Nixpkgs, can be done in several ways:

- `$NIX_PATH` environment variable³⁷⁰
- `-I` option³⁷¹ to most commands like `nix-build`, `nix-shell`, etc.
- `fetchurl`³⁷², `fetchTarball`³⁷³, `fetchGit`³⁷⁴ or `Nixpkgs fetchers`³⁷⁵ in Nix expressions

4.4.1 Possible URL values

- Local file path:

```
./path/to/expression.nix
```

Using `./` means that the expression is located in a file `default.nix` in the current directory.

- Pinned to a specific commit:

```
https://github.com/NixOS/nixpkgs/archive/
↪eabc38219184cc3e04a974fe31857d8e0eac098d.tar.gz
```

- Using the latest channel version, meaning all tests have passed:

```
http://nixos.org/channels/nixos-22.11/nixexprs.tar.xz
```

- Shorthand syntax for channels:

```
channel:nixos-22.11
```

- Using the latest channel version, hosted by GitHub:

```
https://github.com/NixOS/nixpkgs/archive/nixos-22.11.tar.gz
```

- Using the latest commit on the release branch, but not tested yet:

```
https://github.com/NixOS/nixpkgs/archive/release-21.11.tar.gz
```

4.4.2 Examples

- `$ nix-build -I ~/dev`
- `$ nix-build -I nixpkgs=http://nixos.org/channels/nixos-22.11/nixexprs.tar.xz`
- `$ nix-build -I nixpkgs=channel:nixos-22.11`
- `$ NIX_PATH=nixpkgs=http://nixos.org/channels/nixos-22.11/nixexprs.tar.xz ↪
↪nix-build`

³⁶⁹ <https://www.youtube.com/@NixCon>

³⁷⁰ https://nix.dev/manual/nix/stable/command-ref/env-common.html#env-NIX_PATH

³⁷¹ <https://nix.dev/manual/nix/stable/command-ref/opt-common.html#opt-I>

³⁷² <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-fetchurl>

³⁷³ <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-fetchTarball>

³⁷⁴ <https://nix.dev/manual/nix/stable/language/builtins.html#builtins-fetchGit>

³⁷⁵ <https://nixos.org/manual/nixpkgs/stable/#chap-pkgs-fetchers>

- `$ NIX_PATH=nixpkgs=channel:nixos-22.11 nix-build`

- In the Nix language:

```
1 let
2   pkgs = import (fetchTarball
3     ↪ "https://github.com/NixOS/nixpkgs/archive/nixos-22.11.tar.gz") {};
4 in pkgs.stdenv.mkDerivation { ... }
```

4.4.3 Finding specific commits and releases

status.nixos.org³⁷⁶ provides:

- Latest tested commits for each release - use when pinning to specific commits
- List of active release channels - use when tracking latest channel versions

The complete list of channels is available at nixos.org/channels³⁷⁷.

Tip

More information on Nixpkgs and NixOS releases: *Which channel branch should I use?* (page 164)

³⁷⁶ <https://status.nixos.org/>

³⁷⁷ <https://nixos.org/channels>

CONCEPTS

These sections contain explanations of history and ideas in the Nix ecosystem.

5.1 Flakes

5.1.1 What are flakes?

Flakes offer an entrypoint file `flake.nix` aimed at sharing Nix code. They make it easy to build programs with the same version.

`flake.nix` is a file that declares inputs and outputs with a [standard structure](#)³⁷⁸.

Note: [Experimental](#)³⁷⁹, requires Nix 2.4³⁸⁰.

This file can look like:

```
1 {
2   description = "My example flake";
3
4   inputs = {
5     nixpkgs.url = "github:nixos/nixpkgs?ref=nixos-unstable";
6   };
7
8   outputs = { self, nixpkgs }: {
9     packages.x86_64-linux = {
10       default = self.packages.x86_64-linux.hello;
11       hello = nixpkgs.legacyPackages.x86_64-linux.hello;
12     };
13   };
14 }
```

`outputs`³⁸¹ include various [built-in types](#)³⁸², but can be [extended](#)³⁸³. You can find an overview of these on the [wiki](#)³⁸⁴.

`inputs`³⁸⁵ let you declare dependencies.

Nix creates a `flake.lock`³⁸⁶ to pin dependencies once you run a `nix` command³⁸⁷.

If these dependencies have `inputs` of their own, Nix will check *their* lock files to find the versions to use. Using the same versions helps make sure programs work as intended, but you can override these.

³⁷⁸ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-flake.html#flake-format>

³⁷⁹ <https://nix.dev/manual/nix/stable/development/experimental-features#xp-feature-flakes>

³⁸⁰ <https://nix.dev/manual/nix/stable/release-notes/rl-2.4.html#highlights>

³⁸¹ https://wiki.nixos.org/wiki/Flakes#Output_schema

³⁸² <https://github.com/NixOS/nix/blob/38c755f168b7c38cd4687aac5d7e59f049658d3/src/nix/flake.cc#L594-L769>

³⁸³ <https://github.com/NixOS/nix/blob/38c755f168b7c38cd4687aac5d7e59f049658d3/src/nix/flake.cc#L772-L776>

³⁸⁴ https://wiki.nixos.org/wiki/Flakes#Output_schema

³⁸⁵ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-flake.html#flake-inputs>

³⁸⁶ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-flake.html#lock-files>

³⁸⁷ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix.html>

`nix command`³⁸⁸s natively integrate with flakes by default.

```
nix build github:NixOS/nixpkgs#hello
```

You may pass [references](#)³⁸⁹ to local (e.g. `.`) or remote (e.g. `github:NixOS/nixpkgs`) project directories. For further details see the reference on `nix command`³⁹⁰s.

Aliases to flakes are stored in a [registry](#)³⁹¹. This can be extended by [command-line](#)³⁹² or by *NixOS* option `nix.registry`³⁹³.

The NixOS manual further explains [flake-based installs](#)³⁹⁴.

5.1.2 Should I use flakes in my project?

Flakes are an experimental extension format with outstanding issues. Its functionality can generally be achieved without them as well.

If you need to run existing software that already used flakes, or want to contribute to their development, feel free to use them. If you want to write Nix code yourself, consider also our guide on [dependency management](#)^{395,433}. This overview can help get what you need from flakes while preserving compatibility.

Discoverability

A first step in use of flakes is to add a `flake.nix` file specifying outputs.

Pros:

- Use the code from other flake projects.
- Nix checks `flake.nix`'s structure is valid.

Cons:

- Flakes have no [parameters](#)³⁹⁶. This means `flake.nix` and its end-user must be explicit about the used `system`³⁹⁷. This is made easier by say `flake-utils`³⁹⁸.
- As an experimental feature, flakes can still change.

Alternatives:

- Use flakes as thin wrappers over existing Nix code. This way, code can be used in both ways.
- Use Nix modules: flake users can import these with `flake = false;`.
- Since NixOS 26.05, one or more NixOS configurations can be loaded from a single `system.nix` [entrypoint](#)³⁹⁹.

Running commands

Flakes are used from Nix's `v3 nix command line interface`⁴⁰⁰. It can build or run programs by a reference like `.` or `github:NixOS/nixpkgs`.

You can enable this for one command by adding:

³⁸⁸ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix.html>

³⁸⁹ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-flake#flake-references>

³⁹⁰ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix.html>

³⁹¹ <https://github.com/NixOS/flake-registry>

³⁹² <https://nix.dev/manual/nix/2.28/command-ref/new-cli/nix3-registry.html>

³⁹³ <https://search.nixos.org/options?channel=unstable&show=nix.registry&query=registry>

³⁹⁴ <https://nixos.org/manual/nixos/stable/#sec-installation-manual-installing>

³⁹⁵ <https://nix.dev/guides/recipes/dependency-management.html>

⁴³³ Nix repositories offering only flake entrypoints may be imported using `flake-inputs`⁴³⁴.

⁴³⁴ <https://github.com/fricklerhandwerk/flake-inputs>

³⁹⁶ <https://github.com/NixOS/nix/issues/2861>

³⁹⁷ <https://github.com/NixOS/nix/issues/3843>

³⁹⁸ <https://github.com/numtide/flake-utils>

³⁹⁹ <https://nixos.org/manual/nixos/stable/release-notes.html#sec-release-26.05-highlights>

⁴⁰⁰ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix.html>

```
--experimental-features 'nix-command flakes'
```

Or permanently in NixOS or Home Manager configurations using:

```
nix.settings.experimental-features = [ "nix-command" "flakes" ];
```

To build the derivation in your `flake.nix`'s `packages.x86_64-linux.default`, run:

```
nix build .#packages.x86_64-linux.default
```

You can shorten this to `nix build .#default`, or just `nix build`.

`nix run` runs programs in `outputs.apps`. `nix run .#default` runs `outputs.apps.default`. Just `nix run` also runs that.

For example, to run the `hello` package from *Nixpkgs*:

```
nix run nixpkgs#hello -- --greeting "hello from flakes"
```

This uses the version set by your registry's alias `nixpkgs`.

To run the `hello` package from *Nixpkgs*' `nixpkgs-unstable` branch:

```
nix run github:NixOS/nixpkgs/nixpkgs-unstable#hello
```

Pros:

- Flakes cache builds to save time on later identical builds. This can save time if you run unchanged builds in Continuous Integration, for example.
- Flakes promote making programs easy to run, also from remote repositories.
- Flakes default to running in *pure mode*⁴⁰¹. This promotes a style of writing programs more likely to make them reproducible⁴³⁵.
- Flakes build only tracked files, for projects using *Git*⁴⁰². This helps prevent rebuilds.

Cons:

- Builds copy the whole `flake` directory to the Nix store. This caches them, but can be *slower*⁴⁰³ for large repositories like *Nixpkgs*.
- The implementation still has issues for both *flakes*⁴⁰⁴ and the *v3 CLI*⁴⁰⁵.
- Files must be staged for flakes to see them.

Alternatives:

- Plain Nix files can be used with the [v2 commands] (like `nix-build`⁴⁰⁶, `nix-shell`⁴⁰⁷), or with v3 commands' `--file flag`⁴⁰⁸ or `-f`.
- In *NixOS*, you can make v3 commands' `nixpkgs` to a package set `pkgs` by setting `nixpkgs.flake.source = pkgs.path;`⁴⁰⁹ in your NixOS configuration. Also see *managing dependencies*⁴¹⁰.

⁴⁰¹ <https://nix.dev/manual/nix/stable/tutorials/nix-language.html#impurities>

⁴³⁵ Even in pure mode, reproducibility is *not actually guaranteed*⁴³⁶.

⁴³⁶ <https://discourse.nixos.org/t/nix-flakes-explained-what-they-solve-why-they-matter-and-the-future/72302/7>

⁴⁰² <https://git-scm.com/>

⁴⁰³ <https://github.com/NixOS/nix/issues/3121>

⁴⁰⁴ <https://github.com/NixOS/nix/issues?q=is%3Aissue+is%3Aopen+label%3Aflakes+sort%3Areactions-%2B1-desc>

⁴⁰⁵ <https://github.com/NixOS/nix/issues?q=is%3Aissue+is%3Aopen+label%3Anew-cli+sort%3Areactions-%2B1-desc>

⁴⁰⁶ <https://nix.dev/manual/nix/stable/command-ref/nix-build.html>

⁴⁰⁷ <https://nix.dev/manual/nix/stable/command-ref/nix-shell.html>

⁴⁰⁸ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-build.html#options-that-change-the-interpretation-of-installables>

⁴⁰⁹ <https://search.nixos.org/options?channel=unstable&show=nixpkgs.flake.source&query=nixpkgs.flake.source>

⁴¹⁰ <https://nix.dev/guides/recipes/dependency-management#managing-nixos-configurations>

- Using `builtins.fetchTree`⁴¹¹ from experimental feature `fetch-tree`⁴¹², `nix run`⁴¹³ may be emulated⁴³⁷ for non-flake entrypoints.

Dependency management

Flakes' inputs attribute can manage dependencies. By default this handles recursive dependencies implicitly. In case a library is used multiple times, this can give different versions of the same library. You can override these if you want using `follows` statements:

```
{
  inputs = {
    nixpkgs.url = "github:nixos/nixpkgs?ref=nixos-unstable";
    home-manager = {
      url = "github:nix-community/home-manager";
      inputs.nixpkgs.follows = "nixpkgs";
    };
  };
}
```

This way, Home Manager's inputs reuse your chosen `nixpkgs`.

Pros:

- Make it easy to reproduce published software, following the versions they used.
- You can override recursive inputs.

Cons:

- Flakes by default follow versions from dependencies' `flake.lock`, so if you don't override these with `follows`, you may get:
 - multiple versions of the same dependency.
 - outdated dependencies, if their versions are not actively updated.
- Dependencies are fetched eagerly, loading dependencies you may not use.
- Dependencies managed by `flake inputs` are hard to override if you don't also use flakes.
- If your `flake` is used as a library, you need to add `follows` statements for all recursive inputs. Otherwise downstream consumers cannot add their `follows` on your indirect inputs.

Alternatives:

- Handle dependencies with `npins`⁴¹⁴.
- Handle dependencies inline using functions such as the `fetchers`⁴¹⁵ or `builtins.fetchTree`⁴¹⁶.
- Use `inputs.<name>.flake = false;`

⁴¹¹ <https://noogle.dev/f/builtins/fetchTree>

⁴¹² <https://nix.dev/manual/nix/stable/development/experimental-features#xp-feature-fetch-tree>

⁴¹³ <https://nix.dev/manual/nix/stable/command-ref/new-cli/nix3-run.html>

⁴³⁷ `nix run github:NixOS/nixpkgs#hello` for non-flake projects may look like `nix-shell -p '(import (builtins.fetchTree "github:NixOS/nixpkgs").outPath { }).hello' --run 'hello'`. A drop-in command `nix-run` using the `nix run` syntax could be defined using a Bash alias like `alias nix-run='run() { $(nix-instantiate --raw --impure --eval --expr "(import <nixpkgs> {}").lib.getExe (import (builtins.fetchTree \"$${cut -d \"#\" -f 1 <<< \"$1\")\"}).outPath { }).$(cut -d \"#\" -f 2 <<< \"$1\")"; }; run'`.

⁴¹⁴ <https://nix.dev/guides/recipes/dependency-management.html>

⁴¹⁵ <https://nixos.org/manual/nixpkgs/stable/#chap-pkgs-fetchers>

⁴¹⁶ <https://noogle.dev/f/builtins/fetchTree>

Flake-only Nix

As flakes (largely⁴³⁸) use Nix as an internal language, you could even place all Nix code in flake files. In the community, such a coding style is called dendritic pattern. Using flakes, this pattern gets easier with library `flake-parts`⁴¹⁷, which lets you spread code over different flake-like files.

Pros:

- Helps use flakes' schema and inputs from any such Nix code.

Cons:

- Makes it harder to access this code without using flakes.

Alternatives:

- Use flakes as thin wrappers over existing Nix code, so code can be used in both ways.
- Use library `flake-compat`⁴¹⁸ to expose a flake's default package or shell to non-flake users.
- Propagate needed parameters across modules explicitly or with NixOS's `specialArgs`⁴¹⁹.

History

- Conception
 - Flakes were proposed in [RFC 49](#)⁴²⁰, and introduced in a [blog post](#)⁴²¹.
- Design
 - The flakes proposal was criticised for trying to solve too many problems at once and at the wrong abstraction layer.
 - The design still has [various problems](#)⁴²² including around versioning, composability, cross-compilation, and tight coupling with nixpkgs.
 - There are also still many [open design questions](#)⁴²³ around the nix CLI.
- Implementation
 - There are still [problems with the implementation](#)⁴²⁴.
- Process
 - While there were still outstanding concerns about the design, the implementation was merged without the RFC having been accepted (and in fact being withdrawn on merge), raising questions about proper process.
 - The RFC was closed with no timeline to conclude the experiment.
 - Flakes had become depended on by many projects, making it harder to iterate on their design without breaking many people's code.
- Community
 - The design had not been accepted by all parts of the community, with e.g. *Nixpkgs* not using it in its internal tooling. As a result of this, branching approaches to flakes have been made, with e.g. company Determinate Systems (which offers proprietary features around flakes) unilaterally declaring the

⁴³⁸ Flakes default to pure mode, isolating builds from the host environment. This is also called hermetic evaluation, and prevents evaluating (non-network) [impure] functions. Flake `inputs` and `metadata` fields cannot be arbitrary Nix expressions. This is to prevent complex, possibly non-terminating computations. The `outputs` field's function parameter must be specified: it does not support `eta-reduction`⁴³⁹.

⁴³⁹ https://wiki.haskell.org/Eta_conversion

⁴¹⁷ <https://github.com/hercules-ci/flake-parts>

⁴¹⁸ <https://github.com/NixOS/flake-compat>

⁴¹⁹ https://nixos.org/manual/nixos/unstable/options#opt-_module.args

⁴²⁰ <https://github.com/NixOS/rfcs/pull/49>

⁴²¹ <https://tweag.io/blog/2020-05-25-flakes/>

⁴²² <https://wiki.lix.systems/books/lix-contributors/page/flakes-feature-freeze#bkmrk-design-issues-of-fla>

⁴²³ <https://github.com/NixOS/nix/issues?q=is%3Aissue+is%3Aopen+label%3Anew-cli+sort%3Areactions-%2B1-desc>

⁴²⁴ <https://github.com/NixOS/nix/issues?q=is%3Aissue+is%3Aopen+label%3Aflakes+sort%3Areactions-%2B1-desc>

feature stable, while community-driven Nix fork Lix [consolidated the featureset](#)⁴²⁵ to a de-facto ‘v1’. Such branching could potentially end up breaking the promise of a unified interface that propelled the flakes experiment in the first place.

5.1.3 Further reading

- [wiki article](#)⁴²⁶
 - [Flakes aren’t real and cannot hurt you: a guide to using Nix flakes the non-flake way](#)⁴²⁷ (Jade Lovelace, January 2024)
 - [Nix Flakes is an experiment that did too much at once...](#)⁴²⁸ ([comments](#)⁴²⁹) (Samuel Dionne-Riel, September 2023)
 - [Experimental does not mean unstable](#)⁴³⁰ ([comments](#)⁴³¹) (Graham Christensen, September 2023)
 - [The Nix Hour: comparing flakes to traditional Nix](#)⁴³² (Silvan Mosberger, November 2022)
-

5.2 Frequently Asked Questions

5.2.1 What is the origin of the name Nix?

The name *Nix* is derived from the Dutch word *niks*, meaning *nothing*; build actions do not see anything that has not been explicitly declared as an input.

— [Nix: A Safe and Policy-Free System for Software Deployment](#)⁴⁴⁰, LISA XVIII, 2004

The Nix logo is inspired by an idea for the Haskell logo⁴⁴¹ and the fact that *nix* is Latin for *snow*⁴⁴².

5.2.2 What are flakes?

See *Flakes* (page 159).

5.2.3 Which channel branch should I use?

Nixpkgs and NixOS have both stable and rolling releases.

These releases are distributed in variants called “channel branches”: Git branches used for releases, which are also converted to Nix channels.

Tip

Consult the [nix-channel](#)⁴⁴³ entry in the Nix Reference Manual for more information on channels, and the [Nixpkgs contributing guide](#)⁴⁴⁴ on the Nixpkgs branching strategy.

⁴²⁵ <https://wiki.linuxsystems/books/lix-contributors/page/flake-stabilisation-proposal>

⁴²⁶ <https://wiki.nixos.org/wiki/Flakes>

⁴²⁷ <https://jade.fyi/blog/flakes-arent-real/>

⁴²⁸ <https://samuel.dionne-riel.com/blog/2023/09/06/flakes-is-an-experiment-that-did-too-much-at-once.html>

⁴²⁹ <https://discourse.nixos.org/t/nix-flakes-is-an-experiment-that-did-too-much-at-once/32707>

⁴³⁰ <https://determinate.systems/posts/experimental-does-not-mean-unstable>

⁴³¹ <https://discourse.nixos.org/t/experimental-does-not-mean-unstable-detsyss-perspective-on-nix-flakes/32703>

⁴³² <https://www.youtube.com/watch?v=atmoYyBAhF4>

⁴⁴⁰ <https://edolstra.github.io/pubs/nspfsd-lisa2004-final.pdf>

⁴⁴¹ <https://wiki.haskell.org/File:Sgf-logo-blue.png>

⁴⁴² <https://nix-dev.science.uu.narkive.com/VDaaP1BY/nix-logo>

⁴⁴³ <https://nix.dev/manual/nix/2.22/command-ref/nix-channel>

⁴⁴⁴ <https://github.com/NixOS/nixpkgs/blob/master/CONTRIBUTING.md#branch-conventions>

Stable

Stable releases receive conservative updates to fix bugs or security vulnerabilities; otherwise package versions are not changed. A new stable release is made every six months.

- On Linux (including NixOS and WSL), use `nixos-*`⁴⁴⁵.

These branches point to commits where most Linux packages got pre-built and can be fetched from the binary cache. Furthermore, these commits passed the full NixOS test suite.

- On macOS/Darwin, use `nixpkgs-*-darwin`⁴⁴⁶

These branches point to commits where most Darwin packages got pre-built and can be fetched from the binary cache.

- On any other platform it doesn't matter which one of the above is used.

Hydra doesn't pre-build any binaries for other platforms.

All of these “channel branches” follow the corresponding `release-*`⁴⁴⁷ branch.

Example

`nixos-23.05` and `nixpkgs-23.05-darwin` are both based on `release-23.05`.

Rolling

Rolling releases follow `master`⁴⁴⁸, the main development branch.

- On Linux (including NixOS and WSL), use `nixos-unstable`⁴⁴⁹.
- On any other platform, use `nixpkgs-unstable`⁴⁵⁰.

`*-small`⁴⁵¹ channel branches have passed a smaller test suite, which means they are more up-to-date with respect to their base branch, but offer fewer stability guarantees.

5.2.4 Are there any impurities left in sandboxed builds?

Yes. There is:

- CPU architecture—great effort is being made to avoid compilation of native instructions in favour of hardcoded supported ones.
- System's current time/date.
- The filesystem used for building (see also `TMPDIR`⁴⁵²).
- Linux kernel parameters, such as:
 - IPv6 capabilities⁴⁵³.
 - binfmt interpreters, e.g., those configured with `boot.binfmt.emulatedSystems`⁴⁵⁴.
- Timing behaviour of the build system—a parallel Make build may not get the correct inputs in some cases.
- Insertion of random values, e.g., from `/dev/random` or `/dev/urandom`.

⁴⁴⁵ <https://github.com/NixOS/nixpkgs/branches/all?query=nixos->

⁴⁴⁶ <https://github.com/NixOS/nixpkgs/branches/all?query=nixpkgs->

⁴⁴⁷ <https://github.com/NixOS/nixpkgs/branches/all?query=release->

⁴⁴⁸ <https://github.com/NixOS/nixpkgs/branches/all?query=master>

⁴⁴⁹ <https://github.com/NixOS/nixpkgs/branches/all?query=nixos-unstable>

⁴⁵⁰ <https://github.com/NixOS/nixpkgs/branches/all?query=nixpkgs-unstable>

⁴⁵¹ <https://github.com/NixOS/nixpkgs/branches/all?query=-small>

⁴⁵² <https://nix.dev/manual/nix/stable/command-ref/env-common.html#env-TMPDIR>

⁴⁵³ <https://github.com/NixOS/nix/issues/5615>

⁴⁵⁴ <https://search.nixos.org/options?show=boot.binfmt.emulatedSystems>

- Differences between Nix versions. For instance, a new Nix version might introduce a new environment variable. A statement like `env > $out` is not promised by Nix to result in the same output, going into the future.

CONTRIBUTING

6.1 How to contribute

The Nix ecosystem is developed by many volunteers and a few paid developers, maintaining one of the largest open source software distributions in the world. Keeping it working and up to date – and improving it continuously – would not be possible without your support.

This guide shows how you can contribute to *Nix*, *Nixpkgs* or *NixOS*. It assumes that you’re already somewhat proficient with basic concepts and workflows, which are outlined in the *beginner tutorial series* (page 3). The most important aspects are *the Nix language* (page 12), the various Nixpkgs mechanisms for *constructing derivations to build software* (page 40), *the module system* (page 72), and *NixOS integration tests* (page 105).

Important

If you cannot contribute time, consider [donating to the NixOS Foundation on Open Collective](https://opencollective.com/nixos)⁴⁵⁵.

Currently the focus is on [funding in-person events](https://github.com/NixOS/funding)⁴⁵⁶ to share knowledge and grow the community of developers proficient with Nix. With enough budget, it would be possible to pay for ongoing maintenance and development of critical infrastructure and code – demanding work that we cannot expect to be done by volunteers indefinitely.

6.1.1 Getting started

Start by asking informed questions, after reading *reference documentation* (page 153) and the code relevant to what you care about.

Join our [community communication platforms](https://nixos.org/community)⁴⁵⁷ to get in contact with other users and developers. Check out and consider participating in our [community teams](https://nixos.org/community/#governance-teams)⁴⁵⁸ if you’re interested in a particular topic.

All the source code and documentation is on [GitHub](https://github.com/NixOS)⁴⁵⁹, and you need a GitHub account to propose changes. Technical discussions happen in issue and pull request comments.

Tip

If you are new to Nix, consider [contributing documentation](https://nixos.org/manual/nixos/chapter-17) (page 171) first.

This is where we need the most help and where it is the easiest to begin.

Documentation and contribution guides are often incomplete or outdated, much as we would like them to be otherwise. We’re working on it. You can help and improve the situation for everyone by immediately solving problems with the contribution workflow as you encounter them. This may slow you down with addressing your original concern. But it will make it a lot easier for anyone to make meaningful contributions in the future. And it will lead to better code and documentation in the long run.

⁴⁵⁵ <https://opencollective.com/nixos>

⁴⁵⁶ <https://github.com/NixOS/funding/issues?q=is%3Aissue%20label%3Afunding-request%20>

⁴⁵⁷ <https://nixos.org/community>

⁴⁵⁸ <https://nixos.org/community/#governance-teams>

⁴⁵⁹ <https://github.com/NixOS>

6.1.2 Report an issue

Note

For asking general questions about the code or how to do things, please use our [community communication platforms](#)⁴⁶⁰

To state technical problems and propose solutions, open GitHub issues and close them when the problem is resolved or invalidated.

We can only fix issues that we know of, so please report any issue you encounter.

- Report issues with *Nix* (including the [Nix reference manual](#)⁴⁶¹) at <https://github.com/NixOS/nix/issues>.
- Report issues with *Nixpkgs* or *NixOS* (including packages, configuration modules, the [Nixpkgs manual](#)⁴⁶², and the [NixOS manual](#)⁴⁶³) at <https://github.com/NixOS/nixpkgs/issues>.

Make sure that there is not already an open issue for your problem. Please follow the issue template and fill in all requested information.

Take particular care to provide a minimal, easy-to-understand example to reproduce the problem you are facing. You should also show what you have found in attempts to solve the problem yourself. This makes it much more likely for the issue to be resolved eventually, and is important for multiple reasons:

- A reproducible sample is concise and unambiguous.
This helps with triaging issues, understanding the problem, finding the root cause, and developing a solution. Your preliminary research further helps maintainers with analysis.
- It allows anyone to determine if the issue is still relevant.
Issues can remain unaddressed for a long time. Deciding what to do with them, even after months or years have passed, requires checking if the underlying problem persists or was resolved. This has to be easy to do: then anyone can help out with triaging, and notify maintainers to close or re-prioritise issues.
- The sample can be used for a regression test when solving the problem.

Tip

Ideally you would also propose or sketch a solution. The perfect issue is, in fact, a pull request that solves the problem directly and ensures with tests that it cannot occur again.

Important

Please open issues to request new features (such as packages, modules, commands, ...) only if you are willing and able to implement them yourself. Then the issue can be used to gauge user interest, to determine if the feature fits into the project, and to discuss implementation strategies.

6.1.3 Contribute to Nix

Nix is the cornerstone of the ecosystem, and is mostly written in C++.

If you want to help with development, check the [contributing guide in the Nix repository on GitHub](#)⁴⁶⁴.

⁴⁶⁰ <https://nixos.org/community>

⁴⁶¹ <https://nix.dev/manual/nix/stable>

⁴⁶² <https://nixos.org/manual/nixpkgs/stable>

⁴⁶³ <https://nixos.org/manual/nixos/stable>

⁴⁶⁴ <https://github.com/NixOS/nix/blob/master/CONTRIBUTING.md>

6.1.4 Contribute to Nixpkgs

Tip

For a verbal introduction, watch the NixCon 2024 talk [Becoming a Nixpkgs Contributor](#)⁴⁶⁵.

Nixpkgs is a large software project with various areas of development. You can find inspiration for things to improve in the *Nixpkgs* issue tracker⁴⁶⁶.

If you want to help, start with the [contributing guide](#) in the *Nixpkgs* repository on GitHub⁴⁶⁷ to get an overview of the code and the contribution process. There are also [programming-language-specific instructions](#)⁴⁶⁸ for adding packages.

6.1.5 Contribute to NixOS

NixOS is a collectively developed Linux distribution that can be configured conveniently in a highly flexible way through declarative programming interfaces. The code for modules and default configurations is in the *nixos* directory of the *nixpkgs* GitHub repository⁴⁶⁹.

See the *NixOS* manual's [development section](#)⁴⁷⁰ to get started with making improvements. Contributor documentation specific to *NixOS* is still lacking, but most conventions for *Nixpkgs* [contributions](#) (page 169) apply. Help with improving that is greatly appreciated.

Check [issues](#) labeled `good-first-bug`⁴⁷¹ if you're a new contributor. If you know your way around, working on popular issues⁴⁷² will be highly appreciated by other *NixOS* users.

6.2 How to get help

If you prepared a pull request and need help moving forward, check [contributing-how-to-get-help](#)⁴⁷³ for more information.

6.3 How to get help

If you need assistance with one of your contributions, there are a few places you can go for help.

6.3.1 How to find maintainers

For better efficiency and a higher chance of success, you should try contacting individuals or groups with more specific knowledge first:

- If your contribution is for a package in *Nixpkgs*, look for its maintainers in the `maintainers`⁴⁷⁴ attribute.
- Check if any teams are responsible for the relevant subsystem:
 - On the *NixOS* website⁴⁷⁵.

⁴⁶⁵ <https://www.youtube.com/watch?v=eijTOBBbCv4>

⁴⁶⁶ <https://github.com/NixOS/nixpkgs/issues?q=is%3Aopen+is%3Aissue+-label%3A%22topic%3A+nixos%22+-label%3A%22topic%3A+module+system%22+-label%3A%22topic%3A+nixos-container%22+sort%3Areactions-2B1-desc>

⁴⁶⁷ <https://github.com/NixOS/nixpkgs/blob/master/CONTRIBUTING.md>

⁴⁶⁸ <https://nixos.org/manual/nixpkgs/unstable/#chap-language-support>

⁴⁶⁹ <https://github.com/NixOS/nixpkgs/tree/master/nixos>

⁴⁷⁰ <https://nixos.org/manual/nixos/stable/index.html#ch-development>

⁴⁷¹ <https://github.com/NixOS/nixpkgs/issues?q=is%3Aopen+label%3A%22skill%3A+good-first-bug%22+label%3A%22topic%3A+nixos%22>

⁴⁷² <https://github.com/NixOS/nixpkgs/issues?q=is%3Aopen+is%3Aissue+label%3A%22topic%3A+nixos%22+sort%3Areactions-2B1-desc>

⁴⁷³ <https://nix.dev/contributing/how-to-get-help#contributing-how-to-get-help>

⁴⁷⁴ <https://nixos.org/manual/nixpkgs/stable/#var-meta-maintainers>

⁴⁷⁵ <https://nixos.org/community/#governance-teams>

- In the list of Nixpkgs maintainer teams⁴⁷⁶.
- In the CODEOWNERS files for Nixpkgs⁴⁷⁷ or Nix⁴⁷⁸.
- Check the output of `git blame`⁴⁷⁹ or `git log`⁴⁸⁰ for the files you need help with. Take note of the email addresses of people who committed relevant code.

6.3.2 Which communication channels to use

Once you’ve found the people you’re looking for, you can contact them on one of the [community communication platforms](#)⁴⁸¹:

- [GitHub](#)⁴⁸²

All the source code is maintained on GitHub. This is the right place to discuss implementation details.

In issue comments or pull request descriptions, [mention the GitHub username](#)⁴⁸³ found in the `maintainers-list.nix` file⁴⁸⁴.

- [Discourse](#)⁴⁸⁵

Discourse is used for announcements, coordination, and open-ended questions.

Try the GitHub username found in the `maintainers-list.nix` file⁴⁸⁶ to mention or directly contact a specific user. Note that some people use a different username on Discourse.

- [Matrix](#)⁴⁸⁷

Matrix is used for short-lived, timely exchanges, and direct messages.

To contact a maintainer, use their Matrix handle found in the `maintainers-list.nix` file⁴⁸⁸. If no Matrix handle is present for a specific maintainer, try searching for their GitHub username, as most people tend to use the same one across channels.

Maintainer teams sometimes have their own public Matrix room.

- Email

Use email addresses found with `git log`.

- Meetings and events

Check the [official NixOS Calendar](#)⁴⁸⁹ and the [Discourse community calendar](#)⁴⁹⁰ for real-time or in-person events. Some community teams hold regular meetings and publish their meeting notes.

6.3.3 Other venues

If you haven’t found any specific users or groups that could help you with your contribution, you can resort to asking the community at large, using one of the following official communication channels:

- A room related to your question in the [NixOS Matrix space](#)⁴⁹¹.

⁴⁷⁶ <https://github.com/NixOS/nixpkgs/blob/master/maintainers/team-list.nix>

⁴⁷⁷ <https://github.com/NixOS/nixpkgs/blob/master/ci/OWNERS>

⁴⁷⁸ <https://github.com/NixOS/nix/blob/master/.github/CODEOWNERS>

⁴⁷⁹ <https://git-scm.com/docs/git-blame>

⁴⁸⁰ <https://www.git-scm.com/docs/git-log>

⁴⁸¹ <https://nixos.org/community>

⁴⁸² <https://github.com/nixos>

⁴⁸³ <https://docs.github.com/en/get-started/writing-on-github/getting-started-with-writing-and-formatting-on-github/basic-writing-and-formatting-syntax#mentioning-people-and-teams>

⁴⁸⁴ <https://github.com/NixOS/nixpkgs/blob/master/maintainers/maintainer-list.nix>

⁴⁸⁵ <https://discourse.nixos.org>

⁴⁸⁶ <https://github.com/NixOS/nixpkgs/blob/master/maintainers/maintainer-list.nix>

⁴⁸⁷ <https://matrix.to/#/#community:nixos.org>

⁴⁸⁸ <https://github.com/NixOS/nixpkgs/blob/master/maintainers/maintainer-list.nix>

⁴⁸⁹ <https://calendar.google.com/calendar/u/0/embed?src=b9o52fobqjak8oq8lfkhg3t0qg@group.calendar.google.com>

⁴⁹⁰ <https://discourse.nixos.org/t/community-calendar/18589>

⁴⁹¹ <https://matrix.to/#/#community:nixos.org>

- The *Help* category⁴⁹² on Discourse.
- The general `#nix`⁴⁹³ room on Matrix.

6.4 Contributing documentation

Thank you for your interest in helping improve documentation in the Nix ecosystem.

6.4.1 Getting started

Check the overview of *documentation resources* (page 172). Documentation contributions should follow the *style guide* (page 175).

Get in touch with the *Nix documentation team*⁴⁹⁴ if you need more guidance.

Important

If you cannot contribute time, consider *donating to the NixOS Foundation's documentation project on Open Collective*⁴⁹⁵ to fund ongoing maintenance and development of reference documentation and learning materials.

6.4.2 Feedback

Feedback is also a valuable contribution. Please share your thoughts in the *Documentation category on Discourse*⁴⁹⁶.

Nix beginners

Try to use official documentation as your primary resource, however incomplete it may appear.

Please open issues and report all problems or questions that arise. Also state your learning goals and the paths you have taken so far.

Sharing your first-hand experience will help guide our efforts and solve recurrent problems with documentation for you and everyone else.

Nix educators

You will probably have observed where learners get stuck most often, and which typical needs and questions they have. You may have your own written notes for classes, trainings, or presentations.

Please share your experience to help us improve upstream documentation and beginner materials, so you can focus on providing the best value to your students.

Domain experts using Nix

If you are proficient in applying Nix to a domain-specific problem, and want to share your expertise on best practices, please check the existing content.

- Does existing material on your subject meet your standards?
- How could we improve it?
- Is there a popular application of Nix's capabilities not yet covered?
- We would be glad to incorporate your insights.

⁴⁹² <https://discourse.nixos.org/c/learn/9>

⁴⁹³ <https://matrix.to/#/#nix:nixos.org>

⁴⁹⁴ <https://nixos.org/community/teams/documentation>

⁴⁹⁵ <https://opencollective.com/nixos/projects/nix-documentation>

⁴⁹⁶ <https://discourse.nixos.org/c/dev/documentation/25>

6.4.3 Licensing and attribution

When opening pull requests with your own contributions, you agree to licensing your work under [CC-BY-SA 4.0](https://creativecommons.org/licenses/by-sa/4.0/)⁴⁹⁷.

When adding material made by others, make sure it has a license that permits this. In that case, unambiguously state source, authors, and license in the newly added content. Ideally, notify the authors *before* using their work.

Add the original author as co-author⁴⁹⁸ to the first commit of your pull request, which should contain the original document verbatim, so we can track authorship and changes through version history.

Using free licenses other than CC-BY-SA 4.0 is possible for individual documents. By contributing changes to those documents you agree to license your work accordingly.

Note

If you have written a tutorial or guide related to Nix, please consider licensing it under CC-BY-SA 4.0. This will allow us to feature your work as official documentation if it complements or improves upon existing materials.

Documentation resources

This is an overview of documentation resources for Nix, Nixpkgs, and NixOS, with suggestions for how you can help to improve them.

Reference manuals

The reference manuals document interfaces and behavior, show examples, and define component-specific terms.

- *Nix reference manual* (page 154)

- [source](#)⁴⁹⁹
- [issues](#)⁵⁰⁰
- [pull requests](#)⁵⁰¹

- *Nixpkgs reference manual*⁵⁰²

- [source](#)⁵⁰³
- [issues](#)⁵⁰⁴
- [pull requests](#)⁵⁰⁵

- *NixOS reference manual*⁵⁰⁶

- [source](#)⁵⁰⁷
- [issues](#)⁵⁰⁸
- [pull requests](#)⁵⁰⁹

⁴⁹⁷ <https://creativecommons.org/licenses/by-sa/4.0/>

⁴⁹⁸ <https://docs.github.com/en/pull-requests/committing-changes-to-your-project/creating-and-editing-commits/creating-a-commit-with-multiple-authors>

⁴⁹⁹ <https://github.com/NixOS/nix/tree/master/doc/manual>

⁵⁰⁰ <https://github.com/NixOS/nix/issues?q=is%3Aopen+is%3Aissue+label%3Adocumentation>

⁵⁰¹ <https://github.com/NixOS/nix/pulls?q=is%3Aopen+is%3Apr+label%3Adocumentation>

⁵⁰² <https://nixos.org/manual/nixpkgs>

⁵⁰³ <https://github.com/NixOS/nixpkgs/tree/master/doc>

⁵⁰⁴ <https://github.com/NixOS/nixpkgs/issues?q=is%3Aopen+is%3Aissue+label%3A%226.topic%3A+documentation%22+-label%3A%226.topic%3A+nixos%22>

⁵⁰⁵ <https://github.com/NixOS/nixpkgs/pulls?q=is%3Aopen+is%3Apr+label%3A%226.topic%3A+documentation%22+-label%3A%226.topic%3A+nixos%22>

⁵⁰⁶ <https://nixos.org/manual/nixos>

⁵⁰⁷ <https://github.com/NixOS/nixpkgs/tree/master/nixos/doc/manual>

⁵⁰⁸ <https://github.com/NixOS/nixpkgs/issues?q=is%3Aopen+is%3Aissue+label%3A%226.topic%3A+documentation%22+label%3A%226.topic%3A+nixos%22+>

⁵⁰⁹ <https://github.com/NixOS/nixpkgs/pulls?q=is%3Aopen+is%3Apr+label%3A%226.topic%3A+documentation%22+label%3A%226.topic%3A+nixos%22+>

The respective manual sections are maintained by developers of the code being documented.

How to help:

- Add links to definitions, commands, options, etc. where only the name is mentioned
- Ensure consistent use of technical terms
- Check that examples are self-contained and follow best practices
- Expand on sections that appear incomplete

NixOS Wiki

NixOS Wiki⁵¹⁰ is a collection of NixOS user guides, configuration examples, and troubleshooting tips. It is meant to be complementary to the NixOS reference manual.

It is collectively edited by the NixOS user community.

How to help:

- Improve discoverability by adding categorisation and links to reference documentation
- Remove redundant or outdated information
- Add guides and sample configurations for your use cases

nix.dev

The purpose of nix.dev⁵¹¹ (source⁵¹²) is to orient beginners in the Nix ecosystem.

The documentation team maintains nix.dev as editors.

How to help:

- Work on open issues⁵¹³
- Review pull requests⁵¹⁴
- Add guides or tutorials following the proposed outline⁵¹⁵. New articles can be based on videos such as:
 - The Nix Hour⁵¹⁶ recordings
 - some of the ~100 NixCon⁵¹⁷ recordings
 - Nix video guides⁵¹⁸ by @jonringer.
 - Summer of Nix 2022 talks⁵¹⁹

Since writing a guide or tutorial is a lot of work, please make sure to coordinate with maintainers, for example by commenting on or opening an issue.

Discourse

Nix users exchange information and support each other on these Discourse categories:

- Help⁵²⁰

⁵¹⁰ <https://wiki.nixos.org/>

⁵¹¹ <https://nix.dev>

⁵¹² <https://github.com/nixos/nix.dev>

⁵¹³ <https://github.com/nixos/nix.dev/issues>

⁵¹⁴ <https://github.com/nixos/nix.dev/pulls>

⁵¹⁵ <https://github.com/NixOS/nix.dev/issues/572>

⁵¹⁶ <https://www.youtube.com/watch?v=wwV1204mCtE&list=PLyzwHTVJIRc8yjlX4VR4LU5A5O44og9in>

⁵¹⁷ <https://www.youtube.com/c/NixCon>

⁵¹⁸ <https://www.youtube.com/user/elitespartan117j27>

⁵¹⁹ https://www.youtube.com/playlist?list=PLt4-_lkyRrOMWyp5G-m_d1wtTcbBaOxZk

⁵²⁰ <https://discourse.nixos.org/c/learn/9>

- [Guides](#)⁵²¹
- [Links](#)⁵²²

How to help:

- Ask informed questions, show your work
- Answer other people's questions
- Address recurrent questions by updating or adding a NixOS Wiki article, nix.dev guide or tutorial, or one of the reference manuals.
- Encourage and help people to incorporate their insights into official documentation

Nix Pills

[Nix Pills](#)⁵²³ is a series of low-level tutorials on building software packages with Nix, showing in detail how Nixpkgs is made from first principles.

The Nix Pills are not actively maintained.

Documentation framework

We aim to build our documentation according to the [Diátaxis framework for technical documentation](#)⁵²⁴, which divides documentation into four categories:

- *Tutorials* (page 174)
- *Guides* (page 175)
- *Reference* (page 174)
- *Concepts* (page 175)

We've found that contributors struggle to understand the differences between these categories, and while we *strongly* recommend reading up on the Diátaxis framework, we can summarize them as follows:

Reference

Reference material should

- Focus on “what's there”, simply listing which functions, classes, etc. exist
- Use terse language, with the text and layout optimized for scanning and random access
- Show relevant and complete usage examples
- Link to related items for better discoverability

Tutorials

Tutorials walk the user through a particular activity to teach them about common tools and patterns in the ecosystem. While the activity itself is important, the goal is also to connect the dots between other things the reader has learned.

The structure of tutorials should minimise the cognitive load on learners, and actively avoid choices and opportunities for user errors.

⁵²¹ <https://discourse.nixos.org/c/howto/15>

⁵²² <https://discourse.nixos.org/c/links/12>

⁵²³ <https://nixos.org/guides/nix-pills/>

⁵²⁴ <https://diataxis.fr>

Guides

Guides are a list of steps showing how to achieve a specific goal or solve a specific problem. The goal is to help the reader reach a specific end, not understand the underlying theory or broader context.

A guide assumes that the reader already has the background to understand the topic at hand and therefore doesn't need to explain the introduction of each new concept.

Concepts

Concepts describe the internals of a piece of code or how to think about a particular idea or entity in the ecosystem. A concept can also describe the historical context behind why something works the way that it does today.

If you find yourself wanting to write about the nitty gritty details of how something works, you most likely want to write an explanation.

Guides vs. Tutorials

We find that contributors primarily struggle with the difference between a Guide and a Tutorial.

Here are several explanations to help you understand the difference.

- A guide is used in a “working” context where the reader just wants a sequence of instructions to achieve an outcome.
 - In this context the reader may already know or may not care how or why these instructions work, they just want to know what to do to achieve the desired result.
- A tutorial is used in a “learning” context where the reader is following a sequence of instructions to gain practice performing a certain task.
 - Some small bits of motivation or explanation are helpful in this context to help a reader connect the dots with other things they may have already learned, but the focus is on the activity, not on *how* or *why*.

A helpful analogy is landing an airplane in two different contexts.

Let's say the pilot is unconscious and you now have to land the plane to avoid a crash landing. In this context you just want to know how not to die. You don't care about how or why, you just want to be on the ground in one piece. This is the context for a guide.

A pilot training in a flight simulator wants to practice landing the plane. The pilot-in-training needs practice knowing when to deploy the landing gear, when to adjust flaps, etc. Actually landing the plane during the flight simulation is less important than learning the individual skills that make up a successful landing. This is the context for a tutorial.

Finally, one last way of thinking about the difference between a how-to guide and a tutorial is like this:

- Guide: “step 1: do this, step 2: do that, etc”
- Tutorial: “take my hand as I show you how to do this”

Style guide

This document outlines the guidelines we use when writing documentation.

Writing style

Aim for clarity and brevity

I would have written a shorter letter, but I did not have the time.

— Blaise Pascal⁵²⁵

⁵²⁵ https://en.m.wikiquote.org/w/index.php?title=Blaise_Pascal&oldid=2978584#Quotes

Readers' time and attention are limited. Respect them.

The same holds for communication directed to contributors and maintainers: This is a public project, and many people will read what you write. Use this leverage with care.

- Follow the evidence-based [plain language guidelines](#)⁵²⁶.
 - Don't use jargon. Readers may not be familiar with particular technical terms.
 - Don't use long, complicated words if there are shorter, simpler words that convey the same meaning.
- Use the imperative voice when giving instructions. For example, write:

Add the `python310` package to `buildInputs`.

Don't use a conversational tone, as it distracts from the content. For example, don't write:

Going forward, let's now add the `python310` package to `buildInputs` as we have seen in the previous tutorial.

Use inclusive language

Adapted from [Contributor Covenant](#)⁵²⁷ and [The Carpentries Code of Conduct](#)⁵²⁸:

- Use welcoming and inclusive language
- Show empathy and respect towards other people
- Be respectful of different viewpoints and experiences
- Give and gracefully accept constructive criticism
- Focus on what is best for the community

Avoid idioms as they can be hard to understand for non-native English speakers.

Don't try to be funny. Humor is highly culturally sensitive. At best, jokes may obfuscate the relevant instructions. At worst, jokes may offend readers and invalidate our effort to help them learn.

Don't use references to popular culture. What you may consider well-known may be entirely obscure and distracting to people from different backgrounds.

Voice

Describe the subject factually and use the imperative voice in direct instructions.

Do not assume a personal relationship with readers, prefer clarity and brevity to emotional appeal.

Use "you" to refer to the reader and only use "we" to refer to the authors. Both should be rarely needed.

For example:

You will have to deploy secrets to the remote machine. We chose to show the explicit, manual process using `scp` here, but there are various tools to automate that.

Be correct, cite sources

The only thing worse than no documentation is *incorrect documentation*. One way to ensure correctness is by citing your sources. If you make a claim about how something works (e.g. that a command line argument exists), link to official documentation for that subject. We would like to maintain a network of documentation, so linking to other documentation helps to reinforce the documentation ecosystem.

It is explicitly encouraged to update or restructure the manuals where appropriate, to improve the overall experience.

⁵²⁶ <https://www.plainlanguage.gov/guidelines/>

⁵²⁷ https://github.com/EthicalSource/contributor_covenant/blob/cd7fcf684249786b7f7d47ba49c23a6bcb3233eb/content/version/2/1/code_of_conduct.md

⁵²⁸ <https://github.com/carpentries/docs.carpentries.org/blob/fb188fa8d7f57ad85eb525091e335ed0d8fea16d/source/policies/coc/index.md#L13-L19>

Markup and source

Code samples

Always motivate code before showing it, describing in words what it is for or what it will do.

Counter-example

Run this command:

```
```bash
:(){ :|:& };:
```
```

Non-trivial examples may need additional explanation, especially if they use concepts from outside the given context. Use a collapsed content box for explanation that would distract from the reading flow.

Example

Set off a **[fork bomb]** (https://en.wikipedia.org/wiki/Fork_bomb):

```
```bash
:(){ :|:& };:
```
```

:::{dropdown} Detailed explanation

This Bash command defines and executes a function ``:`` that recursively spawns  copies of itself, quickly consuming system resources.

```
:::
```

Always explain code in the text itself. Use comments in code samples very sparingly, for instance to highlight a particular aspect.

Readers tend to glance over large amounts of code when scanning for information, even if most of it is comments. Especially beginners will likely find reading more complex-looking code strenuous and may therefore avoid it altogether.

If a code sample appears to require a lot of inline explanation, consider replacing it with a simpler one. If that's not possible, break the example down into multiple parts, explain them separately, and then show the combined result at the end.

Code samples that are *intended* to work should work.

If you are going to present an example that does not work (e.g. you're illustrating a common mistake) explain this beforehand. Many readers will get stuck trying to make example code work without reading ahead to find out that the code isn't intended to work.

Code samples should all include a programming language when applicable for syntax highlighting when rendered, e.g.:

```
```python
print("Hello, World!")
```
```

Headers

Reserve the largest header (#) for the title.

Use Markdown headers ## through ### to divide up content in the body of the document. Finer-grained headings are not necessarily better.

One line per sentence

Write one sentence per line.

This makes long sentences immediately visible. It also makes it easier to review changes and provide direct suggestions, since the GitHub review interface is line-oriented.

Links

Use [reference links](#)⁵²⁹ – sparingly – to ease source readability. Put definitions close to their first use.

Example

```
We follow the [Diátaxis] (https://diataxis.fr/) approach to structure_
→ documentation.
This framework distinguishes between [tutorials], [guides], [reference], and_
→ [explanation].

[tutorials]: https://diataxis.fr/tutorials/
[guides]: https://diataxis.fr/how-to-guides/
[reference]: https://diataxis.fr/reference/
[explanation]: https://diataxis.fr/explanation/
```

Unless explicitly required to point to the latest version of an external resource, all references should be [permanent links](#)⁵³⁰.

Many web services offer permalinks, such as:

- [GitHub URLs to specific commits](#)⁵³¹
- [Wikipedia URLs to specific page versions](#)⁵³²
- [Internet Archive “Save Page Now” for persisting web pages](#)⁵³³

How to write a tutorial

This is a guide to writing tutorials about Nix.

By tutorials we mean *lessons* as described in the [Diátaxis framework for technical documentation](#)⁵³⁴, and recommend becoming familiar with Diátaxis before proceeding. Especially note [the difference between tutorials and guides](#)⁵³⁵.

Target audience

The main target audience of Nix tutorials are software developers with at least basic experience on the Linux command line.

⁵²⁹ <https://github.github.com/gfm/#reference-link>

⁵³⁰ <https://en.wikipedia.org/wiki/Permalink>

⁵³¹ <https://docs.github.com/en/repositories/working-with-files/using-files/getting-permanent-links-to-files>

⁵³² https://en.wikipedia.org/wiki/Wikipedia:Linking_to_Wikipedia#Permanent_links_to_old_versions_of_pages

⁵³³ <https://web.archive.org/save>

⁵³⁴ <https://diataxis.fr/>

⁵³⁵ <https://diataxis.fr/tutorials-how-to/>

Experts answering questions immediately, personalised instructions and training, and other forms of apprenticeship are known to be the most effective support for learning Nix. **These tutorials are targeted at those who don't have access to any of that**, and should therefore be written to be suitable for self-directed learning. This is achieved by following the structure outlined here, which is primarily characterised by aiming to avoid and close all information gaps for the learner.

As a byproduct, a well-written tutorial will be useful as lecture notes for use in interactive training sessions. Therefore, the secondary target audience are instructors teaching Nix.

Process

Writing a high-quality tutorial takes some time – for you and others. Most of that time is typically spent collaboratively:

- Figuring out the right approach
- Ensuring that the instructions are neither too sparse nor too dense for learners
- Finding ever-more succinct and clear ways to convey ideas

Follow these steps to avoid redoing work

Pick a topic

There is a [tracking issue](#)⁵³⁶ for tutorials that the documentation team has decided should exist as part of the tutorial series. Pick an issue that covers a topic that you're either knowledgeable about or have a particular interest in.

Check referenced issues and pull requests to make sure you won't duplicate work that someone else has already started.

There are more [tutorial requests](#)⁵³⁷ than captured in the outline. [Open a new issue](#)⁵³⁸ if what you wanted to work on isn't tracked anywhere. This is an opportunity for you to clarify your goals, and an opportunity for everyone else to find out that there's interest in that subject.

Submit a pull request with an outline

Submit a pull request with an outline of the tutorial following [our recommended structure](#) (page 179). The outline should contain bullet points on each section's content. Reference the tracking issue from the pull request description to announce that you're working on a tutorial.

A review will ensure you're going in the right direction in terms of learning objectives and technical implementation.

Expand on the outline

Elaborate the contents of the tutorial following your outline and the [Style guide](#) (page 175).

A review will ensure that you get all the required information in the right order without overwhelming learners.

Follow up on review comments

Revise your tutorial based on the detailed feedback. We recommend testing your tutorial with friends or coworkers. This will both help with revealing implicit prerequisites as well as provide a realistic estimate of the reading time.

A final review will check that everything is technically correct.

Structure

Each tutorial should answer the following questions.

In addition, we strongly recommend the book [How Learning Works \(summary\)](#)⁵³⁹ as a guide for designing learning materials.

⁵³⁶ <https://github.com/NixOS/nix.dev/issues/572>

⁵³⁷ <https://github.com/NixOS/nix.dev/issues?q=is%3Aopen+is%3Aissue+label%3Atutorial>

⁵³⁸ <https://github.com/NixOS/nix.dev/issues/new?&template=tutorial.md>

⁵³⁹ <https://www.lesswrong.com/posts/mAdMkFqWzbJRB544m/book-review-how-learning-works>

What will you learn?

Describe the problem statement and learning goals.

The learning goal of a tutorial is always acquiring a skill, which is distinguished by being applicable to a set of situations with recurrent patterns.

What do you need?

State the prerequisite knowledge and skills. The tutorial should always be written such that the stated prerequisites are sufficient to achieve the learning goals.

Examples:

- links to previous chapters
- domain-specific skills or knowledge

How long does it take?

Estimate the reading time. This is important for learners to make sure they have the capacity to achieve the planned tasks and thus avoid frustration that may prevent them from continuing on their journey into the Nix ecosystem.

The estimate will depend on the learner's pre-existing knowledge and proficiency. You can note how optional skills or knowledge may influence reading time.

What to do?

Provide steps to achieve the learning goal. These should take the form of direct instructions which repeatably lead to the desired outcome.

It is also worthwhile to add contextual explanations within `::: {dropdown}` blocks. This can help with understanding while keeping distractions minimal.

What did you learn?

Provide exercises or worked examples, and other means of self-assessment.

This is also a good place to offer the readers ways to give feedback or ask the authors questions to continue improving the tutorial.

Next steps

Depending on how well a use case is explored, point the reader to

- reference manuals
- guides or other tutorials
- links to known-good external resources, with summaries
- overview of available support tools, and their state of maturity and maintenance
- overview of ideas, and the state of community discussion.

We recommend making an explicit separation of practical from theoretical learning resources, as then readers will be able to quickly decide to either get things done or learn more.

External resources should have a summary to set expectations, ideally including reading time. Blog posts should have their original title in the link, and (`<author>`, `<year>`): Give authors credit, give readers an idea of how up to date the information is.

ACKNOWLEDGEMENTS

7.1 Sponsoring

The following people and organisations have contributed to make this effort possible:

- [@fricklerhandwerk](#)⁵⁴⁰ serves as the team lead since 2023-02, sponsored by [Antithesis](#)⁵⁴¹ from 2023-02 to 2024-04
- [@zmitchell](#)⁵⁴² led the Learning Journey Working Group from 2023-03 to 2023-08, sponsored by [flox](#)⁵⁴³
- [@infinisil](#)⁵⁴⁴ worked on the team between 2022-11 and 2024-05, sponsored by [Tweag](#)⁵⁴⁵
- [@lucperkins](#)⁵⁴⁶ served as the team lead from 2022-11 to 2023-01, sponsored by [Determinate Systems](#)⁵⁴⁷
- [@fricklerhandwerk](#)⁵⁴⁸ served as the team lead from 2022-05 to 2022-10, sponsored by [Tweag](#)⁵⁴⁹

7.2 History

Many thanks to past contributors, who helped make Nix documentation what it is today:

- [@infinisil](#)⁵⁵⁰ helped lead the team between 2022-11 and 2024-05. During that time he provided diligent technical reviews of countless contributions, reworked the [contribution guides for Nixpkgs](#)⁵⁵¹, and rewrote his [module system tutorial](#)⁵⁵² for publication.
- [@olafklingt](#)⁵⁵³ volunteered on the team from 2022-10 to 2024-05, and was a formal member between 2022-10 and 2024-05. He added an [introduction to NixOS virtual machines](#)⁵⁵⁴ and greatly simplified the [tutorial on NixOS VM tests](#)⁵⁵⁵, and kept them up to date. Both articles enjoy great popularity and are central elements of our tutorial series.
- [@brianmcgee](#)⁵⁵⁶ was part of the team from 2023-03 to 2023-10 and contributed to the Learning Journey Working Group effort.

⁵⁴⁰ <https://github.com/fricklerhandwerk>

⁵⁴¹ <https://antithesis.com>

⁵⁴² <https://github.com/zmitchell>

⁵⁴³ <https://floxdev.com>

⁵⁴⁴ <https://github.com/infinisil>

⁵⁴⁵ <https://tweag.io>

⁵⁴⁶ <https://github.com/lucperkins>

⁵⁴⁷ <https://determinate.systems>

⁵⁴⁸ <https://github.com/fricklerhandwerk>

⁵⁴⁹ <https://tweag.io>

⁵⁵⁰ <https://github.com/infinisil>

⁵⁵¹ <https://github.com/NixOS/nixpkgs/blob/master/CONTRIBUTING.md>

⁵⁵² <https://nix.dev/tutorials/module-system/deep-dive>

⁵⁵³ <https://github.com/olafklingt>

⁵⁵⁴ <https://nix.dev/tutorials/nixos/nixos-configuration-on-vm>

⁵⁵⁵ <https://nix.dev/tutorials/nixos/integration-testing-using-virtual-machines>

⁵⁵⁶ <https://github.com/brianmcgee>

- @zmitchell⁵⁵⁷ led the [Learning Journey Working Group](#)⁵⁵⁸ from 2023-03 to 2023-08 that added a number of tutorials. He published [regular updates on developments in documentation](#)⁵⁵⁹ in that period.
- @Mic92⁵⁶⁰ was a founding member and part of the team from 2022-05 to 2023-01. Jörg had written a great deal of documentation on the NixOS Wiki, and shared his experience to set a direction for the documentation team.
- @domenkozar⁵⁶¹ was a founding member and part of the team from 2022-05 to 2023-01. Domen originally started nix.dev, wrote many basic tutorials, and funded editorial work through [Cachix](#)⁵⁶². He helped bootstrap the documentation team, handed out permissions, and advised us on many aspects. Domen donated nix.dev to the NixOS Foundation in 2023-07.

⁵⁵⁷ <https://github.com/zmitchell>

⁵⁵⁸ https://discourse.nixos.org/search?q=learning%20journey%20working%20group%20-%20meeting%20notes%20in%3Atitle%20order%3Alatest_topic

⁵⁵⁹ https://discourse.nixos.org/search?q=This%20Month%20in%20Nix%20Docs%20in%3Atitle%20before%3A2023-10-30%20order%3Alatest_topic

⁵⁶⁰ <https://github.com/Mic92>

⁵⁶¹ <https://github.com/domenkozar>

⁵⁶² <https://www.cachix.org/>

N

- Nix, [153](#)
- Nix expression, [153](#)
- Nix file, [153](#)
- Nix language, [153](#)
- NixOS, [154](#)
- Nixpkgs, [153](#)